

# ADDENDUM NO. 1

**June 13, 2024**

## **PORTER COUNTY HIGHWAY DEPARTMENT – CENTRAL FACILITY**

### **TO: ALL BIDDERS OF RECORD**

This Addendum forms a part of and modifies the Bidding Requirements, Contract Forms, Contract Conditions, the Specifications, and the Drawings dated May 24, 2024 by A & Z Engineering and MartinRiley. Acknowledge receipt of the Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.

This Addendum consists of Page ADD 1-1 through ADD 1-4, revised Specification Section 00 20 00 – Information Available to Bidders, attached Addendum No. 1 from A & Z Engineering, consisting of 1 page and 8 drawings, and attached Addendum No. 1 from MartinRiley, consisting of 4 pages, Specification Sections 00 01 10 - Table of Contents, 07 42 13 – Metal Wall Panels, 07 71 00 - Roof Specialties, 10 28 00 - Toilet, Bath, and Laundry Accessories, 11 11 19 - Vehicle Lubrication Equipment, 23 31 00 - HVAC Ducts and Castings, 41 22 00 - Hoists and Cranes, and 13 Drawings.

### **A. SPECIFICATION SECTION 00 00 20 – TABLE OF CONTENTS**

1. Under Section 00 20 00 Information Available to Bidders

**ADD:**

Geotechnical Report

2. **ADD:**

Specification Section 09 77 00 – Prefinished Wall Panels  
Specification Section 10 26 01 – Wall and Corner Guards

### **DIVISION 3 - CONCRETE**

1. **REVISE:**

Specification Section 03 30 00 – Cast-In-Place Concrete

**TO READ:**

Specification Section 03 30 00 – Cast-In-Place Concrete (Refer to S001)

### **DIVISION 4 - MASONRY**

1. **REVISE:**

Specification Section 04 20 00 – Unit Masonry

**TO READ:**

Specification Section 04 20 00 – Unit Masonry (Refer to S001)

### **DIVISION 5 - METALS**

1. **REVISE:**

Specification Section 05 12 00 – Structural Steel Framing

Specification Section 05 21 00 – Steel Joist Framing

Specification Section 05 31 00 – Steel Decking

**TO READ:**

Specification Section 05 12 00 – Structural Steel Framing (Refer to S001)

Specification Section 05 21 00 – Steel Joist Framing (Refer to S001)

Specification Section 05 31 00 – Steel Decking (Refer to S001)

### **DIVISION 7 – THERMAL AND MOISTURE PROTECTION**

1. **ADD:**

Specification Section 07 71 00 – Roof Specialties

## **DIVISION 9 - FINISHES**

### **1. ADD:**

Specification Section 09 77 00 – Prefinished Wall Panels

## **DIVISION 10 - SPECIALTIES**

### **1. ADD:**

Specification Section 10 26 01 – Wall and Corner Guards

## **B. SPECIFICATION SECTION 01 12 00 - MULTIPLE CONTRACT SUMMARY**

### **BID CATEGORY NO. 1 – GENERAL TRADES/SITEWORK**

#### **1. ADD:**

Specification Section 09 77 00 – Prefinished Wall Panels

Specification Section 10 26 01 – Wall and Corner Guards

### **BID CATEGORY NO. 3 – ROOFING**

#### **1. ADD:**

Specification Section 07 71 00 - Roofing

### **BID CATEGORY NO. 7 – PLUMBING**

#### **1. DELETE:**

Specification Section 22 15 00 – General-Service Compressed-Air Systems

### **BID CATEGORY NO. 8 – MECHANICAL**

#### **1. ADD:**

Specification Section 22 15 00 – General-Service Compressed-Air Systems

C. **SPECIFICATION SECTION 01 52 60 – RUBBISH CONTAINER**

Under 1.02 RUBBISH CONTAINER

1. **REVISE:**

- A. The **Bid Category No. 1 Contractor** is to provide One Hundred Eighty (70) thirty (30) CY rubbish containers for the Project waste, debris, and rubbish for the life of the project except as specified in 1.02.B and 1.02.C below.

**TO READ:**

- A. The **Bid Category No. 1 Contractor** is to provide Seventy (70) thirty (30) CY rubbish containers for the Project waste, debris, and rubbish for the life of the project except as specified in 1.02.B and 1.02.C below.

## **SECTION 00 20 00 - INFORMATION AVAILABLE TO BIDDERS**

- A. Subsurface Investigation Information: The Soils Exploration Report and Soil Boring Logs were prepared for the Owner by **GME Testing, 3517 Focus Dr., Fort Wayne, IN 46818, (260) 497-8127** for use in design. The following Subsurface Investigation Report is not a part of the construction Contract Documents and is enclosed within this document for informational use only. The Architect/Engineer and Construction Manager do not accept responsibility for the information contained in the report.
1. The enclosed report and Log of Borings, and any interpolations of conditions between test borings is not a warrant or guarantee by the Owner or Architect/Engineer of subsurface conditions.
  2. The Contractor should visit the site and acquaint himself with all existing conditions. Prior to bidding, bidders may make their own subsurface investigations to satisfy themselves as to the site and subsurface conditions, but such subsurface investigations shall be performed only under the time schedules and arrangements approved in advance by the Owner. Any additional information, needed by the Contractor, shall be obtained by the Contractor at no cost to the Owner.
- B. Structural design has been based on the report and assumes that existing soils are clean and can be compacted and will achieve the densities specified in the earthwork section. It shall be the Contractor's responsibility to determine for himself existing Site and or soil conditions.
- C. Existing Site Survey Information: A Site survey can be found within the construction drawings. It is not however, part of the Construction Contract Documents and is for informational use only. Information found is not a warrant or guarantee by the Owner or Project Consultant. The Contractor should visit the site and acquaint himself with all existing conditions. Any additional information, needed by the Contractor, shall be obtained by the Contractor at no cost to the Owner.
- D. Asbestos Report: The Asbestos Report (if applicable), prepared for the Owner, is not part of the Construction Documents, and is on file at the Owner's Office and is available for review upon written request. The Architect and Construction Manager do not accept responsibility for the information contained in the report.
- D. Lead Based Paint: Lead Based Paint Report (if applicable), prepared for the Owner, is not part of the Construction Documents, and is on file at the Owner's Office and is available for review upon written request. The Architect and Construction Manager do not accept responsibility for the information contained in the report.

END OF SECTION 00 20 00



# GME®

## GME TESTING

G R

P C H G

1955 IN-2

V, IN


January 3, 2024

### Prepared For:

A&Z Engineering, LLC  
1220 Ruston Pass  
Fort Wayne, IN 46825

### Prepared By:

GME Testing  
3517 Focus Dr  
Fort Wayne, IN 46818





January 3, 2024  
G23-112119

A&E ENGINEERING, LLC (A&E)  
1220 RIVERVIEW PARK  
FOWLER, IN 46825  
ARON J. ANASTAS, P.E. L. G. E.I.

REF SUBSURFACE EXPLORATION AND RECOMMENDATIONS  
P. C. H. G. I.  
1955 IN-2  
V. IN

Gentlemen:

In compliance with your request and authorization, **GME Testing** is pleased to submit this report on our subsurface exploration and recommendations for the above-referenced project.

We appreciate the opportunity to be of service on this project. Please contact us if you have any questions or require additional services.

Sincerely,  
GME T

Rami M. Anabtawi, P.E., BC.GE



Robert W. McMichael, P.E., GE, BC.GE

S M Naziur Mahmud, E.I.T.

CC: Jack Daniel, AIA – Martin Riley Architects,  
Andrew Vaughn, AIA – Martin Riley Architects

## **TABLE OF CONTENTS**

<b>1.0 INTRODUCTION.....</b>	<b>3</b>
1.1 Purpose and Scope of Work.....	3
1.2 Authorization.....	3
1.3 Site Location and Setting.....	3
1.4 Proposed Construction .....	6
<b>2.0 GME FIELD INVESTIGATION.....</b>	<b>8</b>
<b>3.0 GME LABORATORY TESTING PROGRAM .....</b>	<b>10</b>
<b>4.0 SUMMARY OF GEOTECHNICAL CONDITIONS AND ANALYSIS .....</b>	<b>10</b>
4.1 Surface Materials.....	12
4.2 Old Fill .....	12
4.3 Native Mineral Soils.....	13
4.4 Native Organic Soils .....	13
4.5 Groundwater.....	14
4.6 Seismicity Classification .....	15
<b>5.0 DESIGN RECOMMENDATIONS.....</b>	<b>16</b>
5.1 Ground Modification and Spread Footings in Building Areas .....	16
5.2 Grading and Earthwork in Exterior Areas .....	18
5.3 Truck Parking and/or Driveways Subgrade Areas .....	19
<b>6.0 CONSTRUCTION RECOMMENDATIONS.....</b>	<b>20</b>
6.1 Site Preparation.....	21
6.2 Engineered Fill.....	22
6.3 Temporary Excavations.....	22
6.4 Drainage and Groundwater Control.....	23
<b>7.0 LIMITATIONS.....</b>	<b>25</b>

### **APPENDIX A**

I. Field Exploration, II. Laboratory Testing, Exhibit A - Custom Soil Resource Report Exhibit B - Site Vicinity and Boring Location Map, Exhibit C – Geopier® Evaluation Letter

### **APPENDIX B**

Atterberg Limits, Grain Size Distribution, Boring Logs, General Notes, U.S. Seismic Design Map

## 1.0 INTRODUCTION

### 1.1 PURPOSE AND SCOPE

The purposes of our assignment were to evaluate the subsurface conditions and develop geotechnical recommendations. We anticipate that these will be used by the Owner's team in planning and performing the design and construction for the project. As discussed in this report, some additional geotechnical study may be needed.


### 1.2 AUTHORITY

Our services were performed according to our proposal (GMEP 23-070318) dated July 31, 2023. This proposal was accepted, and our work authorized on December 7, 2023.

### 1.3 SITE LOCATION AND SURROUNDINGS


The project is located at 1955 State Road 2 in Valparaiso. At the time of our field exploration, the site was occupied by several existing structures that will be demolished to allow for the proposed new construction planned on site. The Civil Plans, including the Grading and Drainage Plans, Demolition Plans, Utilities, etc. were not available for our review.

According to Quaternary Geologic Map of Indiana, Indiana Geological Survey Miscellaneous Map 49, Gray, H.H. (1989), the surficial geology at the Site consists of geologically recent "Muck". This material is aligned and associated with the channel of Salt Creek (Figure 1) and indicated in blue in Figure 1. The USDA Web Soil Survey furthermore detailed mapping of the muck and defines this as Adrian muck, Houghton muck, Riddles silt loam and Riddles loam deposits. A copy of the Custom Soil Resource Report of Porter County, Indiana is included as Exhibit A of this report.




F 1 S G M S B M L S

We researched various historical aerial photographs, topographic maps, and flood plain maps (from the Federal Emergency Management Agency, FEMA). Figure 2 presents excerpts from 1962 (photorevised 1980) and 2019 USGS topographic quadrangle maps for Valparaiso, with the location of the Site indicated. A comparison of these images reveals that the Site had been filled and leveled sometime after 1980 indicated. The contour interval is these maps is 10 feet.



F 2 C T M

Figure 3 presents the “FIRMETTE” for the Site as obtained from FEMA, with the location of the Site indicated. An examination of this photograph indicates that a fill pad was constructed over muck prior to the construction of the existing facility. That had the effect of raising most or much of the Site above such that it was in Zone X (Area of Minimal Flood Hazard). The area immediately to the east of the fill pad remains in a flood hazard zone, as does a “finger” of land that extends to the south of the Site.



F 3 FIRMETTE S S F P

#### 1.4 P C

The proposed construction features are shown in Figure 4 and include the following, with approximate plan dimensions. Each building will be single-story in height with no basement.

- ☐ Cold storage building (60 ft by 120 ft)
- ☐ Office building, (80 ft by 100 ft)
- ☐ Maintenance building (80 ft by 90 ft)
- ☐ Salt barn (65 ft by 85 ft)

Other Project construction will include:

- ☐ Truck parking
- ☐ Associated car parking and driveways.
- ☐ Aggregate storage bins and piles



No information regarding the structural systems was available and structural loadings are not known at this time. However, we anticipate these loads to be light to moderate, with maximum column, wall, and floor loadings no more than about 100 kips/column, 6 kips per linear foot for walls and 125 psf, respectively.

Given the existing site conditions as described in Section 1.3 as well as the results of our field and laboratory investigation (discussed in Section 2.0), the Site grading and drainage needs to be carefully planned. The conditions include the presence of a body of undocumented fill that was placed with no known engineering control over organic deposits and very loose sand. For this reason, fill slopes and/or retaining walls used to affect grade changes (e.g., at the edges of the fill pad) should be specifically designed for the conditions at those locations. This design should consider the various potential failure modes, including global stability. For the purpose of this report, we have assumed that GME has been provided with all necessary information to conduct the investigation. We have provided recommendations for subgrade preparation; however, the design and detailing of the pavement will be the responsibility of others.

Furthermore, proposed truck maneuvering and drive aisles will be constructed as a part of the project. Due to the nature of the facility, we anticipate that there will be repeated heavy truck traffic and that the pavements will be constructed of Portland cement concrete. Other pavement areas may be constructed of asphalt concrete. We have provided recommendations for subgrade preparation; however, the design and detailing of the pavement will be the responsibility of others.

For the purposes of this report, all floor slabs and foundations of the proposed cold storage building will be suitably protected against any frost penetration and extreme cold temperatures. This aspect of design should be checked by the design team. We understand that special provisions to address the potential for frost heave are being implemented into the design. Moreover, the proposed construction should be designed such that suitable installation thickness and

materials are used and the structural details must follow good industrial chiller building standards.

We realize that final plans may differ slightly from the initial understandings and available preliminary information reported. If significant changes occur or our assumptions are inaccurate, our office should be contacted to determine if any changes to our recommendations will be necessary after our review.

## **2.0 GME FIELD INVESTIGATION**

GME Testing coordinated their field work logistics, site access, utilities marking, and the geotechnical drilling program schedule with a representative of the client to conduct this geotechnical engineering investigation.

Our field exploration program consisted of drilling twenty-two (22) vertical soil test borings to depths of approximately 10 to 20-feet below the existing ground surface (bgs) as shown on the borehole logs.

The locations of the test borings were established in the field by GME Testing personnel based on a marked aerial plan provided by the client. The boring locations are tabulated in Table 1 and graphically depicted in Exhibit B of this report. We estimated the approximate existing surface elevations at our boring locations from GIS data and have included these on the boring logs (Appendix B). We recommend that A&Z's surveying department determine the site elevations.

T 1 S B					
D	B N	L	L	G E (E.),	B D,
Parking	B-01	41.450319	-87.073628	±696	±20
	B-02	41.450325	-87.073458	±696	±20
Cold Storage Building	B-03	41.450219	-87.073539	±697	±20
	B-04	41.450081	-87.073461	±697	±20
Maintenance Building	B-05	41.449658	-87.073300	±696	±10
	B-06	41.449792	-87.073897	±696	±10
	B-07	41.449764	-87.074144	±696	±20
Parking	B-08	41.449969	-87.073903	±697	±10
	B-09	41.449969	-87.074211	±696	±20
	B-10	41.449961	-87.074486	±696	±20
	B-11	41.449942	-87.074819	±697	±20
Office Building	B-12	41.449828	-87.074494	±696	±20
Parking	B-13	41.449753	-87.074853	±696	±10
	B-14	41.449753	-87.075228	±696	±10
Truck Parking	B-15	41.449592	-87.075042	±694	±10
	B-16	41.449586	-87.074725	±695	±10
	B-17	41.449661	-87.074508	±696	±10
	B-18	41.449358	-87.074611	±694	±10
	B-19	41.449428	-87.074858	±692	±10
	B-20	41.449431	-87.075222	±693	±10
Parking	B-21	41.449392	-87.074050	±694	±20
Salt Barn Building	B-22	41.449267	-87.073853	±693	±20

All depths and elevations referred to in this report are referenced from the ground surface existing at the time of this report was prepared, unless otherwise stated. The elevations presented on our borehole logs are considered accurate to  $\pm$  one (1) foot.

### **3.0 GME LABORATORY TESTING PROGRAM**

Representative soils collected using a split spoon sampler were subjected to laboratory testing according to ASTM and/or AASHTO standard specifications. Our laboratory testing program included performing ☐ visual soil classifications according to ASTM D-2487 and ASTM D-2488, ☐ natural moisture content tests according to ASTM D-2216 on all samples, ☐ unconfined compressive strength tests and calibrated spring hand penetration tests in general accordance with ASTM D-2166. The results of all laboratory tests are included on the respective plots in Appendix B. Additionally, grain size distribution and analyses (ASTM D-421, D-422, and D-1140), Loss-on-Ignition Test (ASTM D-2974), and Atterberg limit determinations (ASTM D-4318) were performed on representative samples.

Testing of old fills, soils, and groundwater for corrosivity characteristics or environmental contamination was not in the scope of our work and therefore was not performed. We recommend that the design and construction team address these concerns.

### **4.0 SUMMARY OF GEOTECHNICAL CONDITIONS AND ANALYSIS**

The geotechnical conditions of the site are summarized in the following paragraphs. **S**ince the site is located in an urban area, the geotechnical conditions are expected to be complex. **P**reliminary geotechnical analysis indicates that the planned design and construction is possible (feasible), it will be challenging and require a high attention to detail.

The poor conditions include old, undocumented fills. In places, these fills were placed directly over old organic soils. The natural soils include extensive loose sand deposits. **T**he geotechnical conditions are complex and the poor conditions are not always apparent from the surface. We provide our recommendations for support of structures in Section 5.0.

**T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. **T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. **T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands.

**T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. **T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. **T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. It should be expected that these areas are underlain by very weak organic soils. In some places, these will be hidden beneath old fills and may escape detection during earthwork operations.

Exterior pavement areas can be rendered suitable for traffic. However, long-term compression of deeper organic soils may occur, especially where there is additional net loading (e.g., in areas of new grade-raise fill).

The following narrative provides a general summary of the Site geotechnical conditions based on our field and laboratory testing programs. These are based on the conditions observed at the time of our work on the specified dates. **I**f the geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. **T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands. **T**he geotechnical conditions are complex and will vary with conditions including the stage of the adjacent Salt Creek and its associated marsh lands.

#### 4.1 S ☐ ☐ ☐ ☐ ☐ M ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

Given the development history of the Site, the surficial materials are generally not natural. The conditions at the boring locations included:

- Topsoil in borings B-01 through B-03 ranging between approximately 12 to 18-inches.
- Approximately 2 to 15 inches of man-made limestone products were disclosed on surface at the B-07 through B-15 locations.
- Old asphalt ranging from 2 to 13 inches thick, was noted at Borings B-05 through B-07 and B-17.
- Various granular aggregate materials were found in borings B-07 through B-09, B-12 and B-13. These ranged in thickness of up to about 19 inches.

#### 4.2 O ☐ ☐ F ☐ ☐

Based on our soil boring results, as well as our research into the development history, the Site was filled to raise it above the flood hazard zone associated with Salt Creek. In places, the fill was placed over muck, peat or otherwise unsuitable soils. This will represent a concern for the proposed development.

The fill material is undocumented and consisted of a mixture of black, dark brown and brown, fine to medium coarse silty sand, clayey sand, sand and gravel, crushed limestone, sandy silty clay with traces of organics, gravel, cobblestones, interbedded clay lenses as shown on the test boring logs. Some test borings encountered dark colored soil that may resemble topsoil. The old fill materials were typically disclosed to varying depths of approximately 1.5 to 9-feet as shown below in Table 2.

TYPICAL 2 DRAINAGE DITCHES			
BORING NO.	APPROXIMATE DEPTH OF FILL, FEET	BORING NO.	APPROXIMATE DEPTH OF FILL, FEET
B-07	±3	B-16	±8
B-09	±9	B-17	±8.5
B-10	±7.5	B-18	±7.5
B-11	±5	B-19	±3
B-12	±5.5	B-20	±2.5
B-13	±5.5	B-21	±1.5
B-15	±5	B-22	±3

\*Depths referenced below existing ground surface.

The old fills are undocumented and non-engineered. They cannot reliably support structures, heavy or concentrated loads, or settlement-sensitive construction and will require mitigation. Mitigation strategies are discussed in Section 5.

#### 4.3 NATIVE MATERIALS

The existing native soils (disclosed below existing fill) generally consisted of cohesionless soils such as sand, silty sand, sand and gravel, clayey silty sand, clayey sand, and gravelly sand. The relative densities of the granular soils ranged from loose to medium dense to dense. Such granular soils were in moist to wet/saturated condition. In boring B-06, medium stiff, sandy clay was present.

#### 4.4 NATURAL ORGANIC SOILS

Test borings B-07, B-13, B-16, B-18, B-19, B-21, and B-22 encountered organic clays and peat to depths of approximately 6 to 10-feet or more as shown in the test boring logs.

Note that such organic clays and peat are highly compressible material and will undergo large and long-term settlement when loaded and also upon dewatering. The variations, exact depth, and lateral extent of existing organic soils on site are not known. It should be expected that significant organic deposits will be undetected because they are often hidden beneath the thickness of the old fill.

#### 4.5 Groundwater

Groundwater level measurements were taken during our field operations by noting the depth of water on the rods and in open boreholes following withdrawal of the drilling augers after the completion of drilling activities in test borings.

In summary, perched water and groundwater were encountered during or following our drilling program in the borings as shown on Table 3 and the boring logs.

TABLE 3 Groundwater Data by Boring and Depth					
Boring No.	Groundwater Data, (Elevation, ft)		Boring No.	Groundwater Data, (Elevation, ft)	
	Depth (ft)	Is it Perched? (Yes/No)		Depth (ft)	Is it Perched? (Yes/No)
B-01	±11 (±685)	NO	B-12	NO	±6.5 (±689.5)
B-02	±10 (±686)	±8 (±688)	B-13	±8 (±688)	±8.5 (±687.5)
B-03	±10 (±687)	±9 (±688)	B-14	±8 (±688)	NO
B-04	±10 (±687)	±8 (±689)	B-15	NO	NO
B-05	NO	NO	B-16	±8 (±687)	±8.5 (±686.5)
B-06	±9.5 (±686.5)	NO	B-17	±8.5 (±687.5)	±8.5 (±687.5)
B-07	±8 (±688)	NO	B-18	NO	NO
B-08	NO	NO	B-19	NO	NO
B-09	±8.5 (±687.5)	±8.5 (±687.5)	B-20	NO	NO
B-10	±9 (±687)	±9 (±687)	B-21	±8 (±686)	±8 (±686)

TABLE 3 Groundwater Depth Data by Boring Location					
Boring No.	Groundwater Depth, (Elevation, Feet)		Boring No.	Groundwater Depth, (Elevation, Feet)	
	Depth	Is it a Confined Aquifer?		Depth	Is it a Confined Aquifer?
B-11	±5 (±692)	NO	B-22	±10 (±683)	±8 (±685)

\*Depths referenced below existing ground surface.

† Not Observed (NO) at completion of drilling.

The groundwater depths shown on the boring logs reflect groundwater levels only for the date which the borings were drilled. Fluctuations in the level and rate of seepage of groundwater will occur due to variations in rainfall, water level, and other factors.

#### 4.6 Seismic Design Category

The seismic design requirements for buildings and other structures are based on seismic design category. A seismic site class “D” may be used for this project, and seismic report is included in Appendix B of this report. The parameters presented in Table 4 below can be used for design.

TABLE 4 Seismic Design Category Parameters	
Designation	Value
2012 International Building Code Site Classification (IBC)	D <sup>1</sup>
Site Latitude	41.450319
Site Longitude	-87.073628
S <sub>s</sub>	0.117g
S <sub>1</sub>	0.064g
S <sub>DS</sub>	0.125
S <sub>D1</sub>	0.102

1. The 2012 IBC uses a site profile extending to a depth of 100-feet for seismic site classification. Borings at this site were extended to a maximum depth of 20-feet. The site properties below the boring depth to 100 feet were estimated based on our experience and knowledge of geologic conditions of the general area.

## **5.0 DESIGN RECOMMENDATIONS**

The following design recommendations have been developed to assist in the design and development of the proposed project. They are intended for the specific project discussed herein and any substantial changes in the project description, location, or assumed grades should be brought to our attention so that we may evaluate how such changes may affect our evaluation.

A strategy for mitigating the geotechnical problems at this Site is needed because the underlying materials (both native and man-made) are not suitable for heavy, concentrated or settlement-sensitive construction. In such areas, we recommend ground improvement using rammed earth rigid inclusions for the proposed buildings (foundations and slabs).

We have considered other methods of ground improvement such as removing the old fills and organic soils and replacing them with new engineered fill, grouting, preloading/surcharging the site, deep dynamic compaction, etc. but have deemed these to be impractical for this project.

Structural solutions, such as supporting the structural loads and floors on systems of deep foundations (i.e., helical piers) are potentially viable and could be addressed separately if requested by the client.

### **5.1 Geotechnical Mitigation and Structural Foundation Analysis**

We recommend conventional footings constructed over rammed aggregate piers to support the proposed Porter County highway garage facility buildings. We recommend that the rammed aggregate piers must tip to suitable depths below the existing fill and organic soils as determined by the specialty contractor. That contractor should consider the effectiveness of their product given the geotechnical conditions, including the existence of buried organic soils.

---

This specialty work should only be performed using a contractor with a proven record of performance that delivers their work on a design-build basis. Exhibit C provides a letter from Geopiers® representing that they deem the use of their product to be feasible.

Rammed aggregate piers are constructed by drilling 24 to 30-inch diameter holes within the shallow foundation footprint, and then compacting the holes with crushed stone to form a dense aggregate pier. The footings are then constructed directly on the reinforced subgrade using conventional construction methods.

It is important to note that the ground improvement contractor retains the responsibility for the final pier designs and can estimate settlements, along with warranting the performance of the footings supported by rammed aggregate piers. The ground improvement contractor should review the soil conditions at the site and ensure that the proposed ground improvement system is suitable for the site soil conditions. It will be their responsibility to determine whether additional geotechnical data is needed for their purposes.

All exterior footings and footings in unheated areas should bear at a minimum of three and a half (3.5) feet below final exterior grade for frost protection. All footings should be adequately protected from frost penetration during and after construction and should bear on firm material.

Special attention should be made to the placement of backfill against the building foundations and walls as inadequate compaction of these locations may cause cracking of the slab edges and corners due to subsidence of the backfill.

The detailing of joints in heavily loaded floor areas will be the responsibility of the floor designer. However, the interior slabs should be effectively isolated from the foundations so that a small amount of independent movement can occur without causing damage.

---

We recommend the slab-on-grade subgrade soils be protected from frost during winter construction. Frozen soils must be thawed and compacted or removed and replaced prior to slab-on-grade construction.

Depending on the choice of floor finishes, it may be appropriate to incorporate a moisture barrier below the floor slab. This decision should be evaluated by the architect and structural engineer based on the intended floor usage, planned finishes, and in accordance with ACI recommendations.

The floor slab subgrade soils should be protected from frost penetration both during construction and the service life of the proposed building(s). To protect foundations and slabs under extreme cold temperatures associated with the proposed cold storage building, we recommend that these structural elements be suitably designed by a qualified professional structural engineer in accordance with special cold storage specifications and good construction practice.

Additional details regarding the design and construction of the foundations and floor slabs for the buildings will be provided by the specialty contractor.

## 5.2 General Site Grading and Earthwork Areas

Given the general concerns about the undocumented fill and underlying organic soils, special attention will be needed in planning and executing the Site grading. In areas outside the footprint of new buildings or other settlement-sensitive construction, it will probably be possible to avoid the full ground improvement called for in building areas.

Considerations in planning the grading include the amount and location of cutting and filling. In general, the application of grade-raise fill will result in settlement, some of which would be long-term in nature. As such, filling should be avoided wherever possible.

Activities that require construction dewatering should be avoided to the extent possible. A reason for this is that dewatering could induce settlement.

Of particular concern are the design and construction of retaining walls or slopes. Given the subsurface conditions, engineering stability analyses (geotechnical and structural) will be needed.

Due to the undocumented nature of the existing development, there may be buried objects that are unknown to GME. This might include tanks, wells, cisterns, old concrete remnants, utilities, etc. Identification of contaminated soil or groundwater was not within the scope of our assignment.

GME should be retained to review and comment on the grading and drainage plans when they are available.

### 5.3 TYPICAL PAVEMENT DESIGN AND SPECIALTIES

We anticipate that regrading can result in a California Bearing Ratio (CBR) value of approximately 3 percent (a resilient modulus value equivalent to approximately 4,500 psi). This assumes that the subgrade is properly prepared and new fill is compacted as recommended in this report.

Notwithstanding the above, the Owner and project team should, however, be aware of an increased but unquantifiable risk of long-term settlement due to the presence of buried organic soils. This will probably require more frequent than normal maintenance and may favor the use of flexible (asphalt) pavements over Portland cement concrete pavements.

The installation of pavement surfaces for the proposed parking lot and driveway areas should be in accordance with project plans and specifications. GME can assist the team in the development of these specifications upon request. All construction methods and materials should conform to the applicable and current INDOT Standards and Specifications.

Controlling subsurface water in pavement areas is important to enhance the long-term performance of the pavements. The subgrade surface should be uniformly sloped to facilitate drainage through the granular base to the shoulders or inlets and to avoid any ponding of water beneath the pavement.

Assuming that post construction pavement movement can be tolerated, mitigation may include geotextile byproducts. We recommend that a geotextile engineer familiar with similar conditions be contacted to determine the feasibility of their product for the proposed project. Available geotextile products may include woven fabric (i.e., Mirafi® RS580i), Geogrid (e.g., BX 1300 or TriAx® products (e.g., TX 140, TX 150, or TX 190) and new engineered fill may include crushed limestone aggregate (INDOT No. 1 or 2).

Water infiltration into pavement subgrade soils can reduce the service life of the pavement. Therefore, we recommend that adequate surface drainage be provided at the site to minimize any increase in moisture content of the pavement soils. The subgrade surface should be uniformly sloped to facilitate drainage through the granular base to shoulders or inlets and to avoid any ponding of water beneath the pavement.

## **6.0 CONSTRUCTION RECOMMENDATIONS**

In addition to the foregoing design recommendations, we provide the following construction-phase recommendations. The degree and applicability of these recommendations may vary depending on the role of the specialty contractor performing the ground improvement work.

## 6.1 SUBGRADE PREPARATION

The initial step of site preparation should include the demolition of old structures, removal of undocumented fill, vegetation, topsoil, concrete flat work, and properly abandon or relocate all existing utilities within the influence of the proposed construction areas. All buried construction elements shall be removed before new grade-raise is placed on site.

All exposed areas need to be subject to inspection by GME Testing. This will generally consist of probing and proof rolling to expose unsuitable subgrade materials.

Except as directed by a specialty contractor, any subgrade areas observed to be pumping and yielding under evaluation should be undercut and replaced with engineered fill or otherwise mitigated prior to the placement of new fill, floor slabs, pavement, or flatwork. The extent of undercutting will depend on several factors, including weather condition at time of construction and the condition of existing soils at the design subgrade and anticipated traffic within the cut and fill areas.

Depending on the time of the year and moisture contents of existing soils at the time of construction, aerating and conditioning and/or subgrade stabilization may be needed below the building pad and pavement areas.

Care must be exercised during grading and fill placement operations. Repeated and uncontrolled heavy construction traffic over the subgrade could cause the subgrade to pump, yield, and weak areas to develop and, therefore should be avoided. Heavy construction traffic should use designated areas as directed by the contractor.

All excavations should be monitored by a "Competent Person", as defined by the OSHA standard, and appropriate shoring or sloping techniques used to prevent cave-ins.

## 6.2 EROSION CONTROL FILL

New engineered fill will be needed to establish desired grade on site and for the purpose of backfill. The materials removed during site preparation activities may not be suitable for reuse and structural fill and may require offsite disposal. As such, new materials should be imported from approved offsite sources.

All engineered fill needed to replace undercut materials or as a grade-raise fill should be approved by GME Testing prior to placement on site.

Drainage ditches shall be constructed to meet the requirements of the Indiana Department of Transportation (INDOT) Manual of Specifications for Highway Construction, 2010 Edition, Section 53, "Gravel". The material shall be tested and approved by GME Testing prior to placement. The material shall be tested and approved by GME Testing prior to placement. The material shall be tested and approved by GME Testing prior to placement. **ASTM D-1557.**

For granular soils used on this project, it is recommended that it exhibits less than 10 percent non-plastic fines. The proposed material(s) should be sampled at the source for testing and then approved prior to import to the site.

To achieve the recommended compaction limit of the structural fill, the fill material should be placed and compacted in layers not exceeding 8-inches in loose thickness (the loose lift thickness should be reduced to 6-inches when utilizing small hand compactors) and within the range of  $\pm 2$  percentage (%) of the optimum moisture content value. All fill placements should be monitored by a GME Testing representative.

## 6.3 TRENCH EXCAVATION

Where mass removal and replacement are selected for this project, the excavations will be prone to sloughing and cave ins. Additionally, excavations that will extend to or below groundwater levels and granular soils are anticipated to be unstable and will collapse. Therefore, a properly designed and installed

temporary earth retention system comprised of steel sheeting will be necessary to support the excavation. The design of the sheeting and any required bracing is typically performed by the contractor's licensed professional engineer and will be based on economy as well as geometric and ground conditions. In some cases, additional geotechnical information could be required.

Consideration should be given to how installation and extraction of sheeting will affect any nearby structures and underground utilities.

All excavations should be monitored by a "Competent Person", as defined by the OSHA standard, and appropriate shoring or sloping techniques used to prevent cave-ins.

Soils exposed in the bases of all excavations must be protected against any detrimental change in conditions such as from disturbance, rain, and freezing. Surface run-off water must be drained away and not allowed to pond in the excavations.

#### 6.4 Dewatering and Groundwater Control

We observe a high groundwater table that is subject to changing elevation. The soil encountered was generally very transmissive. Moreover, dewatering may induce ground settlement. The design and planning of the work for this project should preferably avoid activities that would require suppression of the ground water table.

Some perched or "nuisance" water seepage and surface drainage might be manageable using conventional sump pump methods.

---

Whenever groundwater is encountered during construction, measures should be taken to permit the construction to be completed in relatively dry conditions. When designing site drainage patterns, site runoff should be diverted away from the foundations and directed to on-site retention areas or storm sewer systems. It is anticipated that these measures can reduce the potential for softening and possible erosion of the foundation subgrade soils. It is necessary that water is not permitted to pond near the building areas and foundations.

---

## 7.0 LIMITATIONS

The field evaluation, laboratory testing, and geotechnical analyses presented in this geotechnical investigation report have been conducted in general accordance with current practice and the standard of care exercised by geotechnical consultants performing similar tasks in the project area. Although individual test borings are representative of the subsurface conditions at the boring locations on the dates drilled, they are not necessarily representative of the subsurface conditions between boring locations or subsurface conditions during other seasons of the year.

The lines of demarcation shown on the logs represent approximate boundaries between the various classifications. The stratification of soils, as shown on the accompanying test borehole logs, represents the soil conditions at the drilled borehole locations, and variations may occur between the boreholes. In-situ strata changes could occur gradually or at different levels. Also, it should be noted that the boreholes depict conditions at the particular locations and times indicated.

The report was prepared by GME Testing solely for the use of the Client in accordance with an executed contract. The Client's use of or reliance on this report is limited by the terms and conditions of the contract and by the qualifications and limitations stated in the report. It is also acknowledged that the Client's use of and reliance of this report is limited for reasons which include actual site conditions that may change with time; hidden conditions, not discoverable within the scope of the assessment may exist at the site; and the scope of the investigation may have been limited by time, budget and other constraints imposed by the client.

---

Neither the report nor its contents, conclusions or recommendations are intended for the use of any party other than the Client. GME Testing and the Client assume no liability for any reliance placed on this report by such party. The rights of the client under contract may not be assigned to any person or entity, without the consent of GME Testing which shall not be unreasonably withheld.

Our services have been provided consistent with its professional standards of care. No other warranties are made, either expressed or implied.

# **APPENDIX A**

## I. FIELD EXPLORATION

### D S P

The test borings were drilled using conventional augers to advance the holes and representative samples of the soils were obtained employing split-barrel sampling techniques in accordance with ASTM procedures D-1586-84. After completion of the borings and water level readings, the auger holes were backfilled with auger cuttings.

The description and depths of soil strata encountered and levels at which samples were recovered are indicated on the accompanying borehole log sheets in the Appendix B. In the column "Soil/Material Description" on the drill borehole log, the horizontal lines represent stratum changes. A solid line represents an observed change, and a dashed line represents an estimated change. An explanation of the symbols and terms used on the boring log sheets is given in Appendix B of this report.

### F T M

**Standard Penetration Test:** During the sampling procedures, Standard Penetration Test (SPT) was performed at regular intervals through the depth of the borings. The SPT value ("N"-value) is defined as the number of blows required to advance a 2-inch O.D., split-barrel sampler a distance of one foot by a 140-pound hammer falling 30-inches. These values provide a useful preliminary indication of the consistency or relative density of most soil deposits and are included on the Borehole Logs in Appendix B.

**Water Level Measurements:** Groundwater level observations were made in the boring holes during and upon completion of the boring operations. The groundwater level measurements are noted on the boring logs presented herein.

All recovered samples were returned to GME Testing laboratory for visual examination and subsequent laboratory testing.

## II. LABORATORY TESTING

Selected soil samples obtained from the drilling and sampling program were tested in the laboratory to evaluate additional pertinent engineering characteristics of the foundation materials necessary in estimating the engineering properties of these materials.

### Soil Laboratory Methods

**Visual Classification:** All samples were visually classified by a geotechnical engineer in general accordance with ASTM D-2488, and on the Borehole Logs, which are located in Appendix B of this report.

**Moisture Content Tests:** The natural moisture content of selected samples was determined by ASTM method D-2216 and is recorded on the Borehole Logs as a percentage of dry weight of soil under the “MC”.

**Hand Penetration Tests:** Samples of cohesive soils obtained from the split spoon sampler were tested with a calibrated hand penetrometer to aid in evaluating the soil strength characteristics. The results from this testing are tabulated on the Borehole Logs under the heading “Q<sub>P</sub>”.

**Unconfined Compressive Strength Tests:** The undrained shear strengths of the cohesive soils were evaluated utilizing unconfined compressive tests on specimens obtained from the split-barrel and/or thin wall tube sampler. The values of strength tests performed on soil samples obtained from the split-barrel sampler are considered approximate recognizing that the sampler provides a representative but somewhat disturbed sample. The test results are tabulated on the Borehole Logs under the heading “Q<sub>u</sub>”.

---

**EXHIBIT A**  
**Custom Soil Resource Report**



United States  
Department of  
Agriculture

**NRCS**

Natural  
Resources  
Conservation  
Service

A product of the National  
Cooperative Soil Survey,  
a joint effort of the United  
States Department of  
Agriculture and other  
Federal agencies, State  
agencies including the  
Agricultural Experiment  
Stations, and local  
participants

# Custom Soil Resource Report for **Porter County, Indiana**



December 18, 2023

# Preface

---

Soil surveys contain information that affects land use planning in survey areas. They highlight soil limitations that affect various land uses and provide information about the properties of the soils in the survey areas. Soil surveys are designed for many different users, including farmers, ranchers, foresters, agronomists, urban planners, community officials, engineers, developers, builders, and home buyers. Also, conservationists, teachers, students, and specialists in recreation, waste disposal, and pollution control can use the surveys to help them understand, protect, or enhance the environment.

Various land use regulations of Federal, State, and local governments may impose special restrictions on land use or land treatment. Soil surveys identify soil properties that are used in making various land use or land treatment decisions. The information is intended to help the land users identify and reduce the effects of soil limitations on various land uses. The landowner or user is responsible for identifying and complying with existing laws and regulations.

Although soil survey information can be used for general farm, local, and wider area planning, onsite investigation is needed to supplement this information in some cases. Examples include soil quality assessments (<http://www.nrcs.usda.gov/wps/portal/nrcs/main/soils/health/>) and certain conservation and engineering applications. For more detailed information, contact your local USDA Service Center (<https://offices.sc.egov.usda.gov/locator/app?agency=nrcs>) or your NRCS State Soil Scientist ([http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/?cid=nrcs142p2\\_053951](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/?cid=nrcs142p2_053951)).

Great differences in soil properties can occur within short distances. Some soils are seasonally wet or subject to flooding. Some are too unstable to be used as a foundation for buildings or roads. Clayey or wet soils are poorly suited to use as septic tank absorption fields. A high water table makes a soil poorly suited to basements or underground installations.

The National Cooperative Soil Survey is a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local agencies. The Natural Resources Conservation Service (NRCS) has leadership for the Federal part of the National Cooperative Soil Survey.

Information about soils is updated periodically. Updated information is available through the NRCS Web Soil Survey, the site for official soil survey information.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require

alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

# Contents

---

<b>Preface</b> .....	2
<b>How Soil Surveys Are Made</b> .....	5
<b>Soil Map</b> .....	8
Soil Map.....	9
Legend.....	10
Map Unit Legend.....	11
Map Unit Descriptions.....	11
Porter County, Indiana.....	13
AbhAT—Adrian muck, drained, heavy till plain, 0 to 1 percent slopes.....	13
Ho—Houghton muck, drained.....	14
RIB—Riddles silt loam, 2 to 6 percent slopes.....	16
RmC2—Riddles loam, 6 to 12 percent slopes, eroded.....	17
<b>References</b> .....	20

# How Soil Surveys Are Made

---

Soil surveys are made to provide information about the soils and miscellaneous areas in a specific area. They include a description of the soils and miscellaneous areas and their location on the landscape and tables that show soil properties and limitations affecting various uses. Soil scientists observed the steepness, length, and shape of the slopes; the general pattern of drainage; the kinds of crops and native plants; and the kinds of bedrock. They observed and described many soil profiles. A soil profile is the sequence of natural layers, or horizons, in a soil. The profile extends from the surface down into the unconsolidated material in which the soil formed or from the surface down to bedrock. The unconsolidated material is devoid of roots and other living organisms and has not been changed by other biological activity.

Currently, soils are mapped according to the boundaries of major land resource areas (MLRAs). MLRAs are geographically associated land resource units that share common characteristics related to physiography, geology, climate, water resources, soils, biological resources, and land uses (USDA, 2006). Soil survey areas typically consist of parts of one or more MLRA.

The soils and miscellaneous areas in a survey area occur in an orderly pattern that is related to the geology, landforms, relief, climate, and natural vegetation of the area. Each kind of soil and miscellaneous area is associated with a particular kind of landform or with a segment of the landform. By observing the soils and miscellaneous areas in the survey area and relating their position to specific segments of the landform, a soil scientist develops a concept, or model, of how they were formed. Thus, during mapping, this model enables the soil scientist to predict with a considerable degree of accuracy the kind of soil or miscellaneous area at a specific location on the landscape.

Commonly, individual soils on the landscape merge into one another as their characteristics gradually change. To construct an accurate soil map, however, soil scientists must determine the boundaries between the soils. They can observe only a limited number of soil profiles. Nevertheless, these observations, supplemented by an understanding of the soil-vegetation-landscape relationship, are sufficient to verify predictions of the kinds of soil in an area and to determine the boundaries.

Soil scientists recorded the characteristics of the soil profiles that they studied. They noted soil color, texture, size and shape of soil aggregates, kind and amount of rock fragments, distribution of plant roots, reaction, and other features that enable them to identify soils. After describing the soils in the survey area and determining their properties, the soil scientists assigned the soils to taxonomic classes (units). Taxonomic classes are concepts. Each taxonomic class has a set of soil characteristics with precisely defined limits. The classes are used as a basis for comparison to classify soils systematically. Soil taxonomy, the system of taxonomic classification used in the United States, is based mainly on the kind and character of soil properties and the arrangement of horizons within the profile. After the soil

scientists classified and named the soils in the survey area, they compared the individual soils with similar soils in the same taxonomic class in other areas so that they could confirm data and assemble additional data based on experience and research.

The objective of soil mapping is not to delineate pure map unit components; the objective is to separate the landscape into landforms or landform segments that have similar use and management requirements. Each map unit is defined by a unique combination of soil components and/or miscellaneous areas in predictable proportions. Some components may be highly contrasting to the other components of the map unit. The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The delineation of such landforms and landform segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, onsite investigation is needed to define and locate the soils and miscellaneous areas.

Soil scientists make many field observations in the process of producing a soil map. The frequency of observation is dependent upon several factors, including scale of mapping, intensity of mapping, design of map units, complexity of the landscape, and experience of the soil scientist. Observations are made to test and refine the soil-landscape model and predictions and to verify the classification of the soils at specific locations. Once the soil-landscape model is refined, a significantly smaller number of measurements of individual soil properties are made and recorded. These measurements may include field measurements, such as those for color, depth to bedrock, and texture, and laboratory measurements, such as those for content of sand, silt, clay, salt, and other components. Properties of each soil typically vary from one point to another across the landscape.

Observations for map unit components are aggregated to develop ranges of characteristics for the components. The aggregated values are presented. Direct measurements do not exist for every property presented for every map unit component. Values for some properties are estimated from combinations of other properties.

While a soil survey is in progress, samples of some of the soils in the area generally are collected for laboratory analyses and for engineering tests. Soil scientists interpret the data from these analyses and tests as well as the field-observed characteristics and the soil properties to determine the expected behavior of the soils under different uses. Interpretations for all of the soils are field tested through observation of the soils in different uses and under different levels of management. Some interpretations are modified to fit local conditions, and some new interpretations are developed to meet local needs. Data are assembled from other sources, such as research information, production records, and field experience of specialists. For example, data on crop yields under defined levels of management are assembled from farm records and from field or plot experiments on the same kinds of soil.

Predictions about soil behavior are based not only on soil properties but also on such variables as climate and biological activity. Soil conditions are predictable over long periods of time, but they are not predictable from year to year. For example, soil scientists can predict with a fairly high degree of accuracy that a given soil will have a high water table within certain depths in most years, but they cannot predict that a high water table will always be at a specific level in the soil on a specific date.

After soil scientists located and identified the significant natural bodies of soil in the survey area, they drew the boundaries of these bodies on aerial photographs and

## Custom Soil Resource Report


identified each as a specific map unit. Aerial photographs show trees, buildings, fields, roads, and rivers, all of which help in locating boundaries accurately.

# Soil Map

---

The soil map section includes the soil map for the defined area of interest, a list of soil map units on the map and extent of each map unit, and cartographic symbols displayed on the map. Also presented are various metadata about data used to produce the map, and a description of each soil map unit.


# Custom Soil Resource Report Soil Map




# Custom Soil Resource Report


## MAP LEGEND


### Area of Interest (AOI)

 Area of Interest (AOI)


### Soils


 Soil Map Unit Polygons


 Soil Map Unit Lines


 Soil Map Unit Points

### Special Point Features

 Blowout

 Borrow Pit


 Clay Spot


 Closed Depression

 Gravel Pit

 Gravelly Spot


 Landfill

 Lava Flow

 Marsh or swamp

 Mine or Quarry


 Miscellaneous Water


 Perennial Water

 Rock Outcrop


 Saline Spot

 Sandy Spot

 Severely Eroded Spot


 Sinkhole


 Slide or Slip

 Sodic Spot

 Spoil Area

 Stony Spot


 Very Stony Spot

 Wet Spot

 Other

 Special Line Features

### Water Features

 Streams and Canals


### Transportation

 Rails


 Interstate Highways

 US Routes

 Major Roads

 Local Roads

### Background

 Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service  
Web Soil Survey URL:  
Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Porter County, Indiana  
Survey Area Data: Version 27, Sep 1, 2023

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 16, 2022—Jun 27, 2022

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

## Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
AbhAT	Adrian muck, drained, heavy till plain, 0 to 1 percent slopes	0.7	6.4%
Ho	Houghton muck, drained	1.1	9.9%
RIB	Riddles silt loam, 2 to 6 percent slopes	5.9	55.8%
RmC2	Riddles loam, 6 to 12 percent slopes, eroded	3.0	27.9%
<b>Totals for Area of Interest</b>		<b>10.6</b>	<b>100.0%</b>

## Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate

pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An *association* is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

## Porter County, Indiana

### AbhAT—Adrian muck, drained, heavy till plain, 0 to 1 percent slopes

#### Map Unit Setting

*National map unit symbol:* 30n4v

*Elevation:* 630 to 740 feet

*Mean annual precipitation:* 34 to 41 inches

*Mean annual air temperature:* 46 to 54 degrees F

*Frost-free period:* 155 to 180 days

*Farmland classification:* Farmland of statewide importance

#### Map Unit Composition

*Adrian, drained, and similar soils:* 75 percent

*Minor components:* 25 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

#### Description of Adrian, Drained

##### Setting

*Landform:* Flood plains, moraines, till plains, lake plains, depressions on outwash plains

*Landform position (two-dimensional):* Toeslope

*Landform position (three-dimensional):* Base slope

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Herbaceous organic material over sandy outwash

##### Typical profile

*Oap - 0 to 10 inches:* muck

*Oa - 10 to 28 inches:* muck

*Cg - 28 to 80 inches:* sand

##### Properties and qualities

*Slope:* 0 to 1 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Very poorly drained

*Runoff class:* Negligible

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately low to high  
(0.14 to 14.17 in/hr)

*Depth to water table:* About 0 inches

*Frequency of flooding:* None

*Frequency of ponding:* Frequent

*Calcium carbonate, maximum content:* 15 percent

*Maximum salinity:* Nonsaline (0.0 to 1.9 mmhos/cm)

*Sodium adsorption ratio, maximum:* 0.4

*Available water supply, 0 to 60 inches:* Very high (about 13.0 inches)

##### Interpretive groups

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 3w

*Hydrologic Soil Group:* A/D

*Ecological site:* R110XY024IL - Ponded Depressional Sedge Meadow

*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)

*Hydric soil rating:* Yes

## Minor Components

### **Antung, drained**

*Percent of map unit:* 10 percent  
*Landform:* Moraines, till plains, lake plains, depressions on outwash plains  
*Landform position (two-dimensional):* Toeslope  
*Landform position (three-dimensional):* Base slope  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Ecological site:* R110XY024IL - Poned Depressional Sedge Meadow  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

### **Edwards, drained**

*Percent of map unit:* 6 percent  
*Landform:* Moraines, till plains, lake plains, depressions on outwash plains  
*Landform position (two-dimensional):* Toeslope  
*Landform position (three-dimensional):* Base slope  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Ecological site:* R110XY024IL - Poned Depressional Sedge Meadow  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

### **Houghton, drained**

*Percent of map unit:* 6 percent  
*Landform:* Moraines, till plains, lake plains, depressions on outwash plains  
*Landform position (two-dimensional):* Toeslope  
*Landform position (three-dimensional):* Base slope  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Ecological site:* R110XY024IL - Poned Depressional Sedge Meadow  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

### **Muskego, drained**

*Percent of map unit:* 3 percent  
*Landform:* Depressions on outwash plains, moraines, till plains, lake plains  
*Landform position (two-dimensional):* Toeslope  
*Landform position (three-dimensional):* Base slope  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Ecological site:* R110XY024IL - Poned Depressional Sedge Meadow  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

## **Ho—Houghton muck, drained**

### **Map Unit Setting**

*National map unit symbol:* 5d5b

## Custom Soil Resource Report

*Elevation:* 600 to 1,400 feet  
*Mean annual precipitation:* 34 to 40 inches  
*Mean annual air temperature:* 47 to 51 degrees F  
*Frost-free period:* 170 to 185 days  
*Farmland classification:* Farmland of statewide importance

### Map Unit Composition

*Houghton, drained, and similar soils:* 75 percent  
*Minor components:* 25 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

### Description of Houghton, Drained

#### Setting

*Landform:* Depressions on moraines, depressions on lake plains, depressions on till plains, depressions on outwash plains  
*Landform position (two-dimensional):* Footslope, toeslope  
*Down-slope shape:* Concave  
*Across-slope shape:* Concave  
*Parent material:* Herbaceous organic material

#### Typical profile

*Op - 0 to 9 inches:* muck  
*Oa - 9 to 80 inches:* muck

#### Properties and qualities

*Slope:* 0 to 1 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Very poorly drained  
*Runoff class:* Negligible  
*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high (0.20 to 6.00 in/hr)  
*Depth to water table:* About 0 inches  
*Frequency of flooding:* None  
*Frequency of ponding:* Frequent  
*Available water supply, 0 to 60 inches:* Very high (about 23.9 inches)

#### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 3w  
*Hydrologic Soil Group:* A/D  
*Ecological site:* R111XC013IN - Deep Muck  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

### Minor Components

#### Adrian, drained

*Percent of map unit:* 7 percent  
*Landform:* Depressions on lake plains, depressions on outwash plains, depressions on till plains  
*Landform position (two-dimensional):* Footslope, toeslope  
*Down-slope shape:* Concave  
*Across-slope shape:* Concave  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

**Edwards, drained**

*Percent of map unit:* 7 percent

*Landform:* Depressions on till plains, depressions on outwash plains, depressions on lake plains

*Landform position (two-dimensional):* Footslope, toeslope

*Down-slope shape:* Concave

*Across-slope shape:* Concave

*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)

*Hydric soil rating:* Yes

**Muskego, drained**

*Percent of map unit:* 6 percent

*Landform:* Depressions on till plains, depressions on outwash plains, depressions on lake plains

*Landform position (two-dimensional):* Footslope, toeslope

*Down-slope shape:* Concave

*Across-slope shape:* Concave

*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)

*Hydric soil rating:* Yes

**Palms, drained**

*Percent of map unit:* 5 percent

*Landform:* Depressions on till plains, depressions on outwash plains

*Landform position (two-dimensional):* Footslope, toeslope

*Down-slope shape:* Concave

*Across-slope shape:* Concave

*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)

*Hydric soil rating:* Yes

**RIB—Riddles silt loam, 2 to 6 percent slopes**

**Map Unit Setting**

*National map unit symbol:* 5d68

*Elevation:* 570 to 870 feet

*Mean annual precipitation:* 34 to 40 inches

*Mean annual air temperature:* 47 to 50 degrees F

*Frost-free period:* 140 to 170 days

*Farmland classification:* All areas are prime farmland

**Map Unit Composition**

*Riddles and similar soils:* 90 percent

*Minor components:* 10 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

**Description of Riddles**

**Setting**

*Landform:* Till plains

*Landform position (two-dimensional):* Summit

*Landform position (three-dimensional):* Interfluve

## Custom Soil Resource Report

*Down-slope shape:* Convex  
*Across-slope shape:* Linear  
*Parent material:* Loamy till

### Typical profile

*H1 - 0 to 10 inches:* silt loam  
*H2 - 10 to 48 inches:* loam  
*H3 - 48 to 60 inches:* loam

### Properties and qualities

*Slope:* 2 to 6 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Well drained  
*Runoff class:* Low  
*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.60 to 2.00 in/hr)  
*Depth to water table:* More than 80 inches  
*Frequency of flooding:* None  
*Frequency of ponding:* None  
*Calcium carbonate, maximum content:* 40 percent  
*Available water supply, 0 to 60 inches:* High (about 9.5 inches)

### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 2e  
*Hydrologic Soil Group:* B  
*Ecological site:* F097XA018MI - Dry Loamy Drift Plains  
*Other vegetative classification:* Trees/Timber (Woody Vegetation)  
*Hydric soil rating:* No

### Minor Components

#### Pewamo

*Percent of map unit:* 5 percent  
*Landform:* Depressions  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

#### Washtenaw

*Percent of map unit:* 5 percent  
*Landform:* Depressions  
*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)  
*Hydric soil rating:* Yes

## RmC2—Riddles loam, 6 to 12 percent slopes, eroded

### Map Unit Setting

*National map unit symbol:* 5d69  
*Elevation:* 570 to 870 feet  
*Mean annual precipitation:* 34 to 40 inches  
*Mean annual air temperature:* 47 to 50 degrees F

## Custom Soil Resource Report

*Frost-free period:* 140 to 170 days

*Farmland classification:* Not prime farmland

### Map Unit Composition

*Riddles and similar soils:* 90 percent

*Minor components:* 10 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

### Description of Riddles

#### Setting

*Landform:* Till plains

*Landform position (two-dimensional):* Backslope

*Landform position (three-dimensional):* Side slope

*Down-slope shape:* Linear

*Across-slope shape:* Linear

*Parent material:* Loamy till

#### Typical profile

*H1 - 0 to 10 inches:* loam

*H2 - 10 to 48 inches:* loam

*H3 - 48 to 60 inches:* loam

#### Properties and qualities

*Slope:* 6 to 12 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Well drained

*Runoff class:* Medium

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.60 to 2.00 in/hr)

*Depth to water table:* More than 80 inches

*Frequency of flooding:* None

*Frequency of ponding:* None

*Calcium carbonate, maximum content:* 40 percent

*Available water supply, 0 to 60 inches:* High (about 9.5 inches)

#### Interpretive groups

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 3e

*Hydrologic Soil Group:* B

*Ecological site:* F097XA018MI - Dry Loamy Drift Plains

*Other vegetative classification:* Trees/Timber (Woody Vegetation)

*Hydric soil rating:* No

### Minor Components

#### Pewamo

*Percent of map unit:* 5 percent

*Landform:* Drainageways

*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)

*Hydric soil rating:* Yes

#### Washtenaw

*Percent of map unit:* 5 percent

*Landform:* Drainageways

*Other vegetative classification:* Mixed/Transitional (Mixed Native Vegetation)

*Hydric soil rating:* Yes



# References

---


- American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.
- American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.
- Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.
- Federal Register. July 13, 1994. Changes in hydric soils of the United States.
- Federal Register. September 18, 2002. Hydric soils of the United States.
- Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.
- National Research Council. 1995. Wetlands: Characteristics and boundaries.
- Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. [http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2\\_054262](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_054262)
- Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. [http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2\\_053577](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053577)
- Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. [http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2\\_053580](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053580)
- Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.
- United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.
- United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. [http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2\\_053374](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2_053374)
- United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. <http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/landuse/rangepasture/?cid=stelprdb1043084>

## Custom Soil Resource Report


United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. [http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2\\_054242](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2_054242)

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. [http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2\\_053624](http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053624)

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. [http://www.nrcs.usda.gov/Internet/FSE\\_DOCUMENTS/nrcs142p2\\_052290.pdf](http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf)



VICINITY MAP (NOT TO SCALE)



## NOTES

1. All boring locations are approximate.
2. Vicinity map generated using imagery from google.com/maps.

## E B – APPROXIMATE BORING LOCATION MAP

P Proposed Porter County Highway Garage  
 L 1955 IN-2, Valparaiso, IN  
 C A&Z Engineering, LLC (A&Z)  
 GME P G23-112119



## LEGEND

 B-01  
 Test Boring Location and Designation



**EXHIBIT C**  
**Geopier® Evaluation Letter**

**To:** Rami Anabtawi **From:** Zach Ethington, P.E.

---

**Company:** Geotechnical & Materials Engineers, Inc. **Pages:** 2

---

**Re:** Delegated Design Technical Memorandum  
Porter County Highway Garage  
GFC Project No.: PGL-3340 **Date:** January 3, 2024  
**CC:**

---

In combination with our licensed installer for this area, Geopier is pleased to present this technical memorandum to utilize a *Geopier*® system for the above-referenced project. A future budget estimate for a scope of work based upon our review of the preliminary information can be provided by our licensed installer. Please note that any changes to the proposed site layout may necessitate additional soil borings for this project.

This anticipated scope includes the following:

- Installation of piers below foundations at the following structures as designated by Geopier.
  - 60'x120' Cold Storage Building
  - 97'x80' Office Building
  - 80'x90' Maintenance Building
  - 65'x85' Salt Barn Building
- Mobilization and demobilization from the site.
- Union installer.
- Geopier testing (fulltime technician on site during installation).
- Geopier design calculations and preparation of shop drawings.

Items not included in anticipated scope are:

- Support of parking lot areas.
- Spoils removal from the building pad.
- Surveying/layout of the piers in the field.
- Obstruction removal, if encountered.
- Street cleaning / traffic control.
- Modulus test.


Technical Comments:

- This memo is based on the following assumed design criteria:
  - Anticipated column loads not exceeding 100 kips
  - Anticipated wall loads not exceeding 6 kips per linear foot
  - Anticipated floor loads not exceeding 125 pounds per square foot
  - Site grading requiring no more than 2 feet of new fill
- Please refer to the geotechnical information prepared by GME (Project No.: G23-112119) for more information regarding the subsurface conditions at the project site. Problematic subgrade conditions consist of variable soft/saturated clays, loose sands, and pockets of organics.
- *Geopier can provide a foundation-support system with bearing capacities up to 4,000 ksf and calculated overall settlements of approximately 1-inch for the above assumed conditions.*
- Stable working grades with maximum slopes of 2.5% should be established prior to Geopier installations. We expect working grades at or near the existing surface grade.
- All Geopier elements should be installed to depths required for settlement control. Piers will be terminated upon mandrel refusal in dense till when encountered.

- Please note that the general contractor is responsible for removal of all below-grade obstructions (including remnant foundations, slabs, shallow fill obstructions, utilities, etc.) prior to the installation of the Geopier® elements.
- Prior to pricing, generation of shop drawings, and Geopier® installation, it will be necessary to provide us with:
  - Civil site/grading plans
  - Foundation plans (with Auto CAD copy)
  - Loading information for Geopier supported foundations.
  - Settlement criteria
  - Confirmation of working pad elevations, locations, and approach
- Based on the information provided, our licensed contractor can provide a future budget proposal for design and construction of a Geopier ground improvement system for this project.
- Geopier systems are provided turn-key. Upon project approval, we will submit detailed design calculations and shop drawings for the Geopier Design.

Should this bid be accepted, your contract would be with the licensed installer for this area. This appears to be a good site for Rammed Aggregate Pier® soil improvement using the Geopier® system. A Geopier® solution should offer great economy and schedule savings to this project while providing proven performance. If you have any questions concerning this report, or if we can be of further assistance, please contact us.

Sincerely,

A handwritten signature in black ink, appearing to read 'Zach Ethington', written in a cursive style.



Zach Ethington, P.E.



Region Engineer

859 583 3681

[zethington@geopier.com](mailto:zethington@geopier.com)


## **APPENDIX B**









## SUMMARY OF BORINGS




## SUMMARY OF BORINGS



## SUMMARY OF BORINGS



## SUMMARY OF BORINGS



CLIENT: A&Z Engineering, LLC

GME PROJECT NO: G23-112119

PROJECT TYPE: Proposed Porter County Highway Garage

LOCATION: 1955 IN-2, Valpraiso, IN

# TEST BORING LOG

BORING NO.: **B-01**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.450319</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.073628</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 11.0 ft ☒ At completion Dry ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.0		±12" Black, Sandy TOPSOIL.							
	2.5		SS 1	2-3-2 (5)	100	10.7			
	5.0	Brown, Moist, Fine SAND, Trace Gravel.	SS 2	1-2-3 (5)	100	11.7			
	7.5		SS 3	3-4-4 (8)	100	12.7			
688.0	8.0								
	10.0	Brown, Moist, Fine SILTY SAND, Trace Gravel and Clay.	SS 4	4-6-7 (13)	100	15.2			
685.0	11.0								
	12.5								
	15.0	Gray, Wet, Fine to Medium Coarse SILTY SAND, with Gravel.	SS 5	16-17-19 (36)	100				
	17.5								
676.0	20.0		SS 6	20-16-20 (36)	100				
	22.5	Bottom of Boring at 20.0 ft							
	25.0								

# TEST BORING LOG

BORING NO.: **B-02**  
 SHEET 1 OF 1  
**GME PROJECT NO:** **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.450325</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.073458</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 10.0 ft ☒ At completion 8.0 ft ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.0		±12" Black, Sandy TOPSOIL.							
	2.5	Brown, Moist, CLAYEY SILTY SAND, Trace Gravel.	SS 1	3-2-3 (5)	100	17.1			
693.0									
	5.0	Brown, Moist, Fine SAND, Trace Gravel.	SS 2	2-1-2 (3)	100	14.6			
	7.5		SS 3	2-2-4 (6)	100	15.1			
688.0		Brown, Very Moist, SILTY SAND.	SS 4	9-5-6 (11)	100	15.5			
686.0	10.0								
	12.5								
	15.0	Gray, Very Moist, Medium Coarse SAND and GRAVEL.	SS 5	14-13-15 (28)	100	9.8			
	17.5								
676.0	20.0	Bottom of Boring at 20.0 ft	SS 6	15-16-15 (31)	100	6.8			
	22.5								
	25.0								

# TEST BORING LOG

# TEST BORING LOG

BORING NO.: **B-04**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>697.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.450081</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.073461</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 10.0 ft ☒ At completion 8.0 ft ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
696.3		±9" ASPHALT.							
696.0		±12" Black, Sandy TOPSOIL.							
	2.5		SS 1	6-5-3 (8)	100	6.8			
	5.0		SS 2	4-3-3 (6)	100	8.6			
	7.5		SS 3	4-4-4 (8)	100	12.0			
	10.0		SS 4	10-10-9 (19)	100	16.3			
	12.5								
	15.0		SS 5	10-13-15 (28)	100				
	17.5								
	20.0		SS 6	10-15-14 (29)	100				
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-05**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449658</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.0733</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at Dry ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.8		±2" ASPHALT.							
	2.5	Brown, Moist, Fine SAND.	SS 1	10-6-4 (10)	100	6.8			
693.0									
	5.0		SS 2	3-4-3 (7)	100	7.6			
	7.5	Brown, Moist, Fine SILTY SAND, Trace Gravel, Fuel Smell to ±5'.	SS 3	5-4-4 (8)	100	15.4			
686.0	10.0		SS 4	10-8-9 (17)	100	14.0			
		Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-06**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449792</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.073897</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at 9.5 ft ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.8		±3" ASPHALT Product.							
695.2		±10" Black, Moist, Sandy ASPHALT Product.							
	2.5		SS 1	7-5-4 (9)	100	9.1			
		Brown, Moist, Fine CLAYEY SILTY SAND, Trace Gravel.							
	5.0		SS 2	3-3-3 (6)	100	14.4			
690.5									
	7.5		SS 3	3-3-3 (6)	100	15.7		2.0	
		Brown and Gray, Moist, SANDY CLAY.							
687.5									
	8.5		SS 4	4-4-5 (9)	100				
		Brown, Wet, Fine SILTY SAND, Trace Gravel.							
686.0	10.0								
		Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-07**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valparaiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449764</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074144</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 8.0 ft ☒ At completion Dry ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.8		±3" LIMESTONE Product.							
694.8		±15" Black and Dark Brown, Moist, Gravelly SAND Product.							
693.0	2.5	FILL: Brown and Black, Moist, Fine Silty Sand, Trace Gravel, Interbedded Clay Lenses.	SS 1	10-11-13 (24)	100	14.3			
	5.0		SS 2	1-1-2 (3)	100	21.3			
	7.5	Black, Very Moist, Sandy PEAT.	SS 3	2-1-1 (2)	100	23.5			
688.0	8.0		SS 4	8-9-10 (19)	100				
	10.0	Brown, Wet, Fine SILTY SAND, Trace Fine Gravel.							
684.0	12.5		SS 5	8-14-15 (29)	100				
	15.0	Gray, Wet, Fine SILTY SAND, Trace Fine Gravel.							
	17.5		SS 6	8-12-14 (26)	100				
676.0	20.0	Bottom of Boring at 20.0 ft							
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-08**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>697.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449969</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.073903</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at Dry ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
696.8		±3" LIMESTONE Product.							
695.4		±19" Black, Moist, Gravelly SAND Product.							
	2.5		SS 1	6-6-4 (10)	100	12.2			
	5.0	Brown, Moist, Fine SILTY SAND, Trace Fine Gravel.	SS 2	2-2-3 (5)	100	15.1			
691.5									
	7.5	Brown and Gray, Moist, Fine SILTY SAND, Trace Fine Gravel.	SS 3	2-3-3 (6)	100	16.2			
689.0									
	10.0	Brown, Wet, Fine SILTY SAND, Trace Fine Gravel.	SS 4	4-4-5 (9)	100				
687.0									
		Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-09**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449969</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074211</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☐ Encountered at 8.5 ft ☒ At completion 8.5 ft ☒ Caved in at 8.5 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.8		±2" LIMESTONE Products.							
694.7		Brown, Dark Stained, Moist, Gravelly SAND Product.							
	2.5	FILL: Brown and Black, Moist, Silty Sand, Trace Clay and Gravel.	SS 1	3-4-4 (8)	100	13.0			
693.0									
	5.0		SS 2	1-2-3 (5)	100	13.5			
	7.5	POSSIBLE FILL: Dark Brown and Black, Moist, Clayey Sand, Trace Organics.	SS 3	2-2-3 (5)	100	11.7			
687.0									
	10.0		SS 4	3-3-3 (6)	100				
		Brown, Wet, Very Fine SILTY SAND, Trace Gravel.							
684.0									
	12.5								
	15.0		SS 5	4-5-7 (12)	100				
		Gray, Wet, Fine SILTY SAND, Trace Fine Gravel.							
	17.5								
676.0									
	20.0		SS 6	7-8-8 (16)	100				
		Bottom of Boring at 20.0 ft							
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-10**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449961</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074486</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 9.0 ft ☒ At completion 9.0 ft ☒ Caved in at 9.5 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.5		±6" LIMESTONE Product.							
693.5	2.5	FILL: Brown and Dark Brown, Moist, Sand, Trace Gravel.	SS 1	5-7-7 (14)	100	13.2			
	5.0	FILL: Dark Brown, Moist, Fine Silty Sand, Trace Fine Gravel.	SS 2	5-6-7 (13)	100	10.0			
688.5	7.5		SS 3	6-7-6 (13)	100	10.7			
686.5	9.5	Brown, Gravelly SAND.	SS 4	5-6-7 (13)	100	20.0			
	12.5								
	15.0	Brown and Gray, Wet, Fine SILTY SAND, Trace Gravel.	SS 5	5-7-8 (15)	100				
	17.5								
676.0	20.0	Bottom of Boring at 20.0 ft	SS 6	9-10-9 (19)	100				
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-11**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>697.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449942</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074819</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 5.0 ft ☒ At completion Dry ☒ Caved in at 5.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
696.5		±6" Dark Stained, Moist, LIMESTONE Product.							
	2.5	POSSIBLE FILL: Brown, Moist, Fine to Medium Coarse Silty Sand, Trace Gravel.	SS 1	8-8-8 (16)	100	7.3			
692.0	5.0		SS 2	2-3-2 (5)	100	11.6			
	7.5	Brown, Moist, Fine to Medium Coarse SILTY SAND.	SS 3	2-2-2 (4)	100	15.8			
689.0	10.0		SS 4	6-7-8 (15)	100				
	15.0	Brown, Wet, Fine SILTY SAND, Trace Clay and Gravel.	SS 5	6-7-9 (16)	100				
677.0	20.0		SS 6	6-7-10 (17)	100				
	22.5	Bottom of Boring at 20.0 ft							
	25.0								

# TEST BORING LOG

BORING NO.: **B-12**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449828</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074494</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☐ Encountered at Dry ☒ At completion 6.5 ft ☒ Caved in at 7.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.7		±4" LIMESTONE Product.							
694.7		Black, Moist, Sandy GRAVEL Product.							
	2.5		SS 1	9-13-9 (22)	100	7.4			
	5.0	FILL: Dark Brown, Moist, Clayey Sand, Trace Gravel.	SS 2	10-11-8 (19)	100	11.1			
690.5									
	7.5	Gray, Very Moist, SILTY SAND, Trace Peat and Gravel.	SS 3	2-3-3 (6)	100	19.8			
687.5			SS 4	5-7-8 (15)	100				
	10.0								
	12.5								
	15.0	Gray and Brown, Wet, Fine SILTY SAND, Trace Gravel.	SS 5	7-9-13 (22)	100				
	17.5								
676.0	20.0		SS 6	6-7-13 (20)	100				
		Bottom of Boring at 20.0 ft							
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-13**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449753</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074853</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at 8.0 ft ☒ At completion 8.5 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
695.5		±6" LIMESTONE Product. 0.5							
694.7		Black, Moist, Sandy GRAVEL Product. 1.3							
	2.5		SS 1	6-6-7 (13)	100	13.0			
		FILL: Dark Brown and Black, Moist, Silty Sandy Clay, Trace Organics and Gravel.							
	5.0		SS 2	3-4-5 (9)	100	16.3			
690.5		5.5							
	7.5	Black, Very Moist, PEAT, and Brown, Moist, Sand, with Peat.	SS 3	4-5-5 (10)	100	26.8			
687.5		8.5							
		Brown and Gray, Wet, Fine SILTY SAND.	SS 4	4-5-6 (11)	100				
686.0	10.0	10.0							
		Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-14**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>696.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449753</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.075228</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at 8.0 ft ☒ At completion Dry ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
694.8		±15" Black Stained, Moist, LIMESTONE Product.							
	2.5	Brown, Moist, Fine SILTY SAND.	SS 1	15-8-5 (13)	100	10.6			
692.5									
	5.0		SS 2	2-3-2 (5)	100	11.6			
		Brown and Gray, Moist to Wet, Fine SILTY SAND, Trace Gravel,							
	7.5	Wet @ ±8.5'.	SS 3	2-2-2 (4)	100	17.7			
686.0	10.0		SS 4	4-3-4 (7)	100				
		Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-15**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>694.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449592</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.075042</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at Dry ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
691.5	2.5	FILL: Black, Sand and Gravel, with Cobble Stones.	SS 1	N/S-Stone- ( )					
689.0	5.0	FILL: Black, Organic Sandy Silty Clay.	SS 2	3-3-4 (7)	100	14.8			
	7.5	Gray, Moist, Fine SILTY SAND, Trace Gravel.	SS 3	4-4-5 (9)	100	16.4			
684.0	10.0		SS 4	14-14-14 (28)	100	17.2			
		Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-16**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : RS/DW

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>695.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449586</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074725</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at 8.0 ft ☒ At completion 8.5 ft ☒ Caved in at 8.8 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
692.0	2.5	FILL: Crushed Limestone Product.	SS 1	10-9-7 (16)	100	3.7			
	5.0	POSSIBLE FILL: Dark Brown and Gray, Moist, Clay with Organics, Trace Gravel.	SS 2	4-5-6 (11)	100	15.6		2.5	
687.0	7.5		SS 3	5-5-6 (11)	100	16.8	4.3	2.0	
685.0	10.0	Black, Very Moist, PEAT.	SS 4	2-2-3 (5)	100	164.7			
	12.5	Bottom of Boring at 10.0 ft							
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

# TEST BORING LOG

BORING NO.: **B-18**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>694.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449358</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074611</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at Dry ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
691.0	2.5	FILL: Black, Sand, Silty Limestone Fragments.	SS 1	12-19-17 (36)	100	9.5			
	3.0								
	5.0	POSSIBLE FILL: Dark Brown, Moist, Silty Clay, Trace Organics.	SS 2	3-2-4 (6)	100	16.8		1.0	
686.5	7.5		SS 3	4-2-4 (6)	100	24.0	0.8	0.5	
	10.0	Black, Fibrous PEAT.	SS 4	7-6-5 (11)	100	121.7			
684.0	10.0	Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-19**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>692.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449428</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.074858</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at Dry ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
689.0	2.5	MISC. FILL: Black, Moist, Sandy Clay, with Trace Gravel and Brick Fragments.	SS 1	6-7-8 (15)	100	16.6		1.5	
	3.0								
	5.0	Black, Fibrous PEAT.	SS 2	2-2-3 (5)	100	115.0			
685.5	6.5								
	7.5	Gray, Moist, CLAYEY SAND.	SS 3	4-3-2 (5)	100	19.3			
683.5	8.5								
682.0	10.0	Gray, Very Moist, Fine SAND.	SS 4	12-11-10 (21)	100	16.1			
	10.0	Bottom of Boring at 10.0 ft							
	12.5								
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-20**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>693.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449431</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.075222</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>10.0 ft</u>		

GROUNDWATER: ☒ Encountered at Dry ☒ At completion Dry

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
690.5	2.5	FILL: Dark Brown, Moist, Fine Silty Sand.	SS 1	7-4-3 (7)	100	11.8			
	5.0		SS 2	7-8-9 (17)	100	15.8			
	7.5	Gray, Moist, Fine to Medium Coarse SILTY SAND, Trace Gravel.	SS 3	10-8-8 (16)	100	12.1			
683.0	10.0		SS 4	12-13-10 (23)	100	12.0			
	12.5	Bottom of Boring at 10.0 ft							
	15.0								
	17.5								
	20.0								
	22.5								
	25.0								

# TEST BORING LOG

BORING NO.: **B-21**  
 SHEET 1 OF 1  
**GME PROJECT NO:** G23-112119  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valparaiso, IN

ELEVATION : <u>694.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449392</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.07405</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☒ Encountered at 8.0 ft ☒ At completion 8.0 ft ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
692.5	2.5	POSSIBLE FILL: Black Stained, Moist, Clayey Silty Sand, Trace Gravel.	SS 1	11-7-5 (12)	100	16.7			
690.5	3.5	Black and Gray, Moist, SILTY CLAY.	SS 2	4-7-7 (14)	100	50.7			
688.0	6.0	Black, Fibrous PEAT.	SS 3	8-5-8 (13)	100	25.7			
685.5	8.5	Gray, Moist, CLAYEY SAND, Trace Organics.	SS 4	8-9-10 (19)	100	18.3			
	15.0	Gray, Moist, Fine to Medium Coarse SILTY SAND, Trace Gravel, Interbedded Clay Lenses.	SS 5	14-15-10 (25)	100	14.6			
674.0	20.0	Bottom of Boring at 20.0 ft	SS 6	13-20-20 (40)	100	17.2			

# TEST BORING LOG

BORING NO.: **B-22**  
 SHEET 1 OF 1  
 GME PROJECT NO: **G23-112119**  
 STRUCTURE \_\_\_\_\_  
 DATUM : \_\_\_\_\_  
 DATE STARTED : 12-13-23  
 DRILLER/INSP : DB/BG

CLIENT: A&Z Engineering, LLC  
 PROJECT TYPE : Proposed Porter County Highway Garage  
 LOCATION : 1955 IN-2, Valpraiso, IN

ELEVATION : <u>693.0</u>	BORING METHOD : <u>ASTM D-1586</u>	LATITUDE : <u>41.449267</u>
STATION : _____	RIG TYPE : <u>Skid</u>	LONGITUDE : <u>-87.073853</u>
OFFSET : _____	CASING DIA. : <u>3.3 in</u>	
LINE : _____	HAMMER : <u>Auto</u>	
DEPTH : <u>20.0 ft</u>		

GROUNDWATER: ☐ Encountered at 10.0 ft ☒ At completion 8.0 ft ☒ Caved in at 8.0 ft

STRATUM ELEVATION	SAMPLE DEPTH	SOIL/MATERIAL DESCRIPTION	SAMPLE NUMBER	SPT per 6" (N)	% RECOVERY	% MOISTURE CONTENT	UNCONF. COMP., tsf	Qp (tsf)	REMARKS
691.2	2.5	±22" Black Stained, Sandy GRAVEL Product.	SS 1	10-7-5 (12)	100				
690.0	3.0	FILL: Brown, Moist, Sandy Silty Clay, Trace Gravel.							
688.0	5.0	Dark Gray, Moist, Organic SANDY CLAY.	SS 2	2-2-2 (4)	100	14.8			
	7.5		SS 3	4-2-6 (8)	100	19.1			
	10.0		SS 4	13-10-15 (25)	100	15.9			
	12.5	Gray, Moist, Fine to Medium Coarse SILTY SAND, Trace Gravel.							
	15.0		SS 5	7-8-9 (17)	100	14.7			
	17.5								
673.0	20.0	Bottom of Boring at 20.0 ft	SS 6	8-8-10 (18)	100	15.4			
	22.5								
	25.0								

# GENERAL NOTES

## SAMPLE IDENTIFICATION

Visual soil classifications are made in general accordance with the United States Soil Classification System on the basis of textural and particle size categorization, and various soil behavior and characteristics. Visual classifications should be made by appropriate laboratory testing when more exact soil identification is required to satisfy specific project applications criteria.

## RELATIVE PROPORTIONS OF COHESIONLESS SOILS

<u>Term</u>	<u>Defining Range by % of Weight</u>
Trace	1-10 %
Little	11-20 %
Some	21-35 %
And	36-50 %

### **WATER LEVEL MEASUREMENT**

NE	No Water Encountered
BF	Backfilled upon Completion

### **ORGANIC CONTENT BY COMBUSTION METHOD**

<u>Soil Description</u>	<u>LOI</u>
w/ organic matter	4-15 %
Organic Soil (A-8)	16-30 %
Peat (A-8)	More than 30%

### **LABORATORY TESTS**

Qp	Penetrometer Reading, tsf
Qu	Unconfined Strength, tsf
MC	Moisture Content, %
LL	Liquid Limit, %
PL	Plastic Limit, %
PI	Plastic Index
SL	Shrinkage Limit, %
pH	Measure of Soil Alkalinity/Acidity
$\gamma$	Dry Unit Weight, pcf
LOI	Loss of Ignition, %

## DRILLING AND SAMPLING SYMBOLS

AS	Auger Sample
BS	Bag Sample
PID	Photo ionization Detector (Hnu meter) volatile vapor level,(PPM)
COA	Clean-Out Auger
CS	Continuous Sampling
FA	Flight Auger
HA	Hand Auger
HAS	Hollow Stem Auger
NR	No Recovery
PT	3" O.D. Piston Tube Sample
RB	Rock Bit
RC	Rock Coring
REC	Recovery
RQD	Rock Quality Designation
RS	Rock Sounding
S	Soil Sounding
SS	2" O.D. Split-Barrel Sample
2ST	2" O.D. Tin-Walled Tube Sample
3ST	3" O.D. Thin-Walled Tube Sample
VS	Vane Shear Test
DB	Diamond Bit
WS	Wash Sample
RB	Roller Bit
ST	Shelby Tube, 2" O.D. or 3" O.D.
CB	Carbide Bit
WOH	Weight of the Hammer

### **GRAIN SIZE TERMINOLOGY**

### **RELATIVE DENSITY**

### **CONSISTENCY**

### **PLASTICITY**

<u>Soil fraction</u>	<u>Particle size</u>	<u>Us standard sieve size</u>	<u>Term</u>	<u>"N" Value</u>	<u>Term</u>	<u>"N" Value</u>	<u>Term</u>	<u>Plastic Index</u>
Boulders	larger than 75 mm	Larger than 3"	Very Loose	0-5	Very Soft	0-3	None to Slight	0-4
Gravel	2mm to 75 mm	#10 to 75 mm	Loose	6-10	Soft	4-5	Slight	5-7
Coarse Sand	0.425 mm to 2 mm	#40 to #10	Medium Dense	11-30	Medium Stiff	6-10	Medium	8-22
Fine Sand	0.075mm to 0.425 mm	#200 to #40	Dense	31-50	Stiff	11-15	High/Very High	Over 22
Silt	0.002 mm to 0.075 mm	Smaller than #200	Very Dense	51+	Very Stiff	16-30		
Clay	Smaller than 0.002 mm	Smaller than #200			Hard	31+		

Note(s):

The penetration resistance, "N" Value, is the summation of the number of blows required to effect two successive 6-inch penetrations of the 2-inch split-barrel sampler. The sampler is driven with a 140-lb. weight falling 30-inches and is seated to a depth of 6-inches before commencing the standard penetration test.

Water level measurements shown on the boring logs represent conditions at the time indicated and may not reflect static levels, especially in cohesive soils

## **GME TESTING**

3517 Focus Drive

Fort Wayne, IN 46818

(260) 497- 8127 • (877) 660-4GME • (260) 497- 0826 fax

Division of **GEOTECHNICAL & MATERIALS ENGINEERS, INC.**

[www.gmetesting.com](http://www.gmetesting.com)

# SOIL CLASSIFICATION CHART

MAJOR DIVISIONS			SYMBOLS		TYPICAL DESCRIPTIONS
			GRAPH	LETTER	
COARSE GRAINED SOILS  MORE THAN 50% OF MATERIAL IS LARGER THAN NO. 200 SIEVE SIZE	GRAVEL AND GRAVELLY SOILS  MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	CLEAN GRAVELS  (LITTLE OR NO FINES)		GW	WELL-GRADED GRAVELS, GRAVEL - SAND MIXTURES, LITTLE OR NO FINES
				GP	POORLY-GRADED GRAVELS, GRAVEL - SAND MIXTURES, LITTLE OR NO FINES
		GRAVELS WITH FINES  (APPRECIABLE AMOUNT OF FINES)		GM	SILTY GRAVELS, GRAVEL - SAND - SILT MIXTURES
				GC	CLAYEY GRAVELS, GRAVEL - SAND - CLAY MIXTURES
	SAND AND SANDY SOILS  MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	CLEAN SANDS  (LITTLE OR NO FINES)		SW	WELL-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES
				SP	POORLY-GRADED SANDS, GRAVELLY SAND, LITTLE OR NO FINES
		SANDS WITH FINES  (APPRECIABLE AMOUNT OF FINES)		SM	SILTY SANDS, SAND - SILT MIXTURES
				SC	CLAYEY SANDS, SAND - CLAY MIXTURES
FINE GRAINED SOILS  MORE THAN 50% OF MATERIAL IS SMALLER THAN NO. 200 SIEVE SIZE	SILTS AND CLAYS  LIQUID LIMIT LESS THAN 50			ML	INORGANIC SILTS AND VERY FINE SANDS, ROCK FLOUR, SILTY OR CLAYEY FINE SANDS OR CLAYEY SILTS WITH SLIGHT PLASTICITY
				CL	INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, SANDY CLAYS, SILTY CLAYS, LEAN CLAYS
				OL	ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY
	SILTS AND CLAYS  LIQUID LIMIT GREATER THAN 50			MH	INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS FINE SAND OR SILTY SOILS
				CH	INORGANIC CLAYS OF HIGH PLASTICITY
				OH	ORGANIC CLAYS OF MEDIUM TO HIGH PLASTICITY, ORGANIC SILTS
HIGHLY ORGANIC SOILS				PT	PEAT, HUMUS, SWAMP SOILS WITH HIGH ORGANIC CONTENTS

NOTE: DUAL SYMBOLS ARE USED TO INDICATE BORDERLINE SOIL CLASSIFICATIONS

USGS web services were down for some period of time and as a result this tool wasn't operational, resulting in *timeout* error.  
USGS web services are now operational so this tool should work as expected.



**Latitude, Longitude: 41.450319, -87.073628**



<b>Date</b>	12/18/2023, 2:45:18 PM
<b>Design Code Reference Document</b>	IBC-2012
<b>Risk Category</b>	III
<b>Site Class</b>	D - Stiff Soil

Type	Value	Description
$S_S$	0.117	$MCE_R$ ground motion. (for 0.2 second period)
$S_1$	0.064	$MCE_R$ ground motion. (for 1.0s period)
$S_{MS}$	0.188	Site-modified spectral acceleration value
$S_{M1}$	0.153	Site-modified spectral acceleration value
$S_{DS}$	0.125	Numeric seismic design value at 0.2 second SA
$S_{D1}$	0.102	Numeric seismic design value at 1.0 second SA

Type	Value	Description
SDC	B	Seismic design category
$F_a$	1.6	Site amplification factor at 0.2 second
$F_v$	2.4	Site amplification factor at 1.0 second
PGA	0.055	$MCE_G$ peak ground acceleration
$F_{PGA}$	1.6	Site amplification factor at PGA
$PGA_M$	0.088	Site modified peak ground acceleration
$T_L$	12	Long-period transition period in seconds
$S_{sRT}$	0.117	Probabilistic risk-targeted ground motion. (0.2 second)
$S_{sUH}$	0.128	Factored uniform-hazard (2% probability of exceedance in 50 years) spectral acceleration
$S_{sD}$	1.5	Factored deterministic acceleration value. (0.2 second)
$S_{1RT}$	0.064	Probabilistic risk-targeted ground motion. (1.0 second)
$S_{1UH}$	0.073	Factored uniform-hazard (2% probability of exceedance in 50 years) spectral acceleration.
$S_{1D}$	0.6	Factored deterministic acceleration value. (1.0 second)
$PGA_d$	0.6	Factored deterministic acceleration value. (Peak Ground Acceleration)
$PGA_{UH}$	0.055	Uniform-hazard (2% probability of exceedance in 50 years) Peak Ground Acceleration
$C_{RS}$	0.917	Mapped value of the risk coefficient at short periods


Type	Value	Description
C <sub>R1</sub>	0.867	Mapped value of the risk coefficient at a period of 1 s
C <sub>V</sub>		Vertical coefficient

## DISCLAIMER

While the information presented on this website is believed to be correct, SEAOC / OSHPD and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in this web application should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. SEAOC / OSHPD do not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the seismic data provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the search results of this website.

1. Sheet C105 – Site Plan
  - a. Revised dimensions of Aggregate Bays to reflect the actual size of the ecology blocks.
  - b. Added note that Aggregate Bays (Ecology Blocks) will be procured and installed by others.
  - c. Added note to HMA for Mainline Legend item to clarify procurement and installation of materials.
    - HMA materials will be procured and installed by the County
    - The contractor is responsible for the procurement and installation of Compacted Aggregate No. 53's and Geogrid BX1300.
    - The Contractor is responsible for preparation of Subgrade.
2. Sheet C106 – Grading Plan
  - a. Added spot elevations for the proposed Concrete Washout.
3. Sheet C109 – Storm Sewer Utility Plan
  - a. Added 4" Aluminum Orifice Plate to the basin's 12" outlet pipe.
4. Sheet C110 – Sanitary Sewer Utility Plan
  - a. Changed callout for Sanitary Interceptor to Sanitary Triple Basin Separator.
  - b. Revised invert elevations for the following structures:
    - Sanitary Manhole 3
    - Sanitary Triple Basin Separator
    - Sanitary Cleanouts 4, 5, 6, 7, 8 & 9
  - c. Revised slopes of sanitary sewer pipes (SDR-35) between the following structures:
    - Sanitary Cleanouts 5 & 6
    - Sanitary Cleanouts 6 & 7
    - Sanitary Cleanouts 8 & 9
5. Sheet C112 – Sanitary Sewer Profiles
  - a. SAN – 1 Profile
    - Changed callout for Sanitary Interceptor to Sanitary Triple Basin Separator.
    - Revised invert elevations for Sanitary Triple Basin Separator
  - b. SAN – 3 Profile
    - Revised invert elevations and slopes of pipes
    - Added 8" PVC Storm Drain crossing
6. Sheets C117 to C119 – Miscellaneous Details
  - a. Added Orifice Restrictor detail to C117
  - b. Moved RIPRAP Swale Section (Adjacent to Aggregate Storage) and RIPRAP Swale Typical Section from C118 to C119
  - c. Added Concrete Truck Washout detail to C118
  - d. Revised "Grade to Inlet Invert" and "Grade to Outlet Invert" for 550 Gallon Triple-Basin Detail.
7. Provided Geotechnical Report

S:\2023 Projects\23-1529 Porter County Vapo Site-Design\CD\231529 SITE PLAN.dwg-----6/7/2024-----MHHHML--Landscape




New Construction Work for :

# Porter County Highway Department - Central Facility

1955 IN-2  
Valparaiso, IN 46383



**A & Z ENGINEERING**  
1220 Ruston Pass  
Fort Wayne, IN 46825  
260-485-7077  
www.az-engineering.net



BY: *Warren J. Zwick*  
DATE: 5-24-2024



ALL IDEAS, DESIGN, ARRANGEMENTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY AND THE PROPERTY OF A&Z ENGINEERING, LLC. AND WILL BE KEPT IN CONFIDENTIALITY AND NOT BE REPRODUCED OR USED IN CONNECTION WITH THE PROJECT. NO PART OF THIS DESIGN, ARRANGEMENTS OR PLANS SHALL BE USED BY OR DISCLOSED TO ANY PERSON OR ENTITY WITHOUT THE WRITTEN PERMISSION OF A&Z ENGINEERING, LLC. THE USER OF THIS DRAWING SHALL BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS ON THE JOB AND THIS OFFICE SHALL BE NOTIFIED OF ANY VARIATION FROM THE DIMENSIONS AND CONDITIONS SHOWN IN THESE DRAWINGS. SHOP DETAILS MUST BE SUBMITTED TO THE OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

REVISION: AD-1 - ADDENDUM #1  
DATE: 06/04/24

DRAWN BY: PDH  
COMMISSION NUMBER: F22146  
REVIEWED BY: LSG  
DATE: 2024-05-24

# C105

SITE PLAN



**LEGEND**

— ST — PROPOSED SANITARY SEWER

==== PROPOSED STORM SEWER

== == EXISTING STORM SEWER

— SAN — EXISTING SANITARY SEWER


New Construction Work for :

# Porter County Highway Department - Central Facility

1955 IN-2  
Valparaiso, IN 46383



1220 Ruston Pass  
Fort Wayne, IN 46825  
260.485.7077  
[www.az-engineering.net](http://www.az-engineering.net)



BY: Warren Lewis  
DATE: 5-24-2024

ALL IDEAS, DESIGNS, ARRANGEMENTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY, AND THE PROPERTY OF ALZ ENGINEERING, LLC, AND HEREIN CREATED, EVOLVED, AND DEVELOPED FOR USE ON, AND IN CONNECTION WITH THE SPECIFIED PROJECT. NONE OF THE IDEAS, DESIGNS, ARRANGEMENTS OR PLANS SHALL BE USED OR DISCLOSED TO ANY PERSON OR ENTITY FOR ANY REASON OR IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF ALZ ENGINEERING, LLC. ANY VARIATIONS OR DIMENSIONS ON THESE DRAWINGS SHALL HAVE PRECEDENCE OVER SCALE DIMENSIONS. CONTRACTORS SHALL VERIFY AND BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS ON THE JOB AND THIS OFFICE MUST BE NOTIFIED OF ANY VARIATION FROM THE DIMENSIONS AND CONDITIONS SHOWN BY THESE DRAWINGS. SHOP DETAILS MUST BE SUBMITTED TO THIS OFFICE FOR REVIEW AND APPROVAL. THIS OFFICE WILL NOT BE RESPONSIBLE FOR ANY VARIATIONS FROM THE DIMENSIONS AND CONDITIONS SHOWN BY THESE DRAWINGS. THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

REVISION:  
AD-1 - ADDENDUM #1

DATE:  
05/04/24



DRAWN BY: PDH  
COMMISSION NUMBER: F2214

REVIEWED BY: LSG  
DATE: 2024-09-10

# C106

## GRADING PLAN

S:\2023 Projects\23-1529 Porter County Vapo Site-Design\CD\231529 UTI PLAN.dwg---6/14/2024---1" = 30'---Landscape



LEGEND  
--- SAN --- PROPOSED SANITARY SEWER  
--- STM --- PROPOSED STORM SEWER  
--- SAN --- EXISTING STORM SEWER  
--- SAN --- EXISTING SANITARY SEWER

New Construction Work for :

# Porter County Highway Department - Central Facility

1955 IN-2  
Valparaiso, IN 46383



1220 Ruston Pass  
Fort Wayne, IN 46825  
260-485-7077  
www.az-engineering.net



BY: *Warren J. Zwick*  
DATE: 5-24-2024

ALL IDEAS, DESIGN, ARRANGEMENTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY AND THE PROPERTY OF A&Z ENGINEERING, LLC. AND ARE NOT TO BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF A&Z ENGINEERING, LLC. NO PART OF THIS DRAWING SHALL BE USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF A&Z ENGINEERING, LLC. THE DESIGNER AND CONTRACTOR SHALL BE RESPONSIBLE FOR THE DESIGN AND CONSTRUCTION OF THE PROJECT. THE DESIGNER SHALL BE RESPONSIBLE FOR THE DESIGN AND CONSTRUCTION OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONSTRUCTION OF THE PROJECT. THE DESIGNER SHALL BE RESPONSIBLE FOR THE DESIGN AND CONSTRUCTION OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONSTRUCTION OF THE PROJECT.

REVISION:  
AD-1 - ADDENDUM #1

DATE:  
06/04/24

DRAWN BY: PDH  
COMMISSION NUMBER: F22146



REVIEWED BY: LSG  
DATE: 2024-05-24

# C109

STORM SEWER  
UTILITY PLAN

NOTE: ALL OPEN FLARED-ENDED  
PIPES SHALL HAVE A DEBRIS/ANIMAL  
GUARD.

S:\2023 Projects\23-1528 Porter County Vapo Site-Design\CD\231528 SAN-SEWER PLAN.dwg--6/1/2024--1" = 30'--LondonDrog




New Construction Work for :

# Porter County Highway Department - Central Facility

1955 IN-2  
Valparaiso, IN 46383



**A & Z ENGINEERING**  
1220 Ruston Pass  
Fort Wayne, IN 46825  
260-485-7077  
www.az-engineering.net



BY: *Warren J. Zwick*  
DATE: 5-24-2024

ALL DESIGN, DESIGN ARRANGEMENTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY AND THE PROPERTY OF A&Z ENGINEERING, LLC. AND ARE NOT TO BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF A&Z ENGINEERING, LLC. THE USER OF THIS DRAWING SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES AND FOR THE LIMITED PURPOSE OF OBTAINING PERMITS FOR CONSTRUCTION OF THE PROJECT AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH CONSTRUCTION.



REVISION: AD-1 - ADDENDUM #1 DATE: 06/04/24

DRAWN BY: PDH COMMISSION NUMBER: F22146 REVIEWED BY: LSG DATE: 2024-05-24


# C110

SANITARY SEWER  
UTILITY PLAN

S:\2023 Projects\23-1529 Porter County Valpo Sewer Design\CAD\231529 DESIGN BASE - REVISED.dwg -- 6/7/2024 -- MHHH -- London Group



ALL STORM SEWER, SANITARY SEWER AND WATER MAIN CROSSINGS SHALL MEET A MINIMUM OF 18" SEPARATION. ALL PROPOSED PARALLEL WATER MAIN AND SEWER LINES SHALL MEET A MINIMUM 10 FT. SEPARATION.




New Construction Work for :

# Porter County Highway Department - Central Facility

1955 IN-2  
Valparaiso, IN 46383

**A & Z ENGINEERING**  
1220 Ruston Pass  
Fort Wayne, IN 46825  
260-485-7077  
www.az-engineering.net



BY: *Warren J. Zwick*  
DATE: 5-24-2024

ALL IDEAL DESIGN ARRANGEMENTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY AND THE PROPERTY OF A&Z ENGINEERING, LLC. AND BEING CREATED, DEVELOPED, AND DESIGNED FOR USE ON, AND IN CONNECTION WITH THE SPECIFIC PROJECT. NONE OF THE IDEAL DESIGN, ARRANGEMENTS, OR PLANS SHALL BE USED BY OR DISCLOSED TO ANY PERSON OR ENTITY OTHER THAN THE CLIENT WITHOUT THE WRITTEN PERMISSION OF A&Z ENGINEERING, LLC. THE CLIENT SHALL BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS ON THE JOB AND THIS OFFICE SHALL BE NOTIFIED OF ANY VARIATION FROM THE DIMENSIONS AND CONDITIONS SHOWN IN THESE DRAWINGS. ASPECT DETAILS MUST BE SUBMITTED TO THIS OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

REVISION:  
AD-1 - ADDENDUM #1

DATE:  
06/04/24

DRAWN BY: PDH  
COMMISSION NUMBER: F22146  
REVIEWED BY: LSG  
DATE: 2024-05-24

# C112

SANITARY SEWER  
PROFILES



Technical drawing of a rectangular concrete foundation for a 401 column. The drawing shows a plan view of the foundation with dimensions and reinforcement details. The overall width is 26'-0" and the overall length is 48'-0". The foundation is 15'-0" wide and 8'-0" deep. The reinforcement includes #401 bars at 12" O.C. and #4 bars at 14 1/2" O.C. The concrete is 4000 PSI. The drawing also shows a 1" chamfer on the top corner of the foundation.

1 1/2" ASPHALT SURFACE COURSE

2 1/2" ASPHALT BASE COURSE

12" AGGREGATE BASE ON BX1300 (OR APPROVED EQUAL)

12" MIN. COMPACTED SUBGRADE, UNIFORMLY COMPACTED TO A MINIMUM OF 95% OF STANDARD PROCTOR MAX. DRY DENSITY (ASTM D-698)

TACK COAT BETWEEN LIFTS

[illegible]

9" CONCRETE PAVEMENT

NOTES:  
1.) CONTROL JOINTS 15'-0" O.C. MAX.

12" AGGREGATE BASE ON  
BX1300 (OR APPROVED EQUAL)


12" MIN. COMPACTED SUBGRADE, UNIFORMLY COMPACTED TO  
A MINIMUM OF 95% OF STANDARD PROCTOR MAX. DRY  
DENSITY (ASTM D-698)

4" CONCRETE PAVEMENT

2" AGG. LEVELING COURSE

4"


NOTE: ALL CONCRETE FLATWORK SHALL ADHERE TO PORTER COUNTY CONSTRUCTION STANDARD SECTIONS 8.06, 8.07 & 8.08 WITH REGARD TO DETAILS C, F, K & W.



**Ecology Block**  
Weight — 2,400 Lbs.

SPECIFICATIONS:

1. Concrete: Design Strength of 5500 PSI at 28 Days.
2. Steel Reinforcement: ASTM A-615 Grade 60.

 <b>Oldcastle Precast</b> <sup>®</sup> 13600 S. Wayside Dr., Houston, TX 77048 Phone: 713-991-2400 Fax: 713-991-0815	<b>2'-0" X 4'-0" X 2'-0" O.D.</b>	<b>ECOLOGY BLOCK</b>
	FILE NAME: 264MAM242EB.DWG	
	ISSUE DATE: JANUARY, 2007	
	<a href="http://www.oldcastlehouston.com">www.oldcastlehouston.com</a>	


Copyright © 2007 **Oldcastle** Precast Inc.



**Oldcastle Precast®**  
 13600 S. Wayside Dr., Houston, TX 77048  
 Phone: 713-991-2400 Fax: 713-991-0815


## CANTILEVER SLIDE GATES

**Gate without barbed wire**




- Must be used for automatic slide gate operators.
- Excellent for areas where the arc of the swing gate will interfere with storage area or roadways.
- Maximum single gate opening width of 30' (double gate width of 60').
- Most common single gate opening width of 24'.
- Gate is fully supported off the ground on four rollers.
- Gate posts (3 required for single gate, 4 required for double gate)
- Four rollers required for each gate panel.

**Gate with barbed wire**



TOTAL GATE LENGTH



1" POST CENTER 1/2 OF GATE OPENING

8 1/4" GATE ROLLERS

5 1/2" LESS RAILANCE HEIGHT



GATE OPENING

4" (MAXIMUM)

GATE ROLLERS

Total gate length = opening size x 1.5, then add 1' (eg. 24' opening: 24' x 1.5 = 36', 36' + 1' = 37')

MISC. DETAILS



New Construction Work for :  
Porter County Highway Department -  
Central Facility

---

1955 IN-2  
Valparaiso, IN 46383



ALL IDEAS, DESIGNS, ARRANGEMENTS, LISTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY, AND THE PROPERTY OF A&Z ENGINEERING, LLC, AND HAVE CREATED, EVOLVED, AND DEVELOPED FOR USE ON, AND IN CONNECTION WITH THIS SPECIFIC PROJECT. NONE OF THE IDEAS, DESIGNS, ARRANGEMENTS OR PLANS SHALL BE USED OR DISCLOSED TO ANY OTHER FIRM OR CORPORATION FOR ANY PURPOSE WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF A&Z ENGINEERING, LLC. ANY REUSE OF ANY OF THE IDEAS, DESIGNS, ARRANGEMENTS OR PLANS WITHOUT THE WRITTEN PERMISSION OF A&Z ENGINEERING, LLC, SHALL BE CONSIDERED A VIOLATION OF THE TERMS OF THIS AGREEMENT. A&Z ENGINEERING, LLC, SHALL BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS ON THE JOB AND THIS OFFICE MUST BE NOTIFIED OF ANY VARIATION FROM DIMENSIONS AND CONDITIONS SHOWN BY THESE DRAWINGS. SHOP DETAILS MUST BE SUBMITTED TO THIS OFFICE FOR REVIEW THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

DRAWN BY: PDH  
COMMISSION NUMBER: F22146

REVIEWED BY: LSG  
DATE: 2024-05-24

# C119

## MISC. DETAILS

# ADDENDUM ONE

Porter County Highway Department  
1955 IN-2  
Valparaiso, IN 46385

MARTINRILEY architects/engineers  
221 West Baker Street  
Fort Wayne, Indiana 46802  
260-422-7994

Commission No.: F22146

Addendum Date: 12 June 2024

**Conditions:** The following clarifications, amendments, additions, deletions, revisions and modifications are a part of the contract documents and change the original documents only in the manner and to the extent stated.

Copies of the Addendum shall be bound with all contract sets of drawings and specifications.

## CLARIFICATIONS:

There are no anticipated locations of double wall duct.

Owner will provide their existing air compressor. Contractor is responsible for moving and installing. Compressor is a Sullair rotary screw air compressor, Model ST0510AC, Serial CN0122080703 with built-in dryer.

Porter County does not require any specific proprietary temperature control vendor for this project. Remainder of requirements as indicated in specification for compatibility are still required.

Section 08 3613 Sectional Doors, Paragraph 2.06.G. **CLARIFY** the 20 transmitters are only for Doors 140B and 140E associated with Truck Parking 140. The operation of these two doors can be combined onto (1) transmitter as long as both buttons meet size requirements. All other overhead doors two have (2) transmitters as applicable.

Section 08 3613 Sectional Doors, Paragraph 2.06.G.3 **CLARIFY** reference to transmitters to "accommodate winter clothing". Buttons should have a minimum size of 1 ½" x ½" to meet this requirement.

## CHANGES TO THE SPECIFICATIONS:

Section 00 0110 Table of Contents, **REPLACE** attached section to volume.

Section 07 4213 Metal Wall Panels, **MODIFY** Paragraph 2.02.B.1. to read, "Profile: Vertical;". **ADD** sub-paragraph 2.02.B.1.a to read, "Basis of Design: Butler Thermawall Fluted Panels" with additional sub-paragraph 2.02.B.1.a.1 to read, "Main Building"

Section 07 4213 Metal Wall Panels, **ADD** Paragraph 2.02.B.1.b. to read, "Basis of Design: Butler Stylwall II Fluted Panels". **ADD** additional sub-paragraph 2.02.B.1.b.1 to read, "Cold Storage"

Section 07 7100 Roof Specialties, **ADD** section to volume.

Section 10 2800 Toilet, Bath, and Laundry Accessories, **ADD** "Bobrick: [www.bobrick.com](http://www.bobrick.com)" as a third approved manufacturer.

Section 11 1119 Vehicle Lubrication Equipment, **ADD** Paragraph 2.02.A.2 to read, "Air: Graco; SDL65B: [www.graco.com](http://www.graco.com)".

Section 11 1119 Vehicle Lubrication Equipment, **ADD** Paragraph 2.02.A.3 to read, "Coolant: Graco; SDL65B: [www.graco.com](http://www.graco.com)".

Section 11 1119 Vehicle Lubrication Equipment, **MODIFY** Paragraph 2.02.A.1 to read, "Oils: Graco; SDM65B: [www.graco.com](http://www.graco.com)".

Section 11 1119 Vehicle Lubrication Equipment, **ADD** Paragraph 2.02.F to read, "Provide hose retraction stops".

Section 23 3100 HVAC Ducts and Casings, **DELETE** the word "outer" from paragraphs 2.02.B.1 and 2.02.C.1.

Section 41 2200 Hoists and Cranes, **ADD** Paragraph 2.01.B.8.c to read, "Wire Rope".

Section 41 2200 Hoists and Cranes, **MODIFY** Paragraph 2.01.A.3 to indicate an operating temperature range to 115 degrees F instead of current indication.

#### **CHANGES TO DRAWINGS:**

Sheet S001 Structural Specifications **MODIFY** Structural Design Criteria. Add "Main Building and Cold Storage" after "1. Risk Category II:".

Sheet S001 Structural Specifications **MODIFY** Structural Design Criteria. Add "2. Risk Category I: Salt Barn" with sub line item "a. Design Engineer to determine minimum uniform snow load and other criteria".

Sheet A001 Life Safety Plan - Central Facility **MODIFY** General Fire Protection Note 8. Add the following sentence to the end of the existing note. "Wash Bay 137 pipe and fittings to be galvanized."

Sheet A002 Life Safety Plans - Cold Storage / Salt Barn **MODIFY** Salt Barn Code Summary classification to indicate S-2 Low Hazard Storage. **MODIFY** allowable square footage to 13,635 square feet and height of 2 stories

Sheet A104 Enlarged Plans **MODIFY / ADD** dimensions for Door 134C and Door 137A.

Sheet A510 Door Schedule and Details **DELETE** Door 150I reference from schedule.

Sheet A510 Door Schedule and Details **MODIFY** Door 160A. Door and frame material to indicate "FIBER".

Sheet A510 Door Schedule and Details **MODIFY** Door 160A. Door and frame material to indicate "FIBER".

Sheet A520 Window Schedule and Details **MODIFY** Detail I/A520. Transaction window counter should be noted, "Solid Surface (SS-1) counter, 4" depth on each side of wall, eased edge".

Sheet A601 Room Finish Schedule and Interior Elevations **DELETE** Rooms 110, 111, and 112 from Room Finish Schedule.

Sheet A601 Room Finish Schedule and Interior Elevations **MODIFY** Room Finish Schedule line item 105 to indicate "CPT-1" floor finish.

Sheet A601 Room Finish Schedule and Interior Elevations **MODIFY** Room Finish Schedule line item 109 to indicate "CPT-2" floor finish.

Sheet A601 Room Finish Schedule and Interior Elevations **MODIFY** Room Finish Schedule line item 121 to indicate "R-1" floor finish.

Sheet A602 Finish Plans **MODIFY** floor finish in Mech Foreman 109 to indicate CPT-2.

Sheet R201 Roof Details **MODIFY** Detail 2 to indicate Work Description Note 20 at all roof insulation locations.

Sheet R201 Roof Details **MODIFY** Details 2 and 3 to remove blanket wall insulation.

Sheet R201 Roof Details **MODIFY** Work Description Note 26 to read, "New manufacturers prefinished GI corrugated wall panel or insulated metal wall panel, refer to wall sections and specifications".

Sheet R201 Roof Details **MODIFY** Detail 7 to remove Work Description Note 48 and move Work Description Note 47.

Sheet R201 Roof Details **MODIFY** Work Description Note 47 to read, "Refer to wall sections for wall composition".

Sheet R201 Roof Details **MODIFY** Work Description Note 20 to read, "New R-19 blanket insulation with vapor retarder at Central Facility. Cold Storage Building does not require insulation".

Sheet P103 Plumbing Plan - Maintenance **MODIFY** Work Description Note 5. Delete "at 23' AFF" from first sentence. Add ", refer to A302" at end of second sentence.

Sheet E102 Electrical Power Plan **ADD** "MDP" reference in Electrical 142.

Sheet E501 Electrical Schedules & Details **MODIFY** wire size reference between MDP and Transfer Switch.

Sheet E502 Electrical Schedules & Details **MODIFY** Main rating for Panel: MDP to 800A.

**ATTACHMENTS:**

S001	A001	Spec 00 0110 - Table of Contents
A002	A104	Spec 07 4213 - Metal Wall Panels
A510	A520	Spec 07 7100 - Roof Specialties
A601	A602	Spec 10 2800 - Toilet, Bath, and Laundry Accessories
R201	P103	Spec 11 1119 - Vehicle Lubrication Equipment
E102	E501	Spec 23 3100 - HVAC Ducts and Casings
E502		Spec 41 2200 - Hoists and Cranes

**END OF ADDENDUM NUMBER ONE**

**SECTION 00 0110  
TABLE OF CONTENTS****PROCUREMENT AND CONTRACTING REQUIREMENTS****DIVISION 00 -- PROCUREMENT AND CONTRACTING REQUIREMENTS**

00 0105 - Certifications Page

00 0110 - Table of Contents

**SPECIFICATIONS****DIVISION 01 -- GENERAL REQUIREMENTS****DIVISION 02 -- EXISTING CONDITIONS**

02 4100 - Demolition

**DIVISION 03 -- CONCRETE**

03 3000 - Cast-in-Place Concrete (Refer within and S001)

03 4500 - Precast Architectural Concrete

**DIVISION 04 -- MASONRY**

04 2000 - Unit Masonry (Refer within and S001)

**DIVISION 05 -- METALS**

05 1200 - Structural Steel Framing (Refer to S001)

05 2100 - Steel Joist Framing (Refer to S001)

05 3100 - Steel Decking (Refer to S001)

05 5000 - Metal Fabrications

05 5213 - Pipe and Tube Railings

**DIVISION 06 -- WOOD, PLASTICS, AND COMPOSITES**

06 1000 - Rough Carpentry

06 4100 - Architectural Wood Casework

**DIVISION 07 -- THERMAL AND MOISTURE PROTECTION**

07 1010 - General Roofing Considerations

07 2100 - Thermal Insulation

07 2119 - Foamed-In-Place Insulation

07 2700 - Air Barriers

07 4113 - Metal Roof Panels

07 4213 - Metal Wall Panels

07 5400 - Thermoplastic Membrane Roofing

07 6200 - Sheet Metal Flashing and Trim

07 7100 - Roof Specialties

07 8400 - Firestopping

07 9200 - Joint Sealants

**DIVISION 08 -- OPENINGS**

08 1113 - Hollow Metal Doors and Frames

08 1416 - Flush Wood Doors

08 1613 - Fiberglass Doors  
08 3323 - Overhead Coiling Doors  
08 3613 - Sectional Doors  
08 4313 - Aluminum-Framed Storefronts  
08 4523 - Fiberglass-Sandwich-Panel Assemblies - Kalwall  
08 7100 - Door Hardware  
08 8000 - Glazing  
08 8300 - Mirrors

**DIVISION 09 -- FINISHES**

09 2116 - Gypsum Board Assemblies  
09 5100 - Acoustical Ceilings  
09 6500 - Resilient Flooring  
09 6700 - Fluid-Applied Flooring  
09 6813 - Tile Carpeting  
09 9113 - Exterior Painting  
09 9123 - Interior Painting  
09 9600 - High-Performance Coatings

**DIVISION 10 -- SPECIALTIES**

10 1423 - Panel Signage  
10 2113.19 - Plastic Toilet Compartments  
10 2800 - Toilet, Bath, and Laundry Accessories  
10 4400 - Fire Protection Specialties  
10 5113 - Metal Lockers

**DIVISION 11 -- EQUIPMENT**

11 1119 - Vehicle Lubrication Equipment

**DIVISION 12 -- FURNISHINGS**

12 2113 - Horizontal Louver Blinds  
12 3600 - Countertops

**DIVISION 13 -- SPECIAL CONSTRUCTION**

13 3100 - Fabric Structures  
13 3419 - Metal Building Systems

**DIVISION 14 -- CONVEYING EQUIPMENT****DIVISION 21 -- FIRE SUPPRESSION****DIVISION 22 -- PLUMBING**

22 0516 - Expansion Fittings and Loops for Plumbing Piping  
22 0517 - Sleeves and Sleeve Seals for Plumbing Piping  
22 0519 - Meters and Gages for Plumbing Piping  
22 0523 - General-Duty Valves for Plumbing Piping  
22 0529 - Hangers and Supports for Plumbing Piping and Equipment  
22 0533 - Heat Tracing for Plumbing Piping  
22 0548 - Vibration and Seismic Controls for Plumbing Piping and Equipment

22 0553 - Identification for Plumbing Piping and Equipment  
22 0716 - Plumbing Equipment Insulation  
22 0719 - Plumbing Piping Insulation  
22 0913 - Instrumentation and Control Devices for Plumbing  
22 1005 - Plumbing Piping  
22 1006 - Plumbing Piping Specialties  
22 1123 - Domestic Water Pumps  
22 1500 - General-Service Compressed-Air Systems  
22 3000 - Plumbing Equipment  
22 4000 - Plumbing Fixtures

**DIVISION 23 -- HEATING, VENTILATING, AND AIR-CONDITIONING (HVAC)**

23 0517 - Sleeves and Sleeve Seals for HVAC Piping  
23 0529 - Hangers and Supports for HVAC Piping and Equipment  
23 0548 - Vibration and Seismic Controls for HVAC  
23 0553 - Identification for HVAC Piping and Equipment  
23 0593 - Testing, Adjusting, and Balancing for HVAC  
23 0713 - Duct Insulation  
23 0716 - HVAC Equipment Insulation  
23 0719 - HVAC Piping Insulation  
23 0913 - Instrumentation and Control Devices for HVAC  
23 0923 - Direct-Digital Control System for HVAC  
23 0934 - Variable-Frequency Motor Controllers  
23 1123 - Facility Natural-Gas Piping  
23 2300 - Refrigerant Piping  
23 3100 - HVAC Ducts and Casings  
23 3300 - Air Duct Accessories  
23 3423 - HVAC Power Ventilators  
23 3516 - Engine Exhaust Systems  
23 3600 - Air Terminal Units  
23 3700 - Air Outlets and Inlets  
23 5233 - Packaged, Modular Water-Tube Boilers  
23 5533 - Fuel-Fired Unit Heaters  
23 7413 - Packaged Outdoor Central-Station Air-Handling Units  
23 8113 - Packaged Terminal Air-Conditioners  
23 8126.13 - Small-Capacity Split-System Air Conditioners  
23 8200 - Convection Heating and Cooling Units

**DIVISION 26 -- ELECTRICAL**

26 0519 - Low-Voltage Electrical Power Conductors and Cables (600 V and Less)  
26 0526 - Grounding and Bonding for Electrical Systems  
26 0529 - Hangers and Supports for Electrical Systems  
26 0534 - Conduit

26 0533.16 - Boxes for Electrical Systems

26 0583 - Wiring Connections

26 2200 - Low-Voltage Transformers

**DIVISION 27 -- COMMUNICATIONS**

**DIVISION 28 -- ELECTRONIC SAFETY AND SECURITY**

**DIVISION 31 -- EARTHWORK**

**DIVISION 32 -- EXTERIOR IMPROVEMENTS**

**DIVISION 33 -- UTILITIES**

**2.01 DIVISION 41 -- MATERIAL PROCESSING AND HANDLING EQUIPMENT**

41 2200 - Hoists and Cranes

**END OF SECTION**

**SECTION 07 4213  
METAL WALL PANELS****PART 1 GENERAL****1.01 SECTION INCLUDES**

- A. Manufactured metal panels for exterior wall panels and interior liner panels, with insulation, related flashings, and accessory components.

**1.02 RELATED REQUIREMENTS**

- A. Section 07 2100 - Thermal Insulation.
- B. Section 07 9200 - Joint Sealants: Sealing joints between metal wall panel system and adjacent construction.
- C. Section 13 3419 - Metal Building Systems

**1.03 REFERENCE STANDARDS**

- A. ASTM A792/A792M - Standard Specification for Steel Sheet, 55% Aluminum-Zinc Alloy-Coated by the Hot-Dip Process; 2023.

**1.04 SUBMITTALS**

- A. See Skillman 01 3300 - Submittal Procedure 01 3000 - Administrative Requirements for submittal procedures.
- B. Shop Drawings: Indicate dimensions, layout, joints, construction details, support clips, and methods of anchorage.

**1.05 QUALITY ASSURANCE**

- A. Manufacturer Qualifications: Company specializing in manufacturing products specified in this section with minimum three years of documented experience.
- B. Installer Qualifications: Company specializing in installing products specified in this section with minimum three years of documented experience.

**1.06 DELIVERY, STORAGE, AND HANDLING**

- A. Protect panels from accelerated weathering by removing or venting sheet plastic shipping wrap.
- B. Store prefinished material off the ground and protected from weather; prevent twisting, bending, or abrasion; provide ventilation; slope metal sheets to ensure proper drainage.
- C. Prevent contact with materials that may cause discoloration or staining of products.

**1.07 FIELD CONDITIONS**

- A. Do not install wall panels when air temperature or relative humidity are outside manufacturer's limits.

**1.08 WARRANTY**

- A. See Skillman Section 01 7800 - Closeout Submittals for additional warranty requirements.

**PART 2 PRODUCTS****2.01 MANUFACTURERS**

- A. Design is based on Stylwall II Fluted Wall System manufactured by Butler Manufacturing.
- B. Same as Building Manufacturer

**2.02 METAL WALL PANEL SYSTEM**

- A. Wall Panel System: Factory fabricated prefinished metal panel system, site assembled.
  - 1. Provide exterior wall panels, interior liner panels, and subgirt framing assembly.

2. Design and size components to support assembly dead loads, and to withstand live loads caused by positive and negative wind pressure acting normal to plane of wall.
  3. Design Pressure: In accordance with applicable codes.
  4. Maximum Allowable Deflection of Panel:  $L/90$  for length(L) of span.
  5. Movement: Accommodate movement within system without damage to components or deterioration of seals, movement between system and perimeter components when subject to seasonal temperature cycling; dynamic loading and release of loads; and deflection of structural support framing.
  6. Drainage: Provide positive drainage to exterior for moisture entering or condensation occurring within panel system.
  7. Fabrication: Formed true to shape, accurate in size, square, and free from distortion or defects; pieces of longest practical lengths.
  8. Corners: Factory-fabricated in one continuous piece with minimum 18-inch returns.
  9. Exterior Finish: Panel manufacturer's standard polyvinylidene fluoride (PVDF) coating, top coat over epoxy primer.
  10. Interior Panel Finish: Panel manufacturer's standard siliconized polyester coating, top coat over recommended primer
- B. Exterior Wall Panels:
1. Profile: Vertical;
    - a. Basis of Design: Butler Thermawall Fluted Panels
      - 1) Main Building
    - b. Basis of Design: Butler Stylwall II Fluted Panels
      - 1) Cold Storage
  2. Side Seams: Manufacturer's standard, sealed with continuous gaskets.
  3. Material: Precoated steel sheet, 24 gage, 0.
  4. Panel Width: 36 inches.
  5. Color: As selected by Architect from manufacturer's standard line.
- C. Interior Liner Panels:
1. Profile: Vertical.
  2. Side Seams: Interlocking, unsealed.
  3. Material: Precoated steel sheet, 26 gauge, 0.0188 inch minimum thickness.
  4. Color: As selected by Architect from manufacturer's standard line.
- D. Subgirt Framing Assembly:
1. Profile as indicated; to attach panel system to building.
- E. Internal and External Corners: Same material, thickness, and finish as exterior sheets; profile to suit system; shop cut and factory mitered to required angles.
- F. Trim: Same material, thickness and finish as exterior sheets; brake formed to required profiles.
- G. Anchors: Galvanized steel.

## 2.03 MATERIALS

- A. Precoated Steel Sheet: Hot-dipped galvanized steel sheet, ASTM A653/A653M, Structural Steel (SS) or Forming Steel (FS), with G90/Z275 coating; continuous coil-coated on exposed surfaces with specified finish coating and on panel back with specified panel back coating.
- B. Insulation: Various types specified in Section 07 2100.

## 2.04 FINISHES

- A. Panel Backside Finish: Panel manufacturer's standard siliconized polyester wash coat.
- B. Interior Application, Panel Finish: Panel manufacturer's standard siliconized polyester coating, top coat over recommended primer.
- C. Fluoropolymer Coil Coating System: Polyvinylidene fluoride (PVDF) multi-coat superior performing organic coatings system complying with AAMA 2605, including at least 70 percent PVDF resin, and at least 80 percent of coil coated metal surfaces having minimum total dry film thickness (DFT) of 0.9 mil, 0.0009 inch; color and gloss as scheduled.

**2.05 ACCESSORIES**

- A. Gaskets: Manufacturer's standard type suitable for use with system, permanently resilient; ultraviolet and ozone resistant.
- B. Sealants:
  - 1. Concealed Sealants: Non-curing butyl sealant or tape sealant, see Section 07 9200
  - 2. Exposed Sealant: Elastomeric; silicone, polyurethane, or silyl-terminated polyether/polyurethane.
- C. Fasteners: Manufacturer's standard type to suit application; with soft neoprene washers, steel, hot dip galvanized. Fastener cap same color as exterior panel.
- D. Field Touch-up Paint: As recommended by panel manufacturer.

**PART 3 EXECUTION****3.01 EXAMINATION**

- A. Verify that building framing members are ready to receive panels.

**3.02 INSTALLATION**

- A. Install panels on walls in accordance with manufacturer's instructions.
- B. Protect surfaces in contact with cementitious materials and dissimilar metals with bituminous paint; allow to dry prior to installation.
- C. Fasten panels to structural supports; aligned, level, and plumb.
- D. Locate joints over supports. Lap panel ends minimum 2 inches.
- E. Provide expansion and control joints where indicated.
- F. Use concealed fasteners unless otherwise indicated by Architect.
- G. Seal and place gaskets to prevent weather penetration. Maintain neat appearance.

**3.03 TOLERANCES**

- A. Offset From True Alignment Between Adjacent Members Abutting or In Line: 1/16 inch, maximum.
- B. Variation from Plane or Location As Indicated on Drawings: 1/4 inch, maximum.

**3.04 CLEANING**

- A. Remove site cuttings from finish surfaces.
- B. Clean and wash prefinished surfaces with mild soap and water; rinse with clean water.

**END OF SECTION**

**SECTION 07 7100  
ROOF SPECIALTIES****PART 1 GENERAL****1.01 SECTION INCLUDES**

- A. Pipe Seal Flashings
- B. Pipe seal curb
- C. Walkpads

**1.02 RELATED REQUIREMENTS**

- A. Section 07 9200 - Joint Sealers.

**1.03 REFERENCE STANDARDS**

- A. ASTM A 653/A 653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process; 2007.
- B. ASTM B 209 - Standard Specification for Aluminum and Aluminum-Alloy Sheet and Plate; 2007.
- C. ASTM B 209M - Standard Specification for Aluminum and Aluminum-Alloy Sheet and Plate [Metric]; 2007.
- D. ASTM C 920 - Standard Specification for Elastomeric Joint Sealants; 2005.
- E. ASTM D4586/D4586M - Standard Specification for Asphalt Roof Cement, Asbestos-Free; 2007 (Reapproved 2018).
- F. NRCA (RM) - The NRCA Roofing Manual; 2024.
- G. ASTM D 4479 - Standard Specification for Asphalt Roof Coatings - Asbestos-Free; 2007.
- H. SMACNA (ASMM) - Architectural Sheet Metal Manual; 2012.

**1.04 SUBMITTALS**

- A. Product Data: Provide data on shape of components, materials and finishes, anchor types and locations.
- B. Shop Drawings: Indicate configuration and dimension of components, adjacent construction, required clearances and tolerances, and other affected work. Include plans, elevations, sections and details. Provide shop drawings for factory or shop fabricated items including installation drawings.
- C. Coordination Drawings: Roof plans drawn to scale and coordinating penetrations and roof-mounted items.
- D. Manufacturer's Installation Instructions: Indicate special procedures, fasteners, supporting members, and perimeter conditions requiring special attention.

**PART 2 PRODUCTS****2.01 MATERIALS**

- A. Aluminum:
  - 1. Sheet: ASTM B 209 (ASTM B 209M) for alclad alloy 3005H25 or alloy and temper required to suit forming operations, with mill finish, unless otherwise indicated.
- B. Galvanized Steel Sheet:
  - 1. ASTM A 653/A 653M with G90 (Z275); commercial steel, unless otherwise indicated.
    - a. Structural Quality: Grade 40 (Grade 275), where indicated or as required for strength.
- C. Fasteners:

1. Same metal as metals being fastened, or nonmagnetic stainless steel or other noncorrosive metal as recommended by manufacturer. Match finish of exposed fasteners with finish of material being fastened.
- D. Gaskets:
  1. Manufacturer's standard tubular or fingered design of neoprene, EPDM, or PVC; or flat design of foam rubber, sponge neoprene, or cork.
- E. Elastomeric Sealant:
  1. Recommended by unit manufacturer that is compatible with joint surfaces; ASTM C 920, Type S, Grade NS, Class 25.

## 2.02 MANUFACTURERS

- A. Pipe Seal Flashings:
  1. Thermoplastic Membrane: As recommended by membrane manufacturer
  2. Metal Roof Flashings: Dektite; Deks North America Inc
  3. Substitutions: See Skillman Section 01 6000 - Product Requirements
- B. Pipe Seal Curb:
  1. Portals Plus, Inc
  2. Substitutions: See Skillman Section 01 6000 - Product Requirements
- C. Walkway Pads:
  1. Carlisle Syntec Corporation
    - a. Sure-Seal interlocking Rubber Pavers
  2. Substitutions: See Skillman Section 01 6000 - Product Requirements

## 2.03 COMPONENTS

- A. Pipe Seal Flashing: Provide new spun aluminum base with neoprene or EPDM pipe seal boots for new or retrofit flashing conditions as required at penetrating elements 6" or less. Separate and reroute clusters of penetrations to install pipe seal flashings. Pipe seal boot shall flash around penetrating element and produce a water tight and weather proof seal with the roof membrane and the penetrating element.
- B. Pipe seal curb: Shall be an 18 GA galvanized curb. Factory installed nailer and 1.5" 3lb rigid fiberglass insulation, and an EPDM compression molded cap. Attachment and installation of the Pipe Portal shall be done in accordance with Portals Plus instructions and the roofing membrane manufacturer's recommendations.
- C. Walkway Pads:
  1. Provide 24 inch square by 2 inch thick rubber pavers with premolded "U" channels weighing 24 pounds per unit. Install whole units according to manufacturer's specification with adhesive attachment along the "U" channel as furnished by walkway pad manufacturer.
  2. Provide ramp tiles (if any) of the same material at transitions and as identified on the drawings.

## 2.04 ACCESSORIES

- A. Sealant: Type Elastomeric as specified in Section 07 9200.
- B. Plastic Cement: ASTM D 4586, Type I.
- C. Protective Backing Paint: Asphaltic mastic, ASTM D 4479 Type I.
- D. Mastic Sealant: Polyisobutylene, nonhardening, nonskinning, nondrying, nonmigrating sealant.
- E. Adhesive: Type recommended for waterproof and weather-resistant seaming and adhesive.

## PART 3 EXECUTION

### 3.01 EXAMINATION

- A. Verify that deck, curbs, roof membrane, base flashing, and other items affecting work of this Section are in place and positioned correctly.

**3.02 INSTALLATION**

- A. Install components in accordance with manufacturer's instructions and NRCA (RM) applicable requirements.
- B. Coordinate installation of roof accessories with installation of roof deck, roof insulation, flashing, roofing membranes, penetrations, equipment, and other construction to ensure that combined elements are waterproof and weathertight. Anchor roof accessories securely to supporting structural substrates so they are capable of withstanding lateral and thermal stresses, and inward and outward loading pressures. Conform to SMACNA Architectural Sheet Metal Manual drawing details for fabricating units.
- C. NRCA's "Roofing and Waterproofing Manual" details for installing units.
- D. Coordinate installation of sealants and roofing cement with work of this section to ensure water tightness.
- E. Separation: Separate metal from incompatible metal or corrosive substrates, including wood, by coating concealed surfaces, at locations of contact, with bituminous coating or providing other permanent separation.
- F. Flange Seals: Unless otherwise indicated, set flanges of accessory units in a thick bed of roofing cement to form seal.
- G. Clean exposed surfaces according to manufacturer's written instructions. Touch up damaged metal coatings.

**END OF SECTION**

**SECTION 10 2800  
TOILET, BATH, AND LAUNDRY ACCESSORIES****PART 1 GENERAL****1.01 SECTION INCLUDES**

- A. Commercial toilet accessories.
- B. Commercial shower accessories.

**1.02 RELATED REQUIREMENTS**

- A. Section 10 2113.19 - Plastic Toilet Compartments.
- B. Section 22 4000 - Plumbing Fixtures: Under-lavatory pipe and supply covers.

**1.03 REFERENCE STANDARDS**

- A. ADA Standards - 2010 ADA Standards for Accessible Design; 2010.
- B. ASTM C1036 - Standard Specification for Flat Glass; 2021.
- C. ASTM C1503 - Standard Specification for Silvered Flat Glass Mirror; 2024.
- D. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- E. ICC A117.1 - Accessible and Usable Buildings and Facilities; 2017.

**1.04 SUBMITTALS**

- A. See Skillman Section 01 3300 - Submittal Procedure, for submittal procedures.
- B. Product Data: Submit data on accessories describing size, finish, details of function, and attachment methods.
- C. Manufacturer's Installation Instructions: Indicate special procedures and conditions requiring special attention.

**PART 2 PRODUCTS****2.01 MANUFACTURERS**

- A. Commercial Toilet, and Shower Accessories:
  - 1. American Specialties, Inc: [www.americanspecialties.com/#sle](http://www.americanspecialties.com/#sle).
  - 2. Bradley Corporation: [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
  - 3. Bobrick: [www.bobrick.com](http://www.bobrick.com)
  - 4. Substitutions: See Skillman Section 01 6000 - Product Requirements.

**2.02 MATERIALS**

- A. Accessories - General: Shop assembled, free of dents and scratches and packaged complete with anchors and fittings, steel anchor plates, adapters, and anchor components for installation.
- B. Keys: Provide 2 keys for each accessory to Owner; master key lockable accessories.
- C. Mirror Glass: Annealed float glass, ASTM C1036 Type I, Class 1, Quality Q2, with silvering, protective and physical characteristics complying with ASTM C1503.
- D. Adhesive: Two component epoxy type, waterproof.
- E. Fasteners, Screws, and Bolts: Hot dip galvanized; tamper-proof; security type.

**2.03 FINISHES**

- A. Stainless Steel: Satin finish, unless otherwise noted.

**2.04 COMMERCIAL TOILET ACCESSORIES**

- A. Toilet Paper Dispenser:

1. Products: Surface mounted cabinet & mounting plate in 18 gauge satin finish stainless steel. Cabinet holds two 9 inch diameter rolls of 3" or 2 1/4 inch diameter core toilet tissue.
  - a. Bradley Model #5425: [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
  - b. Substitutions: Skillman Section 01 6000 - Product RequirementsSection 01 6000 - Product Requirements.
- B. Combination Towel Dispenser/Waste Receptacle: Recessed flush with wall, stainless steel; seamless wall flanges, continuous piano hinges.
  1. Towel dispenser capacity: 800 multi-fold or 600 C-fold paper towels.
  2. Waste receptacle capacity: 12 gallons.
  3. Products:
    - a. Bradley Corp; #234: [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
    - b. Substitutions: Skillman Section 01 6000 - Product Requirements.
- C. Soap Dispenser: foam soap dispenser, heavy gauge stainless steel with exposed surfaces in architectural satin finish. ABS plastic wall plate. Battery box holds (4) "AA" Alkaline batteries provided by contractor.
  1. Capacity: 27 oz.
  2. Products:
    - a. Bradley Corp; #6A01: [www.bradleycorp.com/#sle..](http://www.bradleycorp.com/#sle..)
    - b. Substitutions: Skillman Section 01 6000 - Product Requirements.
- D. Mirrors:
  1. Types:
    - a. Frameless, 1/4 inch thick float glass, thermosetting infrared-cured paint backing
      - 1) Size: 36 by 60 inch.
      - 2) Product: Bradley Corp #747-036600
    - b. Fixed Tilt Mirrors: Minimum 3 inches tilt from top to bottom.
      - 1) Size: 24 by 36 inch
      - 2) Product: Bradley Corp #740-024360
- E. Grab Bars: Stainless steel, smooth surface.
  1. Standard Duty Grab Bars:
    - a. Push/Pull Point Load: 250 pound-force, minimum.
    - b. Dimensions: 1-1/2 inch outside diameter, minimum 0.05 inch wall thickness, exposed flange mounting, 1-1/2 inch clearance between wall and inside of grab bar.
    - c. Finish: Satin.
    - d. Length and Configuration: As indicated on drawings.
    - e. Products:
      - 1) Bradley Corp; 812 Series: [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
      - 2) Substitutions: Skillman Section 01 6000 - Product Requirements.
- F. Sanitary Napkin Disposal Unit: Stainless steel, surface-mounted, self-closing door, locking bottom panel with full-length stainless steel piano-type hinge, removable receptacle.
  1. Products:
    - a. Bradley Corp: [www.bradleycorp.](http://www.bradleycorp.): #4722-15: [www.bradleycorp.com/#sle..](http://www.bradleycorp.com/#sle..)
    - b. Substitutions: Skillman Section 01 6000 - Product Requirements.

## 2.05 COMMERCIAL SHOWER AND BATH ACCESSORIES

- A. Shower Curtain Rod: 18 gauge stainless steel tube, 1 1/4 inch outside diameter, glass polypropylene flanges, 22-gauge stainless steel escutcheons that snap over flanges to conceal mounting screws.
  1. Products:
    - a. Bradley Corp; #9539: [www.bradleycorp.com/#sle..](http://www.bradleycorp.com/#sle..)
    - b. Substitutions: Skillman Section 01 6000 - Product Requirements.
- B. Antimicrobial Shower Curtain:
  1. Material: 9-oz. nylon reinforced antimicrobial PVC vinyl fabric (flameproof and stain resistant, self-deodorizing).

2. Size: 60" x 72" inches, hemmed edges.
3. Grommets: Aluminum; pierced through top hem on 6 inch centers.
4. Color: White.
5. Products:
  - a. Bradley Corp; #9533: [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
  - b. Substitutions: Skillman Section 01 6000 - Product Requirements.
- C. Folding Shower Seat: Wall-mounted surface; welded tubular seat frame, structural support members, hinges, and 7 gauge sating finish stainless steel mounting flanges , L-shaped, right hand and left hand seats.
  1. Seat: 1/2 inch thick Phenolic one-piece seat or seat slats, of white color.
  2. Size: ADA Standards compliant.
  3. Products:
    - a. Bradley Corp; #9569.
    - b. Substitutions: Skillman Section 01 6000 - Product Requirements.
- D. Towel Bar: No. 4 satin finish stainless steel , 3/4" square that projects 3"
  1. Length: 24 inches.
  2. Products:
    - a. Bradley Corp; #9065: [www.bradleycorp.com/#sle..](http://www.bradleycorp.com/#sle..)
    - b. Substitutions: Skillman Section 01 6000 - Product Requirements.
- E. Towel Hook: No. 4 satin finish stainless steel, projects 4- 7/16 inch
  1. Products:
    - a. Bradley Corp; #9314; [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
    - b. Substitutions: \_\_\_\_\_.

### **PART 3 EXECUTION**

#### **3.01 EXAMINATION**

- A. Verify existing conditions before starting work.
- B. Verify exact location of accessories for installation.
- C. Verify that there is reinforcement/blocking in wall for installatio.

#### **3.02 PREPARATION**

- A. Deliver inserts and rough-in frames to site for timely installation.

#### **3.03 INSTALLATION**

- A. Install accessories in accordance with manufacturers' instructions in locations indicated on drawings.
- B. Install plumb and level, securely and rigidly anchored to substrate.
- C. Mounting Heights: As required by accessibility regulations, unless otherwise indicated. Refer to drawings for mounting heights.
  1. Grab Bars: As indicated on drawings.
  2. Mirrors: 40 inch, measured from floor to bottom of mirrored surface.
  3. Other Accessories: As indicated on drawings.

#### **3.04 PROTECTION**

- A. Protect installed accessories from damage due to subsequent construction operations.

### **END OF SECTION**

**SECTION 11 1119  
VEHICLE LUBRICATION EQUIPMENT****GENERAL****1.01 SUMMARY**

- A. This section includes vehicle lubrication systems including the following components:
  - 1. Pneumatic Pumps
  - 2. Reels & Hoses
  - 3. Dispensers
  - 4. Tanks
  - 5. Pipe & Fittings
  - 6. Accessories

**1.02 SUBMITTALS**

- A. Product data for the following products: pumps, reels, hose, dispensers, tanks, accessories.
- B. Shop Drawings showing piping systems including pipe routing, sizing, valving, lubricators, regulators, pumps, nozzles etc. fully noted and scheduled.
- C. Qualifications data for firms and persons specified in the "quality assurance" article to demonstrate their capabilities and experience. Include list of all similar projects with project name, addresses, name(s) of architect(s) and owner(s), plus any other information specified.
- D. Maintenance data for specified products for inclusion into operating and maintenance (O&M) manuals.

**1.03 QUALITY ASSURANCE**

- A. Installer shall have (5) years of experience installing similar lubrication systems.
- B. Single Source Responsibility: Obtain system components from single source having the responsibility and accountability to answer and resolve any problems regarding proper installation, compatibility, performance, and acceptance.

**1.04 PROJECT CONDITIONS**

- A. Field Measurements: Verify dimensions by field measurements. Verify that the products and equipment may be installed in compliance with the original design and referenced standards.

**1.05 WARRANTY**

- A. Submit written warranty, executed by the contractor agreeing to repair or replace products, which fails in materials or workmanship within the specified warranty period.
- B. The warranty period shall be one (1) year following the date of substantial completion.

**PRODUCTS****2.01 PNEUMATIC PUMPS**

- A. Air powered pumps for petroleum and synthetic based oils.
- B. Manufacturers:
  - 1. Graco; Fire-Ball 300 #225852: [www.graco.com](http://www.graco.com)
  - 2. Substitutions: See Section 01 6000 - Product Requirements.
- C. Fluid Pressure Ratio: 5:1
- D. Air Pressure Operational Range: 40 to 180 psi
- E. Max Fluid Working Pressure: 900 psi.

**2.02 REELS & HOSE**

- A. Manufacturers:

1. Oils: Graco; SDM65B: [www.graco.com](http://www.graco.com)
  2. Air: Graco; SDL65B : [www.graco.com](http://www.graco.com)
  3. Coolant: Graco; SDL65B: [www.graco.com](http://www.graco.com)
  4. Substitutions: See Section 01 6000 - Product Requirements.
- B. Reel spool and frame shall be of steel construction.
- C. Reel shall have spring return with constant torque through entire range of operation.
- D. Multi-position guide arm
- E. 50 ft long, 1/2" diameter hose.
- F. Provide hose retraction stops

**2.03 DISPENSERS**

- A. Manufacturers:
1. Graco; 24V037: [www.graco.com](http://www.graco.com)
  2. Substitutions: See Section 01 6000 - Product Requirements.
- B. Mechanical meter
- C. Flow Rate: 0.28 to 8 GPM
- D. Dial Units: Quarts
- E. Accessories: Flexible extension

**2.04 TANKS**

- A. Used Oil:
1. Volume: 500 gallons
  2. Type: Above ground
  3. Construction: 12 GA double wall mild carbon steel
  4. 10" fill hole
  5. Max Dimensions: 3'-8" x 6'-3"
  6. Finish: Primed and painted
  7. Provide field touchup kit
- B. New Fluids:
1. Oil, Coolant, hydraulic fluid, and transmission fluid rated
  2. Volume: 250 gallons minimum each
  3. Type: Above ground
  4. Construction: HDPE with galvanized steel cage
  5. Max Dimensions: 4'-0" x 4'-0"
  6. Finish: Manufacturer standard plastic / galvanized
  7. Coordinate with pump system requirements
  8. Provide forklift compatible base

**2.05 PIPING & FITTINGS**

- A. Schedule 40 black steel pipe ASTM A-53
- B. Extra Heavy Malleable Iron fittings.

**2.06 USE LONG SWEEP ELBOWS WHERE POSSIBLE.****2.07 ACCESSORIES**

- A. Provide pressure relief valve set below the lowest rated system component.
- B. Provide bleed-type air shutoff valve, filter, regulator, lubricator as recommended by pump manufacturer.

**EXECUTION****3.01 INSTALLATION**

- A. Install equipment in strict accordance with approved shop drawings and manufacturer's installation instructions.

- B. Provide shut-off valves at each reel for individual service.
- C. Provide mounting channels and brackets as recommended by manufacturer for reel bank support and connection. Mounting heights as indicated in the drawings. Provide required bracket for such installation.
- D. Install piping adjacent to equipment to allow servicing and maintenance.

### **3.02 FIELD QUALITY CONTROL**

- A. Provide the services of qualified manufacturer's representatives to perform the following:
  - 1. Supervise preparatory work performed by other trades.
  - 2. Supervise installation.
  - 3. Coordinate, prior to installation, the mounting requirements of the fluid pumps to the tanks to assure that proper hardware has been provided.
  - 4. Prior to substantial completion of the facility, supervise testing, by the Vendor/Contractor in the presence of the Engineer, to ensure proper operation of the equipment.
  - 5. Train Owner's personnel in the proper safe operation and maintenance of the equipment.
  - 6. Perform all scheduled and unscheduled maintenance during warranty period; provide all labor and materials.

### **3.03 STARTUP & OWNER TRAINING**

- A. Startup Services, General: Provide services of a factory-authorized service representative to provide startup service and to demonstrate and train owner's maintenance personnel as specified below.
- B. The training program shall include familiarization with safe equipment operation and performance and detailed instruction in operation, maintenance and test procedures.
- C. Review the data in the operation and maintenance (O & M) manuals.
- D. Schedule training with the owner through the Architect with at least seven (7) days' notice.

**END OF SECTION**

**SECTION 23 3100  
HVAC DUCTS AND CASINGS****PART 1 GENERAL****1.01 SECTION INCLUDES**

- A. Metal ducts.
- B. Flexible ducts.
- C. Air plenums and casings.

**1.02 RELATED REQUIREMENTS**

- A. Section 07 8400 - Firestopping.
- B. Section 23 0130.51 - HVAC Air-Distribution System Cleaning: Post install duct cleaning.
- C. Section 23 0713 - Duct Insulation: External insulation and duct liner.
- D. Section 23 3300 - Air Duct Accessories.
- E. Section 23 3700 - Air Outlets and Inlets: Fabric air distribution devices.

**1.03 REFERENCE STANDARDS**

- A. ASTM A653/A653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process; 2023.
- B. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- C. NFPA 90A - Standard for the Installation of Air-Conditioning and Ventilating Systems; 2024.
- D. NFPA 90B - Standard for the Installation of Warm Air Heating and Air-Conditioning Systems; 2024.
- E. SMACNA (DCS) - HVAC Duct Construction Standards Metal and Flexible; 2020.
- F. UL 181 - Standard for Factory-Made Air Ducts and Air Connectors; Current Edition, Including All Revisions.

**1.04 SUBMITTALS**

- A. See Skillman Section 01 3300 - Submittal Procedure, for submittal procedures.
- B. Product Data: Provide data for duct materials.

**1.05 FIELD CONDITIONS**

- A. Do not install duct sealants when temperatures are less than those recommended by sealant manufacturers.
- B. Maintain temperatures within acceptable range during and after installation of duct sealants.

**1.06 WARRANTY**

- A. See Skillman Section 01 770a - Closeout for additional warranty requirements.

**PART 2 PRODUCTS****2.01 GENERAL REQUIREMENTS**

- A. Provide UL Class 1 ductwork, fittings, hangers, supports, and appurtenances in accordance with NFPA 90A and SMACNA (DCS) guidelines unless stated otherwise.
- B. Provide metal duct unless otherwise indicated.
- C. Duct Fabrication Requirements:
  - 1. Duct and Fitting Fabrication and Support: SMACNA (DCS) including specifics for continuously welded round and oval duct fittings.

2. Use reinforced and sealed sheet-metal materials at recommended gauges for indicated operating pressures or pressure class.
3. Construct tees, bends, and elbows with radius of not less than 1-1/2 times width of duct on centerline. Where not possible and where rectangular elbows must be used, provide airfoil turning vanes of perforated metal with glass fiber insulation.
4. Provide turning vanes of perforated metal with glass fiber insulation when acoustical lining is indicated.
5. Increase duct sizes gradually, not exceeding 15 degrees divergence wherever possible; maximum 30 degrees divergence upstream of equipment and 45 degrees convergence downstream.
6. Provide turning vanes of perforated metal with glass fiber insulation when an acoustical lining is required.
7. Where ducts are connected to exterior wall louvers and duct outlet is smaller than louver frame, provide blank-out panels sealing louver area around duct. Use same material as duct, painted black on exterior side; seal to louver frame and duct.

## 2.02 METAL DUCTS

- A. Material Requirements:
  1. Galvanized Steel: Hot-dipped galvanized steel sheet, ASTM A653/A653M FS Type B, with G60/Z180 coating.
- B. Round Metal Ducts:
  1. Round Single Wall Duct: Round lock seam duct with galvanized steel wall.
  2. Round Connection System: Interlocking duct connection system in accordance with SMACNA (DCS).
- C. Round Spiral Duct:
  1. Round spiral lock seam duct with galvanized steel wall.
- D. Connectors, Fittings, Sealants, and Miscellaneous:
  1. Fittings: Manufacture with solid inner wall of perforated galvanized steel.
  2. Joint Sealers and Sealants: Non-hardening, water resistant, mildew and mold resistant.
    - a. Type: Heavy mastic or liquid used alone or with tape, suitable for joint configuration and compatible with substrates, and recommended by manufacturer for pressure class of ducts.
    - b. VOC Content: Not more than 250 g/L, excluding water.
    - c. Surface Burning Characteristics: Flame spread index of zero and smoke developed index of zero, when tested in accordance with ASTM E84.
    - d. For Use with Flexible Ducts: UL labeled.
  3. Gasket Tape:
    - a. Provide butyl rubber gasket tape for a flexible seal between transfer duct connector (TDC), transverse duct flange (TDF), applied flange connections, and angle ring connections.

## 2.03 FLEXIBLE DUCTS

- A. Flexible Ducts: UL 181, Class 1, polyethylene film, mechanically fastened and rolled using galvanized steel to form spiral helix.
  1. Insulation: R6 insulation with polyethylene vapor barrier film.
  2. Pressure Rating: 10 in-wc positive and 5 in-wc negative.
  3. Maximum Velocity: 5500 fpm.
  4. Temperature Range: Minus 20 degrees F to 250 degrees F.
- B. Acoustic Flexible Ducts: UL 181, Class 1, spunbond nylon, mechanically fastened and rolled using galvanized steel to form spiral helix.
  1. Insulation: Fiberglass insulation with metallic vapor barrier.
  2. Inner Core: Spunbonded, nonwoven inner core.
  3. Pressure Rating: 6 in-wc positive and 5 in-wc negative.
  4. Maximum Velocity: 4000 fpm.

5. Temperature Range: Minus 20 degrees F to 250 degrees F.

## **2.04 AIR PLENUMS AND CASINGS**

- A. Fabricate in accordance with SMACNA (DCS) for indicated operating pressures indicated.
- B. Minimum Fabrication Requirements:
  - 1. Fabricate acoustic plenum or casing with reinforcing turned inward.
  - 2. Provide 16-gauge, 0.059-inch sheet steel back facing and 22-gauge, 0.029-inch perforated sheet steel front facing with 3/32 inch diameter holes on 5/32 inch centers.
  - 3. Construct panels 3 inches thick, packed with 4.5 pcf minimum glass fiber insulation media, on inverted channel of 16-gauge, 0.059-inch sheet steel.
  - 4. Mount floor-mounted plenum or casings on 4-inch high concrete curbs. At floor, rivet panels on 8-inch centers to angles. Where floors are acoustically insulated, provide liner of galvanized 18-gauge, 0.052-inch expanded metal mesh supported at 12-inch centers, turned up 12 inches at sides with sheet metal shields.
- C. Access Doors:
  - 1. Install hinged access doors where indicated or required for access to equipment for cleaning and inspection.
  - 2. Reinforce door frames with steel angles tied to horizontal and vertical plenum supporting angles.
  - 3. Provide clear wire glass observation ports, minimum 6 by 6 inch size.

## **PART 3 EXECUTION**

### **3.01 INSTALLATION**

- A. Install, support, and seal ducts in accordance with SMACNA (DCS).
- B. Install products following the manufacturer's instructions.
- C. Comply with safety standards NFPA 90A and NFPA 90B.
- D. During construction, provide temporary closures of metal or taped polyethylene on open ductwork to prevent construction dust from entering the ductwork system.
- E. Increase duct sizes gradually, not exceeding 15 degrees divergence wherever possible; maximum 30 degrees divergence upstream of equipment and 45 degrees convergence downstream.
- F. Duct sizes indicated are precise inside dimensions. For lined ducts, maintain sizes inside lining.
- G. Locate ducts with sufficient space around equipment to allow normal operating and maintenance activities.
- H. Use crimp joints with or without bead for joining round duct sizes 8 inch and smaller with a crimp in the direction of airflow.
- I. Use double nuts and lock washers on threaded rod supports.
- J. Connect terminal units to supply ducts with two feet maximum length of flexible duct. Do not use flexible duct to change direction.
- K. Connect diffusers or light troffer boots to low-pressure ducts with 5 feet maximum length of flexible duct held in place with strap or clamp.
- L. At exterior wall louvers, seal duct to louver frame and install blank-out panels.
- M. Louver Fit-out:
  - 1. Provide blank-out panels sealing available area of wall-mounted exterior-faced louver when connected ductwork is smaller than actual louver free area, and duct outlet is smaller than the louver frame.
  - 2. Use the same duct material painted black on the exterior side, then seal louver frame and duct.
- N. Fire Partitions: Provide firestopping sealing. See Section 07 8400.
- O. Duct Accessories, Terminal Units, Inlets, and Outlets: Interconnect as indicated in Sections 23 3300, and 23 3700.

P. Duct Insulation: Provide duct insulation. See Section 23 0713.

**3.02 CLEANING**

A. Clean thoroughly each duct system.

**END OF SECTION**

**SECTION 41 2200  
HOISTS AND CRANES****PART 1 GENERAL****1.01 SECTION INCLUDES**

- A. Cranes, Hoists and Lifts of the Following Types:
  - 1. Bridge crane
  - 2. Free standing jib cranes

**1.02 RELATED SECTIONS**

- A. Section 03 3000 - Cast-in-Place Concrete

**1.03 REFERENCES**

- A. American Institute of Steel Construction (AISC) - Manual of Steel Construction, Part 5, Specification for Structural Joints Using ASTM A325 or ASTM A490 Bolts.
- B. American National Standards Institute (ANSI):ANSI B30.11 - Monorails and Underhung Cranes.
- C. ASTM International (ASTM):
  - 1. ASTM A36 - Carbon Structural Steel.
  - 2. ASTM A325 - Structural Bolts, Steel, Heat Treated, 120/150 ksi Minimum Tensile Strength.
  - 3. ASTM A490 - Structural Bolts, Alloy Steel, Heat Treated, 150 ksi Minimum Tensile Strength.
- D. American Society for Testing and Materials (ASTM) B221 - Aluminum-Alloy Extruded Bar, Rod, Wire, Shape, and Tube.
- E. American Welding Society (AWS) D1.1 - Structural Welding Code.
- F. Occupational Safety and Health Administration (OSHA) - Specification 1910.179 - Overhead and Gantry Cranes.

**1.04 SUBMITTALS**

- A. Submit under provisions of Skillman Section 01 3300 - Administrative Requirements.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Describe capacities, performance, operation, and applied forces to foundation
  - 2. Preparation instructions and recommendations
  - 3. Storage and handling requirements and recommendations
  - 4. Installation methods
- C. Shop Drawings:
  - 1. Shop drawings showing configuration, dimensions, service area, and construction and installation details.

**1.05 QUALITY ASSURANCE**

- A. Manufacturer Qualifications: Company specializing in designing and manufacturing cranes with 25 years successful experience.
- B. Installer Qualifications: Company experienced in assembly and installation of cranes with 5 years successful experience and acceptable to crane manufacturer.
  - 1. Perform welding by certified operators in accordance with AWS D14.1.
  - 2. Bolted connections shall be in accordance with torque tightening procedures specified in AISC Manual, Part 5.
  - 3. Clearly label crane with rated load capacity. Place label at height and location easily read from floor level and loading position.

**1.06 DELIVERY, STORAGE, AND HANDLING**

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Store and dispose of solvent-based materials, and materials used with solvent-based materials, in accordance with requirements of local authorities having jurisdiction.

**1.07 PROJECT CONDITIONS**

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's absolute limits.

**1.08 WARRANTY**

- A. Manufacturer's Warranty: On manufacturer's standard form, in which manufacturer agrees to repair or replace assemblies and components that fail in materials and workmanship within warranty period from date of Substantial Completion.
  - 1. 5 years or 10,000 hours warranty for manual push-pull work station crane, jib crane, and gantry crane products to cover defects in materials and workmanship.
  - 2. 2 years or 4,000 hours warranty for motorized tractor products.

**PART 2 PRODUCTS****2.01 BRIDGE CRANES**

- A. Performance:
  - 1. Crane shall provide coverage of rectangular area of size indicated on Drawings and consist of:
    - a. Support structure requiring only primary structural support without longitudinal or lateral bracing.
    - b. Two rigid, parallel runways. Cranes with more than two runways or with articulating runways are not acceptable.
    - c. Rigid, single girder bridge moving perpendicular to runways or monorail.
  - 2. Productivity ratio: Crane shall be designed to manually move load with maximum force of 1/100 load weight.
  - 3. Crane operating temperature: 5 to 115 degrees F (-15 to 46 C).
  - 4. Crane shall be designed to withstand:
    - a. Structural design shall include full rated load capacity plus 15 percent for hoist and trolley weight and 25 percent impact factor for speed of lifting device and weight of tooling.
    - b. Crane and hoist dead load.
    - c. Live load capacity equal to net rated hook load: 20,000 pounds
    - d. Inertia forces from crane and load movement.
    - e. CMAA Group C
  - 5. Control Voltage: 460 / 115 V; 60 Hz
    - a. Coordinate with electrical design of building. Provide any required upgrades to provide fully functioning system.
  - 6. Control Type: Pendant
  - 7. Lift: 20'-0"
- B. Bridge crane with support structure, two runways, bridge moving perpendicular to runways, and equipped with track, end trucks, hoist trolley, festooning system, bumpers, and other accessories.
  - 1. Construction: Fabricate from ASTM A36 steel sections with finished ends and surfaces.
  - 2. Support structure: Support crane runways with metal building columns.
    - a. Columns: As designed by Building Manufacturer.
      - 1) Attachment of runway beam to building column by Building Manufacturer
  - 3. Runways: Refer to Drawings.
  - 4. Bridge: Single girder
    - a. Speed: 100 ft/min, stepless

5. End trucks: Rigid frame end truck designed to ride on ASCE 40# rail
  - a. Wheels: Removable, self-centering wheels with sealed lifetime lubricated bearings.
  - b. Designed for easy attachment of peripherals.
6. Hoist trolley: Rigid-body trolley designed to ride on bridge and to carry hoist and load. Articulating trolleys are not acceptable.
  - a. Speed: 65 ft/min / 19 ft/min
7. End stops: Molded composite, resilient bumper installed in runway and bridge tracks to prevent end trucks, hoist trolley, and festoon carriers from rolling out of track. Bolt stops without energy absorbing bumper are not acceptable.
8. Hoist:
  - a. Hoist Group: ASME H4
  - b. Speed: 20 / 3.2 ft/min, 2 speed
  - c. Wire Rope
9. Options:
  - a. Overload Protection
  - b. Under Voltage and Over Current Protection
  - c. Fused disconnect switch and mainline contactor
  - d. 4 Step geared upper limit switch
  - e. Factory Paint: Safety Yellow
  - f. 4 bar runway conductor system with tandem collectors

C. Festoon Assemblies: Cable type

## 2.02 JIB CRANES

A. Basis of Design: Gorbel Freestanding Jib Crane (FS350S-24-W24)

B. Performance:

1. Crane shall be designed, fabricated, and installed in accordance with ANSI B30.11 and OSHA 1910-179.
2. Crane shall be designed for minimum effort manual rotation.
3. Boom shall not drift when at rest.
4. Maximum deflection at boom end: 1/150 span based on capacity plus 15 percent for hoist and trolley weight.
5. Live load capacity equal to net rated hook load: 5 ton (1814 kg).
6. Base crane structural design on live load capacity plus 15 percent for hoist and trolley weight and 25 percent for impact.

C. Free Standing Jib Crane: Crane shall consist of mast requiring foundation support and a 270 degree rotating boom. Provide rotating collector assembly with service entrance and festoon service support as indicated.

1. Foundation:
  - a. Sleeve mounting: Provide steel pipe sleeve with steel base plate and centering pin of size indicated on shop drawings. Pipe sleeve shall be bolted to concrete foundation cast below floor slab and then embedded with reinforced concrete. Sleeve, base plate, and bolts shall not be exposed. Mast equipped with steel plate end with centering hole shall be inserted in sleeve and permanently secured to prevent rotation.
2. Construction: Fabricate from ASTM A36 steel sections with finished ends and surfaces.
3. Mast: Stationary steel pipe, perpendicular to boom. Equip mast top with plate and pivot pin to receive head assembly.
  - a. Accommodate under slab electrical feed for hoist. Junction location to be 24" above finish floor.
4. Boom: Horizontal, wide flange steel beam bolted to head assembly and designed for hoist trolley traveling on bottom flange. Reinforce with cap channel as required for lateral stability. Equip boom with stops to limit movement of trolley.
  - a. Provide rotation stops
  - b. Span: 16 feet

- c. Height Under Boom: 11'-8" minimum
  - d. Max Height: Clear opening height of overhead doors minus 0'-6".
  - e. Rotation: Manual
- 5. Head assembly: Welded steel plate and channel fabrication fitted over mast, bolted to boom, and designed to transfer boom load to mast and to rotate. Assembly shall allow for installation of head prior to boom attachment and provide maximum hoist lift.
  - a. Top pivot bearing assembly: Designed to connect head assembly to mast and transfer load from boom. Weight bearing channel connecting sides of head assembly shall contain tapered roller bearings allowing easy rotation.
  - b. Retaining pin: Inserted through mast pivot pin above weight bearing channel to prevent accidentally dislodging head assembly. Cranes without retaining pin are not acceptable.
  - c. Trunnion roller assembly: Designed to rotate around mast and transmit moment force from boom to mast. Provide trunnion rollers with tapered bearings held in steel channel with 1 inch (25 mm) diameter bolts. Masts less than 18 inches (457 mm) diameter shall have 2 rollers and larger masts shall have 4 rollers. Assembly shall rotate around mast with full roller face contact. Roller surface shall be sufficiently large to prevent cutting into mast. Cranes with small rollers or cams requiring wear band on mast are not acceptable.
- D. Hoist:
  - 1. Basis of Design: Harrington Electric Chain Hoist (PN: NER2M050LD-L)
  - 2. Capacity: 5 ton
  - 3. Lift Height: 15'-0" minimum
  - 4. Lift Speed: 11 / 2 FPM (Dual Speed)
  - 5. Power: 460 volt, 3 phase, 60 cycle
  - 6. Trolley Type: motorized
  - 7. Options:
    - a. Power supply cord sized for span
    - b. Chain container
    - c. Plug in connections
    - d. Limit switch
    - e. Control pendant
    - f. Tagline kit
    - g. Wire rope trolleys
    - h. Flat 8 cable cord grips
    - i. Canvas chain container
- E. Festoon Assemblies:
  - 1. Provide length of cable and/or air hose to supply lifting device. Supply shall be festooned along boom.
  - 2. Festoon trolleys: Four-wheeled trolleys with pivoting saddle and applicable attachment to support service run on boom and allowing festooning as hoist trolley travels.
  - 3. Festoon clamp: Steel clamp assembly attached to track to prevent festoon trolleys and gliders from exiting track.

## **2.03 SHOP FINISHING**

- A. Steel: Steam wash steel crane components with iron phosphate solution and apply yellow baked enamel finish.
- B. Provide spray can of matching color, air-drying paint for field touch-up.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Do not begin installation until support structures have been properly prepared.
- B. Design and construction of reinforced concrete footings and slabs as detailed on Drawings and specified in other sections. Verify that accurate crane applied forces and anchor bolt patterns

are provided for foundation design.

### **3.02 INSTALLATION**

- A. Install units and accessories in accordance with manufacturer's instructions and approved shop drawings.
- B. Do not modify crane components in any manner without advance written approval by crane manufacturer.
- C. Clearances for moving crane components:
  - 1. 3 inches (76 mm) minimum vertical clearance from any overhead obstruction.
  - 2. 2 inches (51 mm) minimum horizontal clearance from any lateral obstruction.
  - 3. Prior to applying proper torque to the bolts, ensure runways are:
    - a. Level to within plus or minus 1/8 inch in 20 feet (3 mm in 6.1 m).
    - b. Parallel with opposite runway to within plus or minus 1/8 inch in 20 feet (3 mm in 6.1 m).

### **3.03 FIELD QUALITY CONTROL**

- A. Perform field quality control testing as recommended by manufacturer.
- B. Move bridge and hoist trolley through entire travel to ensure crane is clear of obstructions and moves freely and smoothly.
- C. Inspect installed crane. Verify all bolts are tight and lock washers fully compressed.
- D. Field test crane and accessories for operating functions. Ensure crane movement is smooth and proper. Adjust as required and correct deficiencies.
- E. Clean surfaces. If necessary, touch-up paint damage, scratches, and blemishes with manufacturer provided matching paint.
- F. Protect crane from other construction operations.

### **3.04 COMMISSIONING**

- A. Provide all inspections and required commissioning

### **3.05 DEMONSTRATING AND TRAINING**



- A. Provide demonstration and training session for Owner's representative covering operation and maintenance.

### **3.06 PROTECTION**

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

**END OF SECTION**

<h2>Code Summary</h2>		<h2>Egress</h2>	
<b>Code:</b> Indiana Building Code - 2014 Edition Indiana Fire Code - 2014 Edition Indiana Plumbing Code - 2012 Edition Indiana Mechanical Code - 2014 Edition Indiana Fuel Gas Code - 2012 Edition Indiana Electrical Code - 2009 Edition Indiana Energy Code - 2010 Edition		Occupant Load: See plan Accessible means of egress: Door Swing in direction of egress: Maximum Travel Distance: Office: 250'-0" Maintenance / Fab: 250'-0" All Others: 400'-0" Maximum Common Path of Egress Travel: Office: 75'-0" All Others: 100'-0" Corridor Fire Resistance: N/R Corridor Minimum width: 44"	
<b>Occupancy Classification</b> B: Office and Administrative (304.1) A-3: Training Room (Accessory) (303.4) S-1: Maintenance and Fabrication (311.2) S-2: Parts, Sign Shop, Wash Bay, Fluid Storage (311.3) S-2: Truck Parking (311.3)		(T1004.1.2) (1007.1) (1008.1.2) (T1016.2) (T1014.3) (T1018.1) (T1018.2)	
<b>Construction Type</b> Type II-B Construction (503.1.2)		<b>Automatic Sprinklers</b> Automatic sprinklers are required (406.8.6, 903.2.9.1, 903.2.10)	
<b>Building Areas</b> Total Existing: 0 Square Feet New construction: B 6,076 Square Feet New construction: A-3 (Accessory) 1,215 Square Feet New construction: S-2 Trucks 25,931 Square Feet New construction: S-2 Truck Mezz 619 Square Feet New construction: S-1 9,256 Square Feet New construction: S-2 Misc 6,120 Square Feet New construction: S-2 Misc Mezz 704 Square Feet New construction: S-2 Wash Bay Mezz 127 Square Feet Total Complete: 48,609 Square Feet		<b>Fire Alarm</b> Required (903.4)	
<b>Allowable Height &amp; Area:</b> Allowable area per floor: 15,750 square feet (507.3, 507.6) Frontage increase (506.2) Sprinkler increase (506.3) Allowable height of 3 stories / 75 feet (T503) Mezzanines may occupy up to 50% of room square footage in Type II construction (505.2.1 EX 2) Mezzanines may be enclosed if occupancy is less than 10 (505.2.3 EX 1)			
<b>Building Elements</b> Structural Frame - Noncombustible (T601, 602.2) Bearing Walls - Noncombustible (T601, 602.2) Nonbearing walls (Exterior) - Noncombustible (T601, 602.2) Nonbearing walls (Interior) - Noncombustible (T601, 602.2) Roof Assembly - Noncombustible (T601) Exterior Walls - Noncombustible (T601, 602.2)			
<b>Occupancy Separation</b> B to S-1: Not required B to S-2: 1 Hour B to A-3: Not required (Accessory) S-1 to S-2: 1 Hour (508.4)			
<b>Incidental Uses</b> Mechanical 143: Equipment over 400,000 BTU Equipment Room 139: Equipment over 400,000 BTU (T509)			



## 1 First Floor

1. IN ANY AND ALL RATED ASSEMBLIES, ANY AND ALL PENETRATIONS SHALL MAINTAIN THE REQUIRED RATED PROTECTION BY FIRESTOPPING ALL MATERIALS, AT ALL EDGES AND OPENINGS THROUGH THE WALL, SO THAT NO OPEN PASSAGES THROUGH THE WALL OR JOINTS, RESPECTIVELY, THE RATED ASSEMBLY PROVIDE SMOKE AND FIRE DAMPERS AT ALL DUCTS THROUGH THE WALL.
2. IT IS THE RESPONSIBILITY OF THE CONTRACTORS TO COORDINATE PROTECTION AT RATED ASSEMBLIES AS REQUIRED FOR ALL TRADES, AND ALL COMPONENTS, WHETHER ARE NOT ITEMS ARE SPECIFICALLY LISTED OR DRAWING SHEETS, WALL SECTIONS OR DETAILS MAY ILLUSTRATE SELECTED COMPONENTS THAT PENETRATE A FIRE RATED ASSEMBLY, HOWEVER THE CONTRACTOR IS RESPONSIBLE TO COORDINATE THE ENTIRE SCOPE OF FIRE STOPPING WORK WITH THE CONSTRUCTION DOCUMENTS.
3. IT IS THE RESPONSIBILITY OF THE CONTRACTORS TO INSTALL ALL RATED PENETRATIONS MANUFACTURED AS REQUIRED TO MAINTAIN THE LISTED UL LISTED SYSTEM ASSEMBLY. PROVIDE DOCUMENTATION OF UL CERTIFICATION FOR ANY AND ALL RATED MATERIALS AND ASSEMBLIES AS REQUIRED BY THE ARCHITECT, FIRE MARSHAL, OR BUILDING OFFICIAL.
4. ALL WORK SHALL COMPLY WITH THE CURRENT EDITION OF THE UNDERWRITERS LABORATORY, INC. DIRECTORY FIRE RESISTANCE MANUAL.
5. CONTRACTOR TO PROVIDE PORTABLE FIRE EXTINGUISHERS DURING CONSTRUCTION.

### Work Description Notes

- 1 PROVIDE 4A-80B C FIRE EXTINGUISHER, MOUNTING BRACK  
AND SIGNAGE
- 2 PROVIDE 4A-80B C FIRE EXTINGUISHER AND SEMI RECESS  
CABINET
- 3 PROVIDE TYPE K FIRE EXTINGUISHER UNDER SINK
- 4 1 HOUR RATING
- 5 1 HOUR RATED CEILING / DECK
- 6 EXTEND RATED ASSEMBLY 2'-0" ABOVE HIGHEST POINT OF  
OFFICE ROOF
- 7 LADDER

## General Fire Protection Notes

- DESIGN AND INSTALL A COMPLETE FIRE SPRINKLER SYSTEM IN ACCORDANCE WITH CRITERIA OUTLINED ON PLANS, NFPA 13 AND ALL APPLICABLE CODES & REQUIREMENTS.
- FIRE PROTECTION SYSTEM SHALL BE DESIGNED BY A STATE LICENSED FIRE PROTECTION CONTRACTOR.
- FIRE PROTECTION CONTRACTOR IS RESPONSIBLE FOR COORDINATE WITH LOCAL FIRE DEPARTMENT AND BUILDING OFFICIALS TO INSURE THE SYSTEM MEETS ALL LOCAL REQUIREMENTS AND THAT THEY ARE ALL INCORPORATED INTO THE SYSTEM DESIGN. NO ADDITIONAL COMPENSATION WILL BE CONSIDERED FOR ANY OTHER REASON. ANYTHING THAT HAS NOT BEEN INDICATED ON THE PLAN, THIS INCLUDES, BUT IS NOT LIMITED TO: VAULTS, METERING, AND LOCATIONS OF ALL UTILITY AND SERVICE EQUIPMENT.
- FIRE PROTECTION CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL DECLUMENTS TO STATE FOR APPROVAL AND PERMITTING, INCLUDING ALL ASSOCIATED FEES.
- FIRE PROTECTION CONTRACTOR IS RESPONSIBLE FOR CONDUCTING A FLOW TEST FOR USE IN DETERMINATION OF SPRINKLER SYSTEM CAPACITY.
- CONTRACTOR RESPONSIBLE FOR SUBMITTING FINAL PENDANT LAYOUT TO ARCHITECT FOR REVIEW OF LAYOUT FOR PURPOSES OF AESTHETICS AND DESIGN INTENT. NOT FOR COVERAGE OR CAPACITY.
- SPRINKLER SYSTEM HEADS ARE TO BE CENTERED ON CEILING TILE. COORDINATE FINAL PENDANT LOCATION WITH ALL TRADES TO AVOID CONFLICT WITH OTHER CEILING MOUNTED DEVICES.
- FIRE PROTECTION SYSTEM IS TO BE HUNG TIGHT TO BUILDING STRUCTURE. REFER TO ARCHITECTURAL/STRUCTURAL DRAWINGS FOR DETAILS OF THE BUILDING STRUCTURE.
- PIPING MATERIALS TO BE BLACK STEEL PIPE, CAST-IRON OR COPPER FITTINGS. PROVIDE MECHANICAL FITTINGS AND COUPLINGS TO SUIT PRESSURE/TEMPERATURE DUTY.
- PIPING SUPPORTS MAY BE REGULARLY FURNISHED MATERIALS.
- COORDINATE FIRE PROTECTION PENETRATIONS WITH OTHER WORK TO AVOID INTERFERENCES. SEAL PENETRATIONS AS NOTED AND/OR SPECIFIED MAINTAINING THE FIRE RATING OF OTHER WORK WHERE APPLICABLE.
- each CONTRACTOR IS RESPONSIBLE FOR THE CUTTING, PATCHING, AND FINISHING ASSOCIATED WITH THE INSTALLATION OF HIS/HER WORK. PROVIDE CUTTING, PATCHING, AND FINISHING IN A FIRST-CLASS, WORKMAN LIKE MANNER WITH METHODS AND MATERIALS TO MATCH EXISTING WORK.
- WATER SUPPLY TO THE FACILITY IS PROVIDED BY THE PUBLIC UTILITY. COORDINATE WITH THE UTILITY COMPANY FOR DETAILS OF THE AVAILABLE WATER SUPPLY.
- THE SPRINKLER SYSTEM SHALL BE CONNECTED TO THE FIRE ALARM SYSTEM PER NFPA AND BE ELECTRICALLY SUPERVISED AS REQUIRED.
- FIRE PROTECTION CONTRACTOR SHALL COORDINATE ALL ELECTRICAL CONNECTIONS WITH THE ELECTRICAL CONTRACTOR INCLUDING BUT NOT LIMITED TO FLOW SWITCHES, TAMPER SWITCHES, SWITCHES TO FIRE ALARM BELL.



PORTER COUNTY  
Indiana



**MARTIN RILEY**  
architects • engineers

221 West Baker Street  
Fort Wayne, Indiana 46802

pho 260.422.7994  
fax 260.426.2067



ALL IDEAS, DESIGNS, ARRANGINGS AND PLANS INDICATED OR REFERRED TO BY THE DRAWING ARE OWNED BY, AND THE PROPERTY OF MARTIN REE, INC. AND WERE CONCEPT, EVOLVED, AND DEVELOPED FOR USE ON AND IN CONNECTION WITH THE SPECIFIED PROJECT. NONE OF THE IDEAS, DESIGNS, ARRANGINGS OR PLANS SHALL BE USED BY OR DISCLOSED TO ANY PERSON, FIRM OR CORPORATION FOR ANY PURPOSE WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF MARTIN REE, INC. WRITTEN DIMENSIONS ON THESE DRAWINGS SHALL HAVE PRECEDENCE OVER SCALE DIMENSIONS. CONTRACTORS SHALL VERIFY AND RE-CONFIRM ALL DIMENSIONS AND CONDITIONS SHOWN ON THESE DRAWINGS. SHOP DETAILS MUST BE SUBMITTED TO THIS OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

REVISION: \_\_\_\_\_ DATE: \_\_\_\_\_

DRAWN BY: SAG  
COMMISSION NUMBER: F22146

REVIEWED BY: ALW  
DATE: 2024-05-24

# A001


# LIFE SAFETY PLAN - CENTRAL FACILITY

New Construction Work for :

# Porter County Highway Department - Central Facility


1955 IN-2  
Valparaiso, IN 46385

F22146 - Porter County Highway  
Central Facility  
C:\Users\seawigh\Documents\F22146 - Porter Co Hwy Complex - Valpo - ARCH - Lawaugh.nvt  
S:\DD\CD



2 Life Safety Plan  
1/8" = 1'-0"

Code Summary		
<b>Code:</b> Indiana Building Code - 2014 Edition Indiana Fire Code - 2014 Edition Indiana Plumbing Code - 2012 Edition Indiana Mechanical Code - 2014 Edition Indiana Fuel Gas Code - 2012 Edition Indiana Electrical Code - 2009 Edition Indiana Energy Code - 2010 Edition		
<b>Occupancy Classifications:</b> S-2: Low Hazard Storage	[311.3]	
<b>Construction Type:</b> Type VB Construction - Two or more buildings on the same lot are within the limits of Table 503	[503.1.2]	
<b>Building Areas:</b> Total Existing: 0 Square Feet New construction: Salt Barn 3,900 Square Feet Total Complete: 3,900 Square Feet		
<b>Allowable Height &amp; Area:</b> Allowable area per floor: 13,635 Square Feet Frontage increase allowed due to 30 feet wide open space surrounding building	[506]	
Allowable height of 2 stories / 40 feet	[T503]	
<b>Building Elements:</b> Structural Frame - Any material permitted by code Bearing Walls - Any material permitted by code Nonbearing walls (Exterior) - Any material permitted by code Nonbearing walls (Interior) - Any material permitted by code Roof Assembly - Any material permitted by code Exterior Walls - Any material permitted by code	[T601, 602.5] [T601, 602.5] [T601, 602.5] [T601, 602.5] [T601] [T601, 602.5]	
<b>Occupancy Separations:</b> Not Applicable	[508.3]	
<b>Incidental Uses:</b> Not Applicable	[T509]	
<b>Egress:</b> Occupant Load: 8 per floor Maximum Travel Distance: 300'-0" Maximum Common Path of Egress Travel: 100'-0"	[T1004.1.2] [T1016.2] [T1014.3]	
<b>Automatic Sprinklers:</b> Not required	[903.2.11]	




1 Life Safety Plan  
1/8" = 1'-0"

Work Description Notes	
1	PROVIDE 4A-80B/C FIRE EXTINGUISHER, MOUNTING BRACKET AND SIGNAGE
Code Summary	
<b>Code:</b> Indiana Building Code - 2014 Edition Indiana Fire Code - 2014 Edition Indiana Plumbing Code - 2012 Edition Indiana Mechanical Code - 2014 Edition Indiana Fuel Gas Code - 2012 Edition Indiana Electrical Code - 2009 Edition Indiana Energy Code - 2010 Edition	
<b>Occupancy Classification</b> S-2: Low Hazard Storage	[311.3]
<b>Construction Type</b> Type VB Construction -	[602.5]
<b>Building Areas</b> Total Existing: 0 Square Feet New construction: Cold Storage 7,200 Square Feet Total Complete: 7,200 Square Feet	
<b>Allowable Height &amp; Area:</b> Allowable area per floor: 23,625 square feet Frontage increase allowed due to 55 feet wide open space surrounding building	[506]
Allowable height of 2 stories / 40 feet	[T503]
<b>Building Elements</b> Structural Frame - Any material permitted by code Bearing Walls - Any material permitted by code Nonbearing walls (Exterior) - Any material permitted by code Nonbearing walls (Interior) - Any material permitted by code Roof Assembly - Any material permitted by code Exterior Walls - Any material permitted by code	[T601, 602.5] [T601, 602.5] [T601, 602.5] [T601, 602.5] [T601] [T601, 602.5]
<b>Incidental Uses</b> Not applicable	[T509]
<b>Egress</b> Occupant Load: 36 per floor Accessible means of egress: Maximum Travel Distance: 300'-0" Maximum Common Path of Egress Travel: 75'-0"	[T1004.1.2] [1007.1] [T1016.2] [T1014.3]
<b>Automatic Sprinklers</b> Not required	[903.2.10, 406.6]
<b>Smoke Detectors:</b> Not required	[406.6]
<b>Fire Alarm</b> Not Required	[406.6]



221 West Baker Street  
Fort Wayne, Indiana 46802

pho 260.422.7994  
fax 260.426.2067



ALL IDEAS, DESIGN, ARRANGEMENTS, NOTICES AND NOTATIONS OR REVISIONS TO THIS DRAWING ARE OWNED BY AND THE PROPERTY OF MARTIN RILEY, INC. AND SHALL REMAIN THE PROPERTY OF MARTIN RILEY, INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF MARTIN RILEY, INC. MARTIN RILEY, INC. SHALL BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS IN THE AS-BUILT AND THIS OFFICE MUST BE NOTIFIED OF ANY VARIATION FROM THE DIMENSIONS AND CONDITIONS SHOWN ON THESE DRAWINGS. ANY VARIATIONS MUST BE SUBMITTED TO THE OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF RECORDING AND CORRECTION. ANY VARIATIONS MUST BE SUBMITTED TO THE OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF RECORDING AND CORRECTION. ANY VARIATIONS MUST BE SUBMITTED TO THE OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF RECORDING AND CORRECTION.

REVISION:	DATE:
1	ADDENDUM 1
	2024-06-12

DRAWN BY:	SAG	REVIEWED BY:	ALW
COMMISSION NUMBER:	F22146	DATE:	2024-05-24

A002



LIFE SAFETY PLANS - COLD  
STORAGE / SALT BARN

New Construction Work for :  
Porter County Highway Department -  
Central Facility


1955 IN-2  
Valparaiso, IN 46385

F22146 - Porter County Highway Department Central Facility  
C:\Users\lawaugh\Documents\F22146 - Porter Co Hwy Complex - Valpo - ARCH\_lawaugh.rvt  
S:\DD\CD


TOILET ACCESSORY SCHEDULE (REFER TO ADA MOUNTING HEIGHTS ON SHEET G101)					
NO.	ITEM	DESCRIPTION	MOUNTING HEIGHT	MODEL	REMARKS
A	GRAB BAR- CONCEALED MOUNTING	42" x 1-1/2" DIAMETER	34" A.F.F. TO CENTER	BRADLEY 812 SERIES, MODEL #001-42"	
B	GRAB BAR- CONCEALED MOUNTING	36" x 1-1/2" DIAMETER	34" A.F.F. TO CENTER	BRADLEY 812 SERIES, MODEL #001-36"	
C	GRAB BAR- CONCEALED MOUNTING	18" x 1-1/2" DIAMETER	34" A.F.F. TO CENTER	BRADLEY 812 SERIES, MODEL #001-18"	
D	TOWEL DISPENSER WASTE RECEPTACLE	17-1/8" x 56" x 8-25/32" D	44" MAX. TO CENTER OF OPERABLE COMPONENT	BRADLEY MODEL #234 - RECESSED	
E	PAPER TOWEL DISPENSER	11" x 15-5/16" x 4"D	44" MAX. TO CENTER OF OPERABLE COMPONENT	BRADLEY MODEL #250-15	
F	DUAL ROLL TOILET PAPER DISPENSER	20-9/16" x 11-3/8" x 4-7/10"	18" A.F.F. TO BOTTOM	BRADLEY MODEL #5425	
G	TILT MIRROR	24" x 36"	40" A.F.F. TO BOTTOM OF REFLECTIVE SURFACE	BRADLEY MODEL #740-024360	2
H	FRAMELESS MIRROR	36" x 60"	60" TO CENTER OF MIRROR	BRADLEY MODEL #747-036600	2
I	SOAP DISPENSER-SURFACE MOUNTED	4-5/8" x 10-9/16" x 4-3/16"	44" MAX. TO CENTER OF OPERABLE COMPONENT	BRADLEY MODEL #6401	
J	SHOWER SEAT- REVERSIBLE	34-1/2" x 22"	17"-19" TO TOP OF SEAT	BRADLEY MODEL #9669	4
K	TOWEL HOOK-SURFACE MOUNTED	2" x 2" x 4-7/16"	48" MAX TO TOP OF HOOK	BRADLEY MODEL #9314	1
L	TOWEL BAR-SURFACE MOUNTED	24" WIDE	48" MAX TO TOP OF BAR	BRADLEY MODEL #9065	1
M	SHOWER CURTAIN ROD- CONCEALED MOUNTING	60" x 1-1/4" DIA.	75"-77" FROM THE FLOOR	BRADLEY MODEL #9539	1
N	ANTIMICROBIAL VINYL SHOWER CURTAIN	60" x 72"		BRADLEY MODEL #9533	3
O	FRAMELESS MIRROR	36" x 60"	TOP OF MIRROR AT 6'-2"	BRADLEY MODEL 747-036600	
P	L-SHAPED HORIZONTAL GRAB BAR	24" x 36" x 1-1/4" O.D	33"-36" TO TOP OF BAR	AMERICAN SPECIALTIES 3490-P	5
Q	SANITARY NAPKIN DISPOSAL- SURFACE MOUNTED	10 3/4"W x 15 1/8"H x 4"D	24" FROM WALL. SEE G101 FOR MOUNTING HEIGHT	BRADLEY MODEL 4722-15	
<b>REMARKS</b> 1. SATIN STAINLESS STEEL 2. MIRROR NOT TO TOUCH PLUMBING FIXTURE 3. SHOWER CURTAIN HOOKS, BRADLEY MODEL #9536 4. REVERSIBLE-LEFT OR RIGHT HAND CONFIGURATION PEENED FINISH					




**2 Enlarged Maintenance Mezzanine**  
1/8" = 1'-0"



**3 Enlarged Restroom**  
3/8" = 1'-0"



**1 Enlarged Parts & Signage**  
1/8" = 1'-0"



**KEY PLAN**

### Work Description Notes


- REMOVABLE RAILING SECTION
- FLOOR / TRNCH DRAIN, REFER TO STRUCTURAL AND PLUMBING
- SEPARATE INFILL POUR AT PIERS RELATED TO FUTURE MEZZANINE LOCATION
- REINSTALL SALVAGED AIR COMPRESSOR. REFER TO ELECTRICAL AND PLUMBING
- ELECTRICAL EQUIPMENT
- PLUMBING FIXTURE
- COILING OVERHEAD DOOR BELOW
- MECHANICAL EQUIPMENT
- DUCTWORK, SEE MECHANICAL
- LOUVER, SEE MECHANICAL
- NATURAL GAS SUPPLY, SEE MECHANICAL
- STRUCTURE, REFER TO PRE-ENGINEERED METAL BUILDING MANUFACTURER DRAWINGS
- STRUCTURE REFER TO S SERIES DRAWINGS
- PROVIDE PRESSURE WASHER, REFER TO PLUMBING SCHEDULE
- HOSE REEL, REFER TO PLUMBING, COORDINATE EXACT PLACEMENT WITH OWNER
- CATWALK, PAINTED, REFER TO STRUCTURAL
- PROVIDE (4) 250 GALLON FLUID STORAGE CONTAINERS WITH PALLET JACK/FORKLIFT COMPATIBLE BASE. CONTAINERS TO BE COMPATIBLE WITH OIL, HYDRAULIC FLUID, COOLANT, AND TRANSMISSION FLUID. PROVIDE 500 GALLON USED OIL STORAGE TANK
- PROVIDE 12"x12" INSULATED STAINLESS STEEL ACCESS DOOR AND WALL SLEEVE. INCLUDE RIANO HINGE, DROP CAP, AND MORTISE CYLINDER KEYS TO BUILDING. BASIS OF DESIGN NYSTRON XTM-CS
- PROVIDE 1/4" STEEL PLATE MECHANICALLY ANCHORED TO FLOOR SLAB TO INFILL VOID. LEAVE MIN 2" SPACE BETWEEN PLATE AND COLUMN
- GUARDRAIL, PAINT, REFER TO DETAILS
- LADDER, REFER TO DETAILS
- PRESSURE WASHER REMOTE INTERFACE LOCATION
- PAINT ALL EXPOSED PRIMARY AND SECONDARY STEEL IN THIS AREA
- PROVIDE TURN KEY FLUID DISTRIBUTION SYSTEM FROM 250 GALLON TANKS TO REELS IN MAINTENANCE BAYS 130. ALL EQUIPMENT, DISPENSERS, PIPING, AND REQUIRED COMPONENTS TO BE PROVIDED. REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION



**MARTIN RILEY**  
architects+engineers

221 West Baker Street  
Fort Wayne, Indiana 46802

pho 260.422.7994  
fax 260.426.2067



ALL DESIGN, DESIGN DEVELOPMENT, AND/OR CONSTRUCTION OF THIS PROJECT IS THE PROPERTY OF MARTIN RILEY, INC. AND SHALL REMAIN THE PROPERTY OF MARTIN RILEY, INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF MARTIN RILEY, INC. MARTIN RILEY, INC. AND ITS EMPLOYEES SHALL BE RESPONSIBLE FOR THE DESIGN AND CONSTRUCTION OF THIS PROJECT. ANY CHANGES TO THE DESIGN SHALL BE SUBMITTED TO MARTIN RILEY, INC. FOR REVIEW AND APPROVAL BEFORE PROCEEDING WITH FABRICATION.


REVISION: 1 ADDENDUM 1 DATE: 2024-06-12

DRAWN BY: SAG COMMISSION NUMBER: F22146 REVIEWED BY: ALW DATE: 2024-05-24



**A104**

ENLARGED PLANS






GENERAL NOTES:  
1. PROVIDE ANY AND ALL TRIM PIECES AND COMPONENTS REQUIRED FOR WEATHER TIGHT AND AESTHETICALLY COMPLETE WINDOW SYSTEM



1955 IN-2  
Valparaiso, IN 46385



221 West Baker Street  
Fort Wayne, Indiana 46802




DRAWN BY: SAG  
COMMISSION NUMBER: F22146

REVIEWED BY: ALW  
DATE: 2024-05-24


## WINDOW SCHEDULE AND DETAILS

F22146 - Porter County Highway Department Central Facility  
C:\Users\awaght\Documents\F22146 - Porter Co Hwy Complex - Valpo - ARCH\_Lawaugh.rvt  
S:\DD\CD


Room Finish Schedule										
Room Number	Room Name	Floor Finish	Base Finish	Wall Finish				Ceiling Finish	Ceiling Height	Remarks
				North	South	East	West			
101	VESTIBULE	CPT-2	B-1	PNT-3	PNT-3	PNT-2	PNT-2	A-1	10'-0"	
102	CIRCULATION	CPT-1/CPT-2	B-1	PNT-2/PNT-3	PNT-2/PNT-3	PNT-2/PNT-3	PNT-2/PNT-3	A-1	10'-0"	1
103	MAIN OFFICE	CPT-1	B-1	PNT-2	PNT-3	PNT-2	PNT-2	A-1	10'-0"	
104	ASST. SUPERVISOR	CPT-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
105	SUPERVISOR	CPT-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
106	ENG. / PROJECT MANAGER	CPT-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
107	UNISEX RR	R-1	B-1	PNT-2	PNT-2	PNT-2	PNT-2	A-2	10'-0"	
108	UNISEX RR	R-1	B-1	PNT-2	PNT-2	PNT-2	PNT-2	A-2	10'-0"	
109	MECH. FOREMAN	CPT-2	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
113	WAPS	CPT-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
114	CONFERENCE	CPT-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
115	MECH.	CONC-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-3	TO DECK	
116	LAUNDRY	R-1	B-1	PNT-2	PNT-2	PNT-2	PNT-2	A-2	10'-0"	
117	STORAGE	CONC-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
118	OFFICE SUPPLY	CPT-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
119	IT	CONC-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	TO DECK	
120	TRAINING / BREAK ROOM	R-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
121	STORAGE	R-1	B-1	PNT-1	PNT-1	PNT-1	PNT-1	A-1	10'-0"	
122	CIRCULATION	CPT-2/EPXY-1	B-1	PNT-2/PNT-3	PNT-2/PNT-3	PNT-2/PNT-3	PNT-2/PNT-3	A-1	10'-0"	1
123	LOCKER ROOM	EPXY-1	B-1	PNT-2	PNT-2	PNT-2	PNT-2	A-2/A-4	10'-0"	3.5
124	LOCKER ROOM	EPXY-1	B-1	PNT-2	PNT-2	PNT-2	PNT-2	A-2/A-4	10'-0"	3.5
125	FOREMAN	CPT-2	B-1	PNT-2	PNT-2	PNT-2	PNT-2	A-1	10'-0"	
130	MAINTENANCE BAYS	CONC-3	NF	LP	LP	PNT-4/LP	LP	A-3	TO DECK	2
131	FABRICATION	CONC-1	NF	LP	LP	LP	LP	A-3	TO DECK	2
132	PARTS	CONC-3	NF	LP	LP/PNT-4	LP/PNT-4	LP/PNT-4	A-3	TO DECK	2
133	UNISEX RR	CONC-1	B-1	PNT-4	PNT-4	PNT-4	PNT-4	A-3	TO DECK	
134	SIGNAGE	CONC-3	NF	PNT-4/LP	LP	PNT-4/LP	LP	A-3	TO DECK	2
135	OFFICE	CPT-2	B-1	PNT-4	PNT-2	PNT-4	PNT-4	A-1	TO DECK	
136	FLUIDS / AIR COMPRESSOR	CONC-3	NF	PNT-4	PNT-4	PNT-4	PNT-4	A-3	TO DECK	
137	WASH BAY	CONC-2	CONC-2	PNT-6	PNT-6	PNT-6	PNT-6	A-3	TO DECK	4
138	STORAGE	CONC-2	CONC-2	LP	PNT-6	PNT-6	PNT-6	A-3	TO DECK	
139	EQUIPMENT ROOM	CONC-2	NF	LP	PNT-6	LP	PNT-6	A-3	TO DECK	
140	TRUCK PARKING	CONC-3	NF	LP/PNT-4	LP	PNT-4/LP	LP	A-3	TO DECK	2
141	FIRE RISER	CONC-1	NF	PNT-4	PNT-4	PNT-4	PNT-4	A-3	TO DECK	
142	ELECTRICAL	CONC-1	NF	PNT-4	PNT-4	PNT-4	PNT-4	A-3	TO DECK	
150	COLD STORAGE	CONC-3	NF	LP	LP	LP	LP	A-3	TO DECK	2
160	SALT BARN	--	NF	NF	NF	NF	NF	A-3	TO DECK	
201	STORAGE MEZZANINE	CONC-1	NF	LP	--	LP/PNT-4	--	A-3	TO DECK	
202	STORAGE MEZZANINE	CONC-1	NF	--	LP	--	--	A-3	TO DECK	
203	STORAGE MEZZANINE	CONC-1	NF	--	LP/PNT-4	--	LP/PNT-4	A-3	TO DECK	2
204	MECHANICAL	CONC-1	NF	PNT-4	LP	PNT-4	LP	A-3	TO DECK	
232	STORAGE MEZZANINE	CONC-1	NF	LP	LP	LP	LP	A-3	TO DECK	2




**6 Locker 123- East**  
3/8" = 1'-0"



**5 Locker 123- North**  
3/8" = 1'-0"



**4 Locker 123- West**  
3/8" = 1'-0"



**3 Locker 123- South**  
3/8" = 1'-0"

#### FINISH SCHEDULE REMARKS

1. REFER TO FINISH PLANS FOR LOCATIONS OF FINISHES.
2. TOUCH UP RUST SPOTS ON PRIMED STEEL.
3. DRYWALL CEILING IN SHOWER ROOM TO BE PAINTED (PNT-7)
4. TOUCH UP PRIMER ON STEEL COLUMNS IN WASH BAY
5. PROVIDE LOCKERS AND ADA BENCH (MISC-4) REFER TO ELEVATIONS ON SHEET A601.

#### FINISH LEGEND

- (A) CEILING**
1. ARMSTRONG CEILINGS "FINE FISSED" HIGH NRC PANELS NO. 1754
    - a. DIMENSIONS: 24" x 24" x 7/8"
    - b. EDGE/COLOR: SQUARE LAY-IN, WHITE
    - c. SUSPENSION SYSTEM/COLOR: 15/16" PRELUDE, WHITE
  2. ARMSTRONG CEILINGS "CLEAN ROOM VL" PANELS NO. 869
    - a. DIMENSIONS: 24" x 24" x 5/8"
    - b. EDGE/COLOR: SQUARE LAY-IN, WHITE
    - c. SUSPENSION SYSTEM/COLOR: PRELUDE 15/16", WHITE
  3. EXPOSED STRUCTURE, NO FINISH
  4. GYPSUM BOARD, PAINTED (PNT-6)
- (B) BASE**
1. ROPPE 4" PINNACLE RUBBER COVE BASE
    - a. COLOR: TO BE SELECTED
    - b. ADHESIVE: MANUFACTURER APPROVED
- (CPT) CARPET**
1. J&J FLOORING "REFLECTIONS" 1865 KINETIX TILE
    - a. DIMENSIONS: 24" x 24" x .205 THICK
    - b. COLOR: TO BE SELECTED
    - c. INSTALLATION METHOD: QUARTER TURN
    - d. ADHESIVE: KINETEX ADHESIVE
  2. J&J FLOORING "CATWALK" WALK-OFF TILE
    - a. DIMENSIONS: 24" x 24"
    - b. COLOR: TO BE SELECTED
    - c. INSTALLATION METHOD: QUARTER TURN
    - d. ADHESIVE: MANUFACTURER APPROVED
- (CONC) CONCRETE**
1. SEALED, CLEAR: SHERWIN WILLIAMS (2) COATS TREAD-PLEX ACRYLIC WATER BASED PRIMER/SEALER, CLEAR (BASIS OF DESIGN)
    - a. FINISH: SEMI-GLOSS
  2. WASH BAY: SHERWIN WILLIAMS (1) COAT 2-PART PRIMER EPOXY 3447 (1) COAT FASTOP SL45 (1) COAT RESUFLOOR 3741 NOVOLAC EPOXY, HIGH GLOSS (BASIS OF DESIGN)
    - a. TOTAL SYSTEM THICKNESS: 1/4"
    - b. COLOR: TO BE SELECTED FROM STANDARD COLORS
    - c. COVE BASE: 6" INTEGRAL COVE BASE, APPLY SILICONE CAULK AT TOP OF BASE
    - d. SLIP RESISTANT FINISH: PROVIDE GRIT ADDITIVE FOR SLIP RESISTANCE
  3. SEALED, CLEAR: SHERWIN WILLIAMS ARMORSEAL (1) 33 EPOXY PRIMER/SEALER (1) COAT ARMORSEAL 100 HS EPOXY, CLEAR (BASIS OF DESIGN)
    - a. FINISH: GLOSS
- (EPXY) EPOXY FLOORING**
1. DUR-A-FLEX "DUR-A-CHIP" EPOXY FLOORING SYSTEM
    - a. SYSTEM: TOPCOAT, GROUT COAT, SECOND CHIP BROADCAST, CHIP BROADCAST, AND PRIMER
    - b. MACRO CHIP COLOR: MANUFACTURER STANDARD COLOR
    - c. FINISH: TEXTURED
- (LP) LINER PANEL**
- (MISC) MISCELLANEOUS**
1. PLASTIC LAMINATE CASEWORK
    - a. FINISH: (PL-1)
    - b. DOORDRAWER PULLS: MOCKETT SLENDER BAR PULL #DP252A- 5 3/8" IN SATIN NICKEL FINISH (1TS)
    - c. TRASH GROMMET: MOCKETT 8" DIA x 2" DEEP TRASH GROMMET #TM2B, SATIN STAINLESS STEEL FINISH
  2. SCRANTON PRODUCTS "HINY HIDERS" HOPE TOILET PARTITION AND URINAL SCREEN
    - a. LAYOUT: FLOOR MOUNTED-OVERHEAD BRACED
    - b. COLOR: TESTED IN ACCORDANCE WITH NFPA 286 STANDARD COLOR WITH ORANGE PEEL TEXTURE
  3. SWF CONTRACT "CLASSIC 1" ALUMINUM BLINDS"
    - a. DIMENSION: CONTRACTOR TO FIELD VERIFY MEASUREMENTS
    - b. SLAT THICKNESS: .008" THICK
    - c. COLOR: MANUFACTURER STANDARD COLORS
    - d. CORD LENGTH: COMPLIANT WITH ANSI WDMA A110 1-2018 STANDARD FOR CORD LENGTH
  4. PEMCO "GEN2" SINGLE TIER METAL WELDED LOCKERS
    - a. DIMENSIONS: 12"W x 18" D x 72" H
    - b. DOOR STYLE: SOLID DOOR WITH MANUF. STANDARD MINI LOUVER
    - c. COLOR: TO BE SELECTED FROM MANUFACTURER STANDARD COLORS
    - d. TOP: CONTINUOUS SLOPE HOOD
    - e. BASE: 4" METAL CHANNEL BASE
    - f. LOCK STYLE: MULTI-POINT LATCH WITH PADLOCK
    - g. LOCKER QUANTITY: REFER TO FLOOR PLAN. TWO (2) LOCKERS TO BE ADA COMPLIANT, ONE PER LOCKER ROOM.
    - h. ADA COMPLIANT FREESTANDING BENCH: (1) PER LOCKER ROOM. 42" WIDE x 24" SEAT DEPTH WITH 18" BENCH BACK. STAINLESS STEEL PEDESTALS WITH RUBBER FEET
  5. A&M ADA VANITY BRACKETS
    - a. SIZE: BRACKETS FOR 24" TOP
    - b. FINISH: US ADA STAINLESS
    - c. PANEL SKIRT: (PL-3) FINISHED W/ SCREWS AND SPRING CLIPS
    - d. MOUNTING: PROVIDE BLOCKING IN WALL AND HARDWARE FOR MOUNTING SINK
  6. ROPPE FLOORING ACCESSORIES
    - a. REDUCERS: CARPET TO CONCRETE
    - b. TRANSITIONS: CARPET TO LVT
    - c. COLOR: MANUFACTURER STANDARD COLOR
    - d. ADHESIVE: MANUFACTURER APPROVED
- (MISC) MISCELLANEOUS CONTINUED**
7. NOT USED
  8. ADA COMPLIANT INTERIOR SIGNAGE
    - a. PRODUCT: INPRO CORP "ASPEN COLLECTION"
    - b. MATERIAL: NON-GLARE ACRYLIC
    - c. TEXT/CHARACTER: TACTILE TEXT WITH RAISED CHARACTERS AND GRADE 2 BRAILLE
    - d. FONT: SANS SERIF FONT, ALL CAPS
    - e. REFER TO SIGNAGE SCHEDULE ON SHEET
  9. CS ACROVYN "SM 20M" SURFACE MOUNTED CORER GUARD
    - a. LEG/PROFILE: 3", 1/4" NOSE RADIUS
    - b. LENGTH: 4'-0"
    - c. COLOR: TO BE SELECTED FROM MANUF. STANDARD COLORS
  10. CRANE COMPOSITES "GLASBOR" FRP PANEL
    - a. SIZE: 4' x 8' x 0.09" (EMBOSSED)
    - b. COLOR: MANUF. STANDARD COLOR
    - c. SEAM TREATMENT: STAINLESS INSIDE CORNER, END CAP TRIM
  11. ROPPE RUBBER REDUCER STRIP
    - a. PROFILE: FLOORING CONTRACTOR TO VERIFY
    - b. COLOR: MANUF. STANDARD COLOR
    - c. ADHESIVE: MANUF. RECOMMENDED/APPROVED
- (NF) NO FINISH**
- (PL) HIGH PRESSURE PLASTIC LAMINATE**
1. CABINETS: WILSONART VERTICAL GRADE
    - a. COLOR: TO BE SELECTED FROM MANUFACTURER'S STANDARD LAMINATES
  2. COUNTERTOP: WILSONART POSTFORMING GRADE
    - a. COLOR: TO BE SELECTED FROM MANUFACTURER'S STANDARD LAMINATES
- (PNT) PAINT**
1. OFFICE GYP BD WALLS: SHERWIN WILLIAMS (1) COAT PROMAR 200 ZERO VOC LATEX PRIMER (2) COATS PROMAR 200 ZERO VOC INTERIOR LATEX, EG-SHEL
    - a. COLOR: TO BE SELECTED
    - b. CMU: PRIMER TO BE (1) COAT LOXON BLOCK SURFACER
  2. CORRIDOR/RESTROOM/LOCKER ROOM WALLS (HIGH PERFORMANCE): SHERWIN WILLIAMS (1) COAT PROMAR 200 ZERO VOC LATEX PRIMER (2) COATS PRO INDUSTRIAL PRE-CATALYZED WATERBASED EPOXY, SEMI-GLOSS
    - a. COLOR: TO BE SELECTED
    - b. CMU: PRIMER TO BE (1) COAT LOXON BLOCK SURFACER
  3. ACCENT WALLS (HIGH PERFORMANCE): SHERWIN WILLIAMS (1) COAT PROMAR 200 ZERO VOC LATEX PRIMER (2) COATS PRO INDUSTRIAL PRE-CATALYZED WATERBASED EPOXY, SEMI-GLOSS
    - a. COLOR: TO BE SELECTED
    - b. CMU: PRIMER TO BE (1) COAT LOXON BLOCK SURFACER
  4. WAREHOUSE/MANUF/DISTRIBUTION CMU WALLS (HIGH PERFORMANCE): SHERWIN WILLIAMS (1) COAT LOXON BLOCK SURFACER (2) COATS PRO INDUSTRIAL WATER BASED CATALYZED EPOXY, SEMI-GLOSS
    - a. COLOR: TO BE SELECTED
  5. WASH BAY CMU WALLS: SHERWIN WILLIAMS (1) COAT KEM CATI-COAT HS EPOXY FILLER/SEALER (2) COATS MACROPOXY 646 FAST CURE EPOXY, GLOSS (1) COAT SHER-LOKANE 800 PROTECTIVE COATING, GLOSS
    - a. COLOR: TO BE SELECTED
  6. DRYWALL CEILING: SHERWIN WILLIAMS (1) COAT PROMAR 200 ZERO VOC PRIMER (2) COATS PROMAR 200 ZERO VOC INTERIOR LATEX, SEMI-GLOSS
    - a. COLOR: TO BE SELECTED
  7. INTERIOR METAL DOORS/DOOR FRAMES/RAILINGS: SHERWIN WILLIAMS (1) COAT PRO INDUSTRIAL PRO-CRYL UNIVERSAL PRIMER (2) COATS PRO INDUSTRIAL PRE-CATALYZED EPOXY, SEMI-GLOSS
    - a. COLOR: TO BE SELECTED
  8. TOP 3'-0" OF LADDER: SHERWIN WILLIAMS (1) COAT PRO INDUSTRIAL PRO-CRYL UNIVERSAL PRIME (2) COATS PRO INDUSTRIAL PRE-CATALYZED EPOXY, SEMI-GLOSS
    - a. COLOR: SAFETY YELLOW
  9. WASH BAY MEZZANINE RAILING AND LADDER: SHERWIN WILLIAMS (1) COAT PRO INDUSTRIAL PRO-CRYL UNIVERSAL PRIMER (2) COATS WATERBASED AGROLON 100 POLYURETHANE, GLOSS
    - a. COLOR: TO BE SELECTED
    - b. SECTION OF LADDER: SAFETY YELLOW
- (R) RESILIENT FLOORING**
1. J&J FLOORING "COMPOSITE 3 MM"
    - a. DIMENSIONS: 18" x 36" x 3MM THICK
    - b. WEAR LAYER: 20 MIL
    - c. COLOR: MANUF. STANDARD COLOR
    - d. INSTALLATION METHOD: MONOLITHIC
    - e. ADHESIVE: MANUFACTURER APPROVED
- (SS) SOLID SURFACE**
1. COUNTERTOP: CORIAN 1/2" SOLID SURFACE
    - a. COLOR: TO BE SELECTED FROM "GROUP 2" COLORS
    - b. FINISH: MATTE
  2. WINDOW SILL: CORIAN 1/2" SOLID SURFACE
    - a. COLOR: TO BE SELECTED FROM "GROUP 2" COLORS
    - b. FINISH: MATTE

New Construction Work for :

Porter County Highway Department -  
Central Facility


1955 IN-2  
Valparaiso, IN 46385



**MARTIN RILEY**  
architects+engineers

221 West Baker Street  
Fort Wayne, Indiana 46802

pho 260.422.7994  
fax 260.426.2067



ALL SEAL, ORIGINAL, REPRODUCTION, AND/OR MODIFICATION OF THIS SEAL IS PROHIBITED. THE SEAL IS THE PROPERTY OF MARTIN RILEY, INC. AND SHALL BE USED ONLY FOR THE PROJECT AND NOT FOR ANY OTHER PROJECT. THE SEAL IS THE PROPERTY OF MARTIN RILEY, INC. AND SHALL BE USED ONLY FOR THE PROJECT AND NOT FOR ANY OTHER PROJECT. THE SEAL IS THE PROPERTY OF MARTIN RILEY, INC. AND SHALL BE USED ONLY FOR THE PROJECT AND NOT FOR ANY OTHER PROJECT.



REVISION	DATE
1	ADDENDUM 1

DRAWN BY	MEK	REVIEWED BY	ALW
COMMISSION NUMBER	F22146	DATE	2024-05-24


**A601**

ROOM FINISH SCHEDULE  
AND INTERIOR ELEVATIONS


F22146 - Porter County Highway  
Central Facility  
C:\Users\lawaugh\Documents\F22146 - Porter Co Hwy Complex - Valpo - ARCH\_lawaugh.rvt  
S:\DD\CD



**2 Maintenance Facility Floor Plan**  
1/8" = 1'-0"



**4 Mech 115 Mop Sink -East**  
3/8" = 1'-0"





**3 Mech 115 Mop Sink-South**  
3/8" = 1'-0"

#### Work Description Notes

- 1 PAINT COLUMN (PNT-7)
- 2 PAINT RAILING (PNT-7)
- 3 PROVIDE SHEETROCK FIBERGLASS SCIM OR DUCT TAPE TO BUILD UP LOWER IN HEIGHT FLOOR FINISH SO THAT THE 2 FORMATS ARE FLUSH
- 4 PAINT MOST OF LADDER (PNT-7), PAINT TOP 3'-0" SECTION OF LADDER SAFETY YELLOW (PNT-8)
- 5 PROVIDE FLOORING TRANSITION/REDUCER BETWEEN TWO DIFFERENT FLOORING MATERIALS/HEIGHT (MISC-6)
- 6 PROVIDE WINDOW BLINDS (MISC-3)
- 7 PROVIDE CORNER GUARD (MISC-9)
- 8 PREP CONCRETE TO RECEIVE EPOXY FINISH (EPX7-1) ON ENTIRE CONCRETE LANDING AND STEPS
- 9 PAINT GUARD RAIL. SEE EXTERIOR PAINT SCHEDULE
- 10 ACCENT WALL (PNT-3)

#### General Finish Notes


1. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL OR OTHER GOVERNING BODIES' CODES. ADDITIONALLY, WORK SHALL BE COMPLETED IN ACCORDANCE WITH APPLICABLE INDUSTRY STANDARDS OR GUIDELINES.
2. ALL DIMENSIONS ARE TO THE FACE OF MASONRY, FACE OF EXISTING WALL AND/OR FACE OF NEW FRAMING UNLESS NOTED OTHERWISE.
3. FURNITURE AND OFFICE EQUIPMENT BY OWNER.
4. ALL DRYWALLED WALL SURFACES SHALL BE MADE SMOOTH PRIOR TO RECEIVING PAINTED FINISH.
5. PRIME AND PAINT HOLLOW METAL DOOR FRAMES (PNT-7).
6. FLOOR COVERING TRANSITIONS (MISC-6) SHALL BE CENTERED BELOW DOORS IN THE CLOSED POSITION UNLESS NOTED OTHERWISE.



**1 First Floor Plan - Offices**  
1/8" = 1'-0"

#### Floor Finish Legend

- (CPT-1) KINETIX TILE
- (CPT-2) WALK-OFF TILE
- (EPXY-1) EPOXY FLOORING
- (CONC-1) SEALED CONCRETE
- (R-1) LVT FLOORING



**KEY PLAN**



**MARTIN RILEY**  
architects+engineers

221 West Baker Street  
Fort Wayne, Indiana 46802

pho 260.422.7994  
fax 260.426.2067



ALL DESIGN, DESIGN DEVELOPMENT, AND/OR CALCULATIONS AND/OR NOTED BY THE DRAWING ARE OWNED BY AND THE PROPERTY OF MARTIN RILEY, INC. AND SHALL REMAIN THE PROPERTY OF MARTIN RILEY, INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF MARTIN RILEY, INC. MARTIN RILEY, INC. SHALL BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS IN THE AS-BUILT AND THIS OFFICE SHALL BE NOTIFIED OF ANY VARIATION FROM THE DIMENSIONS AND CONDITIONS SHOWN ON THESE DRAWINGS. ANY VARIATIONS SHALL BE SUBMITTED TO THE OFFICE FOR REVIEW FOR THE LIMITED PURPOSE OF CORRECTING AND/OR AMENDING INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

REVISION	DATE
1	ADDENDUM 1
	2024-06-12

DRAWN BY:	SAG	REVIEWED BY:	MEK
COMMISSION NUMBER:	F22146	DATE:	2024-05-24

**A602**

FINISH PLANS

New Construction Work for :  
**Porter County Highway Department -  
Central Facility**

1955 IN-2  
Valparaiso, IN 46385




ALL IDEAS, DESIGN, ARRANGEMENTS AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY, AND THE PROPERTY OF MARTIN KLEIN, INC., AND WERE CREATED, EVOLVED, AND DEVELOPED FOR THE USE OF AND IN CONNECTION WITH THE SPECIFIC PROJECT. NONE OF THE IDEAS, DESIGN, ARRANGEMENTS OR PLANS SHALL BE USED BY OR ON BEHALF OF ANY PERSON OR CORPORATION FOR ANY PURPOSE WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF MARTIN KLEIN, INC. WRITTEN DIMENSIONS ON THESE DRAWINGS SHALL HAVE PRECEDENCE OVER SCALE DIMENSIONS. CONTRACTORS SHALL VERIFY AND BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS ON THE JOB AND THIS NOTICE MUST BE NOTICED OF ANY VARIATION FROM DIMENSIONS AND CONDITIONS SHOWN ON THESE DRAWINGS. ALL DETAILS MUST BE LIMITED TO THE SPACE PROVIDED FOR THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

DRAWN BY: RPS  
COMMISSION NUMBER: F22146

REVIEWED BY: RPS  
DATE: 2024-05-24

ELECTRICAL POWER PLAN



7

F22146 - Porter County Highway  
Department - Central Facility  
01/22/2024 2:12:20 PM  
C:\Users\awagh\Documents\F22146 - Porter Co Hwy Complex - Valpo - MEP\_awaagh.nt  
Project Status



- 1 WIRE INDOOR UNIT TO OUTDOOR UNIT WITH 2-#12, 1-#12G IN 3/4"C.
- 2 CAMERA TO BE LOCATED HERE IF COLD STORAGE BLDG ALTERNATE IS NOT TAKEN
- 3 POWER FOR DOOR ACCESS; SEE 7/E501 FOR DETAIL
- 4 RUN 4-#14, 1-#14G IN 3/4"C FORM LOUVER TO STARTER

Work Description Notes



PANEL: MDP

AMPS 800 A	PHASE 3	WIRE 4	VOLTAGE 480/277 WYE	MOUNTING SURFACE	MAIN 800 A	REMARKS: NEMA 1, BOLT ON BREAKERS, 65 KAIC, MCB					
DESCRIPTION	Circuit Number	TRIP	POLE	PHASE A (kVA)	PHASE B (kVA)	PHASE C (kVA)	POLE	TRIP	Circuit Number	DESCRIPTION	
HP1	MDP-1	200 A	3	5.75	4.91			3	200 A	MDP-2 HP2	
--	MDP-3	--	--		6.01	4.77		--	--	MDP-4 --	
--	MDP-5	--	--			1.98	2.91	--	--	MDP-6 --	
HP3	MDP-7	400 A	3	11...	0.00			3	250 A	MDP-8 WH-3	
--	MDP-9	--	--		9.12	0.00		--	--	MDP-10 --	
--	MDP-11	--	--			11.43	0.00	--	--	MDP-12 --	
HP4	MDP-13	100 A	3	0.00						MDP-14	
--	MDP-15	--	--		0.00					MDP-16	
--	MDP-17	--	--			0.00				MDP-18	
--	MDP-19	--	--							MDP-20	
--	MDP-21	--	--							MDP-22	
--	MDP-23	--	--							MDP-24	
--	MDP-25	--	--							MDP-26	
--	MDP-27	--	--							MDP-28	
--	MDP-29	--	--							MDP-30	

PANEL: LP3A												
AMPS 100 A	PHASE 3	WIRE 4	VOLTAGE 120/208 WYE		MOUNTING SURFACE		MAIN 100 A		REMARKS: NEMA 1, BOLT ON BREAKERS, 10 KAIC, MCB			
DESCRIPTION		Circuit Number	TRIP	POLE	PHASE A (kVA)	PHASE B (kVA)	PHASE C (kVA)	POLE	TRIP	Circuit Number	DESCRIPTION	
FUEL ISLAND POWER		LP3A-1	20 A	1	0.50	0.50		1	20 A	LP3A-2	FUEL ISLAND POWER	
FUEL ISLAND POWER		LP3A-3	20 A	1		0.50	0.50		1	20 A	LP3A-4	FUEL ISLAND POWER
SALT BARN POWER		LP3A-5	20 A	1			0.18				LP3A-6	
		LP3A-7									LP3A-8	
		LP3A-9									LP3A-10	
		LP3A-11									LP3A-12	
		LP3A-13									LP3A-14	
		LP3A-15									LP3A-16	
		LP3A-17									LP3A-18	
		LP3A-19									LP3A-20	
		LP3A-21									LP3A-22	
		LP3A-23									LP3A-24	
		LP3A-25									LP3A-26	
		LP3A-27									LP3A-28	
		LP3A-29									LP3A-30	

PANEL: LP3												
AMPS 200 A	PHASE 3	WIRE 4	VOLTAGE 120/208 WYE		MOUNTING SURFACE		MAIN 200 A		REMARKS: NEMA 1, BOLT ON BREAKERS, 10 KAIC, MCB			
DESCRIPTION		Circuit Number	TRIP	POLE	A	B	C	POLE	TRIP	Circuit Number	DESCRIPTION	
		LP3-1								LP3-2		
		LP3-3								LP3-4		
		LP3-5								LP3-6		
		LP3-7								LP3-8		
		LP3-9				0.00		1	20 A	LP3-10	RH	
		LP3-11					0.00	1	20 A	LP3-12	RH	
RH		LP3-13	20 A	1	0.00	0.00		1	20 A	LP3-14	RH	
RH		LP3-15	20 A	1		0.00	0.00	1	20 A	LP3-16	RH	
RH		LP3-17	20 A	1			0.00	0.00	1	20 A	LP3-18	RH
MAINT RECEPT		LP3-19	20 A	1	0.36	0.18		1	20 A	LP3-20	MAINT RECEPT	
MAINT RECEPT		LP3-21	20 A	1		0.18	0.18	1	20 A	LP3-22	MAINT RECEPT	
MAINT RECEPT		LP3-23	20 A	1			0.54	0.18	1	20 A	MAU-1	
MAINT RECEPT		LP3-25	20 A	1	0.36	0.36		1	20 A	LP3-26	MAINT RECEPT	
MAINT RECEPT		LP3-27	20 A	1		0.18	0.18	1	20 A	LP3-28	MAINT RECEPT	
MAINT RECEPT		LP3-29	20 A	1			0.18	0.18	1	20 A	LP3-30	MAINT RECEPT
MAINT RECEPT		LP3-31	20 A	1	0.36	0.36		1	20 A	LP3-32	MAINT RECEPT	
MAINT RECEPT		LP3-33	20 A	1		0.36	0.36	1	20 A	LP3-34	MAINT RECEPT	
MAINT RECEPT		LP3-35	20 A	1			0.36	0.36	1	20 A	LP3-36	MAINT RECEPT
FLUIDS RECEPT		LP3-37	20 A	1	0.36	0.36		1	20 A	LP3-38	PARTS RECEPT	
PARTS RECEPT		LP3-39	20 A	1		1.08	0.54	1	20 A	LP3-40	SIGNS OFFICE RECPTS	
PARTS ROLL DOOR		LP3-41	20 A	1			0.00	0.00	1	20 A	LP3-42	UH-3
CH		LP3-43	20 A	1	0.00	0.36		1	20 A	LP3-44	SIGNAGE RECEPT	
RR RECEPT		LP3-45	20 A	1		0.18	0.36	1	20 A	LP3-46	SIGNAGE RECEPT	
EF-7.8		LP3-47	20 A	1			0.00			LP3-48		
WH-2		LP3-49	20 A	1	0.00	0.00		2	20 A	LP3-50	AIR COMP	
UH-2		LP3-51	20 A	1		0.00	0.00	--	--	LP3-52	--	
MAPS RECEPTS		LP3-53	20 A	1			0.18	0.00	2	15 A	LP3-54	PTHP
SIGNAGE RECEPT		LP3-55	20 A	1	0.72	0.00		--	--	LP3-56	--	
SIGNAGE RECEPT		LP3-57	20 A	1		0.72	0.72	1	20 A	LP3-58	SIGNAGE RECEPT	
SIGNAGE RECEPT		LP3-59	20 A	1			0.72	0.54	1	20 A	LP3-60	WASH BAY RECEPT
RH		LP3-61	20 A	1	0.00	0.36		1	20 A	LP3-62	WASH BAY RECEPT	
UH-5		LP3-63	20 A	1		0.00				LP3-64		
Spare		LP3-65	20 A	1			0.00	0.00	1	20 A	LP3-66	Spare
Spare		LP3-67	20 A	1	0.00	0.00		1	20 A	LP3-68	Spare	
Spare		LP3-69	20 A	1		0.00	0.00	1	20 A	LP3-70	Spare	
Spare		LP3-71	20 A	1			0.00	0.00	1	20 A	LP3-72	Spare
UH-4		LP3-73	20 A	1	0.00	0.00		1	20 A	LP3-74	EF-13	
LIGHTS		LP3-75	20 A	1		0.09	1.00	1	20 A	LP3-76	IT RACK	
EF-9		LP3-77	20 A	1			0.00	1.00	3	10...	LP3-78	LP3A, 120 V/208 V, Thre...
LIFT POWER		LP3-79	20 A	2	0.00	1.00		--	--	LP3-80	--	
--		LP3-81	--	--		0.00	0.18	--	--	LP3-82	--	
--		LP3-83	--	--				--	--	LP3-84	--	


PANEL: LP4											
AMPS 100 A	PHASE 3	WIRE 4	VOLTAGE 120/208 WYE		MOUNTING SURFACE		MAIN 60 A		REMARKS: NEMA 1, BOLT ON BREAKERS, 10 KA/IC, MCB		
DESCRIPTION	Circuit Number	TRIP	POLE	PHASE A (kVA)	PHASE B (kVA)	PHASE C (kVA)	POLE	TRIP	Circuit Number	DESCRIPTION	
STORAGE RECEPT	LP4-1	20 A	1	0.36					LP4-2		
STORAGE RECEPT	LP4-3	20 A	1		0.36				LP4-4		
Power	LP4-5	20 A	1			0.36			LP4-6		
	LP4-7								LP4-8		
	LP4-9								LP4-10		
	LP4-11								LP4-12		
	LP4-13								LP4-14		
	LP4-15								LP4-16		
	LP4-17								LP4-18		
	LP4-19								LP4-20		
	LP4-21								LP4-22		
Spare	LP4-23	20 A	1			0.00	0.00	1	20 A	Spare	
Spare	LP4-25	20 A	1	0.00	0.00			1	20 A	Spare	
Spare	LP4-27	20 A	1		0.00	0.00		1	20 A	Spare	
Spare	LP4-29	20 A	1			0.00	0.00	1	20 A	Spare	

PANEL: LP2											
AMPS 100 A	PHASE 3	WIRE 4	VOLTAGE 120/208 WYE	MOUNTING SURFACE	MAIN 100 A	REMARKS: NEMA 1, BOLT ON BREAKERS, 10 KAIC, MCB					
DESCRIPTION	Circuit Number	TRIP	POLE	PHASE A (kVA)	PHASE B (kVA)	PHASE C (kVA)	POLE	TRIP	Circuit Number	DESCRIPTION	
TRUCK PARKING RECPT	LP2-1	20 A	1	0.36	0.18			1	20 A	LP2-2 TRUCK PARKING RECPT	
TRUCK PARKING RECPT	LP2-3	20 A	1		0.18	0.36		1	20 A	LP2-4 TRUCK PARKING RECPT	
TRUCK PARKING RECPT	LP2-5	20 A	1			0.18	0.54	1	20 A	LP2-6 TRUCK PARKING RECPT	
TRUCK PARKING RECPT	LP2-7	20 A	1	0.36	0.18			1	20 A	LP2-8 TRUCK PARKING RECPT	
TRUCK PARKING RECPT	LP2-9	20 A	1		0.18	0.18		1	20 A	LP2-10 TRUCK PARKING RECPT	
TRUCK PARKING RECPT	LP2-11	20 A	1			0.36	0.36	1	20 A	LP2-12 TRUCK PARKING RECPT	
TRUCK PARKING RECPT	LP2-13	20 A	1	0.36	0.00			1	20 A	LP2-14 RH	
ELEC RM & SPRINKLER RM...	LP2-15	20 A	1		0.00	0.00		1	20 A	LP2-16 RH	
	LP2-17						0.00	1	20 A	LP2-18 RH	
RH	LP2-19	20 A	1	0.00	0.00			1	20 A	LP2-20 EF	
RH	LP2-21	20 A	1		0.00	0.00		1	20 A	LP2-22 EF	
RH	LP2-23	20 A	1			0.00				LP2-24	
	LP2-25									LP2-26	
Spare	LP2-27	20 A	1		0.00	0.00		1	20 A	LP2-28 Spare	
Spare	LP2-29	20 A	1			0.00	0.00	1	20 A	LP2-30 Spare	


PANEL: LP1											
AMPS 200 A	PHASE 3	WIRE 4	VOLTAGE 120/208 WYE	MOUNTING SURFACE	MAIN 200 A	REMARKS: NEMA 1, BOLT ON BREAKERS, 10 KA/IC, MCB					
DESCRIPTION	Circuit Number	TRIP	POLE	A	B	C	POLE	TRIP	Circuit Number	DESCRIPTION	
MAIN OFF RECEPT	LP1-1	20 A	1	0.36	0.72			1	20 A	LP1-2 SUPER RECEPT	
MAIN OFF RECEPT	LP1-3	20 A	1		0.36	0.72		1	20 A	LP1-4 ENG RECEPT	
ASST SUPER RECEPT	LP1-5	20 A	1			0.72	0.90	1	20 A	LP1-6 HALLWAY RECEPT	
FOREMAN RECEPT	LP1-7	20 A	1	0.54	0.54			1	20 A	LP1-8 CONFERENCE RECEPT	
VESTIBULE RECEPT	LP1-9	20 A	1		0.18	0.36		1	20 A	LP1-10 RR RECEPT	
CONFERENCE RECEPT	LP1-11	20 A	1			0.36	0.18	1	20 A	LP1-12 MECH/STORAGE RECEPT	
MAPS RECEPTS	LP1-13	20 A	1	0.36	0.54			1	20 A	LP1-14 STORAGE RECEPT	
WH-1	LP1-15	20 A	1		0.00	0.36		1	20 A	LP1-16 IT RECEPT	
CIRC PUMP	LP1-17	20 A	1			0.18	0.18	1	20 A	LP1-18 IT RECEPT	
TRAINING RECEPT	LP1-19	20 A	1	0.36	0.36			1	20 A	LP1-20 TRAINING RECEPT	
TRAINING RECEPT	LP1-21	20 A	1		0.54	0.18		1	20 A	LP1-22 TRAINING DISHWASHER	
TRAINING RECEPT	LP1-23	20 A	1			0.36	0.18	1	20 A	LP1-24 TRAINING RECEPT	
TRAINING RECEPT	LP1-25	20 A	1	0.54	1.25			2	30 A	LP1-26 DRYER	
WASHER	LP1-27	20 A	1		0.18	1.25		--	--	LP1-28	
DRYER	LP1-29	30 A	2			1.25	0.18	1	20 A	LP1-30 WASHER	
--	LP1-31	--	--	1.25	0.18			1	20 A	LP1-32 LOCKER RM RECEPT	
LOCKER RM RECEPT	LP1-33	20 A	1		0.54	0.72		1	20 A	LP1-34 FOREMAN RECEPT	
Spare	LP1-35	20 A	1			0.00	0.00	1	20 A	LP1-36 Spare	
Spare	LP1-37	20 A	1	0.00	0.00			1	20 A	LP1-38 Spare	
Spare	LP1-39	20 A	1		0.00	0.00		1	20 A	LP1-40 Spare	
Spare	LP1-41	20 A	1			0.00	0.00	1	20 A	LP1-42 Spare	
HALLWAY RECEPT	LP1-43	20 A	1	0.54	0.36			1	20 A	LP1-44 DRINKING FOUNTAINS	
MS-1	LP1-45	20 A	2		0.50	0.18		1	20 A	LP1-46 ROOF RECEPT	
--	LP1-47	--	--				0.00	0.50	1	20 A	LP1-48 EF-4
EF-15	LP1-49	30 A	1	0.50						LP1-50	LP1-50
EF-14	LP1-51	30 A	1	0.50	0.50					LP1-52	LP1-52
	LP1-53									LP1-54	LP1-54
	LP1-55									LP1-56	LP1-56
	LP1-57									LP1-58	LP1-58
	LP1-59									LP1-60	LP1-60




F22146 - Porter County Highway Department - Valparaiso, IN 46385  
C:\Users\seawigh\Documents\F22146 - Porter Co Hwy Complex - Valpo - ARCH\_Lavaughn.rvt  
S:\DD\CD




**7** Base Flashing  
3" = 1'-0"




**6** Multi Pipe Seal  
3" = 1'-0"




**5** High Eave  
3" = 1'-0"




**3** Rake Edge  
3" = 1'-0"



**4** Ridge  
3" = 1'-0"



**2** Gutter  
3" = 1'-0"



**1** Roof Drain  
1 1/2" = 1'-0"

Detail Work Description Notes

- NEW EAVE STRUT - SEE STRUCTURAL DRAWINGS
- NEW ROOF PURLIN - SEE STRUCTURAL DRAWINGS
- NEW TAPERED INSULATION SUMP, SHAVE FLUSH WITH ROOF SUMP DECK FLANGE
- NEW FSR-FLEXIBLE SHEET ROOFING (FSR)
- NEW 1 1/2" TYPE B METAL DECK
- NEW ADHESIVELY ADHERED RECOVER BOARD INSULATION
- PROVIDE NEW CAST IRON ROOF DRAIN BOWL AND OVERFLOW SUMP BOWL, CLAMPING RING, AND STRAINER. SET CLAMPING RING IN NEW LEAD FLASHING
- NEW CONTINUOUS BEAD OF MANUFACTURER'S WATER CUT OFF MASTIC
- NEW 20 GA STEEL PLATE MECHANICALLY ATTACHED TO DECK - EXTEND 2'-0" MIN. FROM CENTER OF ROOF DRAIN
- INSULATE NEW DRAIN BOWL
- NEW ROOF PENETRATION
- NEW INSULATED METAL EQUIPMENT CURB
- NEW STAINLESS STEEL COMPRESSION DRAW BAND
- NEW MANUFACTURER'S FLEXIBLE EPDM MULTI-PENETRATION PIPE SEAL CAP
- NEW WOOD BLOCKING MECHANICALLY ATTACHED TO SUBSTRATE
- NEW MECHANICALLY ATTACHED RIGID INSULATION BOARD AND ADHESIVELY ADHERED COVER BOARD INSULATION
- NEW HOT AIR WELD JOINT WITH TOOLED MANUFACTURERS RECOMMENDED SEALANT
- NEW FLEXIBLE SHEET ROOFING SEAM PLATE WITH FASTENERS 12" C/C MAX
- CLEAN AND PRIME SUBSTRATE, PROVIDE NEW FULLY ADHERED FLEXIBLE SHEET ROOFING (FSR) FLASHING
- NEW R-19 BLANKET INSULATION WITH VAPOR RETARDER AT MAIN BUILDING. COLD STORAGE BUILDING DOES NOT REQUIRE INSULATION
- NEW R-30 BLANKET INSULATION
- NEW MANUFACTURERS EAVE FLASHING TRIM WITH CLOSURE AT NEW METAL WALL PANEL - EXTEND CLOSURE UP INTO PANEL RIBS
- NEW PRE-MANUFACTURED GUTTER SYSTEM
- NEW ROOFING MANUFACTURER GUTTER STRAP
- NEW ROOFING MANUFACTURING CORRUGATED METAL PANEL PLUG
- NEW MANUFACTURERS PREFINISHED GI CORRUGATED WALL PANEL OR INSULATED METAL WALL PANEL, REFER TO WALL SECTIONS AND SPECIFICATIONS
- NEW MANUFACTURERS STRUCTURAL STANDING SEAM METAL ROOF PANEL WITH NEW WMP50 VAPOR RETARDER FACTORY APPLIED TO NEW R19 BLANKET INSULATION
- NEW HIGH PANEL CLIPS AND THERMAL BLOCKS
- NEW MANUFACTURERS "Z" PURLIN
- NEW MANUFACTURERS RIDGE COVER
- NEW MANUFACTURERS RAKE CLOSURE PIECE - INSTALL PER MANUFACTURER REQUIREMENTS
- NEW MANUFACTURERS STANDARD 24 GA PREFINISHED GI RAKE EDGE FLASHING
- NEW STRUCTURAL SYSTEM - SEE STRUCTURAL FOR MORE INFORMATION
- NEW INSULATED WALL PANEL EAVE SUPPORT ANGLE
- NEW MECHANICALLY ATTACHED BASE SHEET
- NEW MANUFACTURERS APPROVED TOOLED SEALANT
- NEW CONTINUOUS MANUFACTURER'S SURFACE MOUNTED TERMINATION BAR MECHANICALLY ATTACHED 6" C/C MAX. CAULK ALL VERTICAL TRANSITIONS
- NEW WATER CUT OFF MASTIC
- NEW 24 GA PREFINISHED GI REGLET RECEIVER
- NEW 24 GA PREFINISHED GI COUNTERFLASHING MECHANICALLY ATTACHED TO RECEIVER AT 12" C/C MAX
- NEW CONTINUOUS TOOLED URETHANE SEALANT
- NEW LEAD WEDGES SPACED 5'-0" C/C MAX
- PROVIDE NEW FOAM BACKER ROD SIZED 50% LARGER THAN JOINT
- NEW METAL SOFFIT
- NEW EXTERIOR GRADE PLYWOOD
- NEW BRICK VENEER
- REFER TO WALL SECTIONS FOR WALL COMPOSITION
- NEW CANOPY FRAMING - SEE STRUCTURAL
- NEW LOCK SEAM PLUG
- NEW BACK UP STRAP

New Construction Work for :


Porter County Highway Department -  
Central Facility

1955 IN-2  
Valparaiso, IN 46385



MARTIN RILEY  
architects+engineers

221 West Baker Street  
Fort Wayne, Indiana 46802  
pho 260.422.7994  
fax 260.426.2067



ALL SEAL, DESIGN, ARRANGEMENTS, NOTICES AND NOTATIONS ON THIS DRAWING ARE OWNED BY, AND THE PROPERTY OF, MARTIN RILEY, INC. AND SHALL REMAIN THE PROPERTY OF MARTIN RILEY, INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF MARTIN RILEY, INC. MARTIN RILEY, INC. SHALL BE RESPONSIBLE FOR ALL DESIGN AND CONSTRUCTION OF THE WORK AND THIS OFFICE SHALL BE NOTIFIED OF ANY VIOLATION FROM THE CONTRACT DOCUMENTS OF THIS DRAWING. ANY VIOLATION SHALL BE SUBJECT TO THE FOLLOWING FOR REVIEW FOR THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH FABRICATION.

REVISION:	DATE:
1	ADDENDUM 1
	2024-06-12

DRAWN BY: CLW  
COMMISSION NUMBER: F22146  
REVIEWED BY: ALW  
DATE: 2024-05-24

R201

ROOF DETAILS

F22146 - Porter County Highway  
Central Facility  
07/22/2024 2:25 PM  
C:\Users\awaghi\Documents\F22146 - Porter Co Hwy Complex - Vapoo - STR - Unweighted  
SDDDDCDD

## Masonry Notes

- THE DESIGN AND CONSTRUCTION SHALL CONFORM TO THE AMERICAN CONCRETE INSTITUTE "BUILDING CODE REQUIREMENTS FOR MASONRY STRUCTURES (ACI 530)," LATEST EDITION.
- CMU SHALL BE HOLLOW CONCRETE MASONRY UNITS CONFORMING TO THE REQUIREMENTS OF THE LATEST EDITION OF ASTM C90, GRADE N, TYPE 1, IN NATURAL GRAY COLOR.
- MINIMUM COMPRESSIVE STRENGTH OF MASONRY,  $f_m = 2000$  psi.
  - NET AREA COMPRESSIVE STRENGTH OF CONCRETE MASONRY UNITS WITH TYPE M OR S MORTAR = 2800 psi.
  - NET AREA COMPRESSIVE STRENGTH OF CLAY MASONRY UNITS WITH TYPE M OR S MORTAR = 4950 psi.
- MINIMUM COMPRESSIVE STRENGTH OF GROUT, AS DETERMINED IN ACCORDANCE WITH THE LATEST EDITION OF ASTM C1019, SHALL MEET OR EXCEED  $f_m$ , BUT NOT LESS THAN 2000 psi. GROUT TYPE AND SPACING REQUIREMENTS SHALL CONFORM TO LATEST EDITION OF ACI 530.
- MORTAR SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST EDITION OF ASTM C270.
- JOINT REINFORCEMENT SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST EDITION OF ASTM A951.
- ALL PLAIN WIRE REINFORCING STEEL SHALL COMPLY WITH THE REQUIREMENTS OF THE LATEST EDITION OF ASTM A62.
- REINFORCING BARS SHALL BE DEFORMED BARS CONFORMING TO THE REQUIREMENTS OF THE LATEST EDITION OF ASTM A615, GRADE 60.
- REINFORCING BARS SHALL HAVE A MASONRY COVER NOT LESS THAN THE FOLLOWING, UNLESS NOTED OTHERWISE:
  - #6 BARS AND LARGER.....2"
  - #5 BARS AND SMALLER.....1-1/2"
  - MASONRY NOT EXPOSED TO EARTH OR WEATHER.....1-1/2"
- THE REQUIRED DEVELOPMENT LENGTH OF REINFORCING BARS SHALL NOT BE LESS THAN 12 INCHES, AND AS FOLLOWS ( $f_y = 2000$  psi;  $K = 2$ ;  $f_d = 60,000$  psi):
  - #3 THROUGH #5.....88d<sup>2</sup>
  - #6 THROUGH #7.....114d<sup>2</sup>
  - #8 THROUGH #11.....131d<sup>2</sup>
- PLATE AND BENT BAR ANCHORS SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST EDITION OF ASTM A36.
- ANCHOR BOLTS SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST EDITION OF ASTM A307, GRADE A.
- ANCHOR BOLTS PLACED IN THE TOP OF GROUTED CELLS AND BOND BEAMS SHALL BE POSITIONED TO MAINTAIN A MINIMUM OF:
  - 1/4-INCH OF FINE GROUT BETWEEN THE BOLTS AND THE MASONRY UNIT.
  - 1/2-INCH OF COURSE GROUT BETWEEN THE BOLTS AND THE MASONRY UNIT.
- ANCHOR BOLTS PLACED IN DRILLED HOLES IN THE FACE SHELLS OF HOLLOW MASONRY UNITS SHALL BE PERMITTED TO CONTACT THE MASONRY UNIT WHERE THE BOLT PASSES THROUGH THE FACE SHELL PROVIDED THE PORTION OF THE BOLT THAT IS WITHIN THE GROUTED CELL SHALL BE POSITIONED TO MAINTAIN A MINIMUM OF:
  - 1/4-INCH OF FINE GROUT BETWEEN THE HEAD OR BENT LEG OF EACH BOLT AND THE MASONRY UNIT.
  - 1/2-INCH OF COURSE GROUT BETWEEN THE HEAD OR BENT LEG OF EACH BOLT AND THE MASONRY UNIT.
- THE CLEAR DISTANCE BETWEEN ANCHOR BOLTS SHALL NOT BE LESS THAN THE NOMINAL DIAMETER OF THE ANCHOR BOLT, NOR LESS THAN ONE INCH.
- SLEEVE TYPE ANCHORS SHALL FEATURE A SPLIT EXPANSION SLEEVE OVER A THREADED STUD BOLT BODY AND INTEGRAL EXPANDER, NUT AND WASHER; SHALL BE ZINC-PLATED CARBON STEEL, UNLESS OTHERWISE SPECIFIED AS STAINLESS STEEL (TYPE 304), AND SHALL BE INSTALLED WITH CARBIDE TIPPED HAMMER DRILL BITS MADE IN ACCORDANCE TO ANSI B212.1-1994.
- DETAILS OF REINFORCEMENT AND METAL ACCESSORIES AS WELL AS PROTECTION REQUIREMENTS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF ACI 530.
- MASONRY UNTEL TOP REINFORCEMENT SHALL EXTEND TWO INCHES BEYOND ROUGH OPENING AND BOTTOM REINFORCEMENT SHALL EXTEND EIGHT INCHES BEYOND ROUGH OPENING.
- PROVIDE A MINIMUM BEARING LENGTH OF EIGHT INCHES AT EACH END OF REINFORCED MASONRY LINTELS.
- ALL MASONRY WALLS SHALL BE PLACED IN A RUNNING-BOND PATTERN UNLESS SPECIFICALLY DETAILED OTHERWISE.
- MESH WALL TIES (MWT) SHALL CONFORM TO THE REQUIREMENTS OF ASTM A185 AND SHALL BE COMPRISED OF MATERIALS CONFORMING TO THE FOLLOWING, AS SPECIFICALLY CALLED OUT IN THE DETAILS:
  - COLD-DRAWN STEEL WIRE.....ASTM A1064/A1064M
  - HARDWARE CLOTH.....ASTM A740
  - HOT-DIP GALVANIZED.....ASTM A153/A153M 82 CLASS B
  - STAINLESS STEEL.....ASTM E2016, TYPE 304

## Steel Joist Notes

- STEEL JOIST CONSTRUCTION SHALL CONFORM TO THE LATEST EDITION OF THE STEEL JOIST INSTITUTE'S "STANDARD SPECIFICATIONS, LOAD TABLES, & WEIGHT TABLES FOR STEEL JOISTS & JOIST GIRDERS".
- HANDLING AND ERECTION OF STEEL JOISTS AND MATERIALS SHALL COMPLY WITH THE STEEL JOIST INSTITUTE'S TECHNICAL DIGEST 9, "HANDLING AND ERECTION OF STEEL JOISTS AND JOIST GIRDERS".
- THE MAXIMUM SPACING OF STEEL JOISTS SHALL BE AS SHOWN ON THE STRUCTURAL PLANS. PROVIDE HEADERS AND DOUBLE JOISTS AS REQUIRED TO FRAME AROUND OPENINGS SHOWN ON THE STRUCTURAL PLANS. THIS WORK SHALL BE FULLY COORDINATED WITH ALL OTHER TRADES.
- ENDS OF STEEL JOISTS SHALL BE ANCHORED TO THE SUPPORTING MEMBERS AS INDICATED BY TYPICAL DETAILS PROVIDED ON THE STRUCTURAL PLANS.
- PROVIDE JOIST SUBSTITUTES CAPABLE OF CARRYING ALLOWABLE TOTAL SAFE LOADS IN LBS/ LINEAR FOOT AS CALLED FOR ON DRAWINGS.
- BRIDGING AND BRIDGING ANCHORS SHALL BE IN ACCORDANCE WITH SECTION 2.7 OF THE SJI CODE OF STANDARD PRACTICE. BRIDGING, STANDARD WITH THE MANUFACTURER AND COMPLYING WITH THE STEEL JOIST INSTITUTE STANDARD SPECIFICATIONS LOAD TABLES & WEIGHT TABLES OF LATEST ADOPTION, SHALL BE USED FOR BRIDGING ALL JOISTS FURNISHED BY THE MANUFACTURER. POSITIVE ANCHORAGE SHALL BE PROVIDED AT THE ENDS OF EACH BRIDGING ROW AT BOTH TOP AND BOTTOM CHORDS.
- MINIMUM 3/8 INCH DIAMETER A307 BOLTS TO BE USED IN ALL BOLTED BRIDGING CONNECTIONS. ALL BOLTS SHALL BE TIGHTENED TO A MINIMUM SNUG-TIGHT CONDITION AND WASHERS SHALL BE USED WITH SLOTTED OR OVERSIZED HOLES.
- ADDITIONAL UPLIFT BRIDGING SHALL BE INSTALLED AS REQUIRED PER SJI STANDARD SPECIFICATIONS.
- VERIFY SIZE AND LOCATION OF ANY INDICATED ROOF OPENINGS WITH MECHANICAL CONTRACTOR (SEE MECHANICAL PLANS FOR ROOF TOP UNIT, RTU, LOCATIONS).
- JOIST MANUFACTURER SHALL DESIGN ROOF JOISTS, WHERE RTUS ARE INDICATED, FOR A 500 LB ADD-LOAD (SEE ROOF PLAN). REINFORCE JOISTS AT CONCENTRATED LOAD LOCATIONS IN ACCORDANCE WITH FIELD REINFORCEMENT DETAIL PROVIDED.

## Structural Steel Notes

- STRUCTURAL STEEL TO BE FABRICATED AND ERECTED IN ACCORDANCE WITH AISC 360 "SPECIFICATIONS FOR STRUCTURAL STEEL BUILDINGS", AND AISC 303 "CODE OF STANDARD PRACTICE FOR STEEL BUILDINGS AND BRIDGES".
- DETERMINE, FURNISH AND INSTALL ALL TEMPORARY SUPPORTS, SUCH AS TEMPORARY GUYS, BEAMS, FALSEWORK, CRIBBING OR OTHER ELEMENTS REQUIRED FOR THE ERECTION OF STRUCTURAL CONCRETE. THE TEMPORARY SUPPORTS SHALL BE SUFFICIENT TO SECURE THE BARE STRUCTURAL STEEL FRAMING OR ANY PORTION THEREOF AGAINST LOADS THAT ARE LIKELY TO BE ENCOUNTERED DURING ERECTION, INCLUDING THOSE DUE TO WIND AND THOSE THAT RESULT FROM ERECTION OPERATIONS.
- STRUCTURAL STEEL SHOP-STANDARD MATERIAL SHALL BE AS FOLLOWS:
  - W AND WT-SHAPES TO BE ASTM A992
  - M, S, MT, ST-SHAPES TO BE ASTM A36
  - HP-SHAPES TO BE ASTM A36
  - L-SHAPES TO BE ASTM A36
  - C AND MC-SHAPES TO BE ASTM A36
  - HSS-SHAPES TO BE ASTM A500, GRADE B
  - PIPE TO BE ASTM A53, GRADE B
  - PLATES AND BARS TO BE ASTM A36
  - ALL THROUGH ROD TO BE ASTM A36
  - ANCHOR RODS TO BE ASTM F1554, GRADE 36
  - HEADED STUDS TO BE TYPE B WITH MINIMUM TENSILE STRENGTH,  $F_u = 65$  ksi, AND MINIMUM YIELD STRENGTH,  $F_y = 51$  ksi.
- BAR GRATING TO BE 19-W-4, WELDED, 1-1/4" x 3/16" RECTANGULAR BAR, SERRATED SURFACE, HOT DIPPED, GALVANIZED STEEL.
- STAIR TREADS TO BE 19-W-4, WELDED, 1-1/4" x 3/16" RECTANGULAR BAR, SERRATED SURFACE, HOT DIPPED, GALVANIZED STEEL W/ CHECKERED PLATE 90° ANGLE NOSING AND BAR GRATING STAIR TREAD CARRIER PLATES ATTACHED.
- HIGH-STRENGTH BOLTS SHALL MEET THE MATERIAL STRENGTHS OF ANSIA/ISC 360 SPECIFICATION GROUP A. DOCUMENTATION SHALL BE PROVIDED BY THE CONTRACTOR TO PROVE QUALITY OF THE BOLTS AND THREADED PARTS.
- ALL WELDING SHALL BE IN ACCORDANCE WITH THE AWS D1.1 "STRUCTURAL WELDING CODE - STEEL" PUBLISHED BY THE AMERICAN WELDING SOCIETY. ELECTRODES FOR WELDED JOINTS SHALL COMPLY WITH THE REQUIREMENTS OF TABLE 3.1 OF AWS D1.1. ALL WELDING TO BE COMPLETED BY QUALIFIED WELDERS CONFORMING TO THE AMERICA WELDING SOCIETY STANDARDS.
- THE STEEL FABRICATOR SHALL DESIGN AND SUPPLY APPROPRIATE PRODUCTS FOR ALL STEEL AND METAL ITEMS NOT SPECIFICALLY DETAILED ON DRAWINGS. ALL DESIGNS, METHODS, AND MATERIALS, SHALL COMPLY WITH THE AISC "STEEL CONSTRUCTION MANUAL," CURRENT EDITION.
- FABRICATION "SHOP" DRAWINGS SHALL BE SUPPLIED BY THE CONTRACTOR. ALL SHOP DRAWINGS SHALL BE SUBMITTED TO THE ENGINEER OF RECORD FOR REVIEW AND APPROVAL PRIOR TO FABRICATION.
- ALL BOLTED CONNECTIONS TO BE SNUG-TIGHTENED JOINTS PER "THE SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS", UNLESS NOTED OTHERWISE.
- BOLTED CONNECTIONS INDICATED AS PRE-TENSIONED SHALL BE FASTENED BY MEANS OF THE TURN-OF-NUT METHOD, UNLESS NOTED OTHERWISE.
- SIMPLE SHEAR CONNECTIONS SHALL BE DESIGNED BY THE FABRICATOR'S ENGINEER FOR THE REACTION RIGS. IF A REACTION IS PROVIDED, THE FABRICATOR'S ENGINEER SHALL DESIGN THE CONNECTION FOR AT LEAST 50% OF THE SUPPORTED BEAMS UNIFORM LOAD CONSTANT,  $w_u$ , DIVIDED BY THE SPAN LENGTH,  $L$ , AS TABULATED IN THE CURRENT EDITION OF THE AISC "STEEL CONSTRUCTION MANUAL," PART 3, "MAXIMUM TOTAL UNIFORM LOAD TABLES".
- SIMPLE SHEAR CONNECTIONS, NOT SHOWN IN THE DRAWINGS, SHALL BE DETAILED BY THE STEEL FABRICATOR IN ACCORDANCE WITH THE CURRENT EDITION OF THE AISC "STEEL CONSTRUCTION MANUAL," PART 10, "DESIGN OF SIMPLE SHEAR CONNECTIONS".
  - FOR SHEAR END-PLATE DOUBLE-ANGLE CONNECTIONS, OFFSET HOLES OR ADD ADDITIONAL ROWS OF BOLTS AS REQUIRED TO COMPLY WITH OSHA SAFETY BOLTING REQUIREMENTS.
  - MINIMUM LENGTH OF CONNECTING ANGLES OR PLATES SHALL BE GREATER THAN THE SUPPORTED BEAM "T" DIMENSION DIVIDED BY 2.
- HORIZONTAL AND VERTICAL BRACING CONNECTIONS SHALL BE DESIGNED BY THE FABRICATOR'S ENGINEER FOR THE AXIAL LOAD (COMPRESSION OR TENSION) LISTED IN THE DRAWINGS. IF NO LOAD IS PROVIDED, THE FABRICATOR'S ENGINEER SHALL DESIGN THE BRACING CONNECTION FOR 100% OF THE BRACING MEMBERS AVAILABLE STRENGTH IN AXIAL TENSION (ASD), AS GIVEN IN THE CURRENT EDITION OF THE AISC "STEEL CONSTRUCTION MANUAL," PART 5.
- HORIZONTAL AND VERTICAL BRACING CONNECTIONS, NOT SHOWN IN THE DRAWINGS, SHALL BE DETAILED BY THE FABRICATOR IN ACCORDANCE WITH THE CURRENT EDITION OF AISC "STEEL CONSTRUCTION MANUAL", AND AISC 360, AS APPLICABLE.
  - GUSSET PLATES SHALL BE SIZED TO ACCOMMODATE REQUIRED LOADS. AS A MINIMUM, GUSSETS SHALL BE 3/8 INCH THICK.
  - AS A MINIMUM, THE WELD BETWEEN THE GUSSET PLATE AND THE SUPPORT SHALL BE SIZED AS (50%).
  - AS A MINIMUM, 3/4-INCH DIAMETER BOLTS SHALL BE UTILIZED FOR BOLTED CONNECTIONS. IF A BOLT IS CHOSEN WITH A NOMINAL DIAMETER GREATER THAN ONE INCH, INCREASE THE SPACING BETWEEN BOLTS TO A MINIMUM OF 3d.
  - ACTUAL LOAD REQUIREMENTS MAY DICTATE THAT MORE BOLTS ARE REQUIRED. A MINIMUM OF TWO BOLTS SHALL BE UTILIZED.

- FABRICATE AND ERECT ALL BEAMS WITH THE MILL CAMBER UP.
- ALL STRUCTURAL STEEL SHALL BE CLEANED AND PREPARED FOR THE SPECIFIED COATING SYSTEM IN ACCORDANCE WITH THE REQUIREMENTS OF SSPC-SP2, UNLESS OTHERWISE SPECIFIED BY THE COATING SYSTEM MANUFACTURER.
- STRUCTURAL STEEL MEMBERS COMPLETELY ENCLOSED IN THE BUILDING ENVELOPE SHALL BE SHOP COATED WITH THE FABRICATOR'S STANDARD SHOP PAINT APPLIED TO A MINIMUM DRY-FILM THICKNESS OF ONE MIL.
- STRUCTURAL STEEL MEMBERS ON THE EXTERIOR OF THE BUILDING, EXPOSED TO SOIL, OR OTHERWISE EXPOSED TO CONDITIONS PROMOTING CORROSION SHALL BE, AT A MINIMUM, PROPERLY PRIMED WITH RUST INHIBITING PRIMER AND PAINTED. REFER TO ARCHITECTURAL DOCUMENTS FOR ADDITIONAL REQUIREMENTS OF EXPOSED STEEL.
- THE CONTRACTOR THAT PERFORMS TOUCH-UP AND FIELD PAINTING IS RESPONSIBLE FOR ALL TOUCH-UP OF ABRASIONS CAUSED BY HANDLING AFTER PAINTING.
- NON-SHRINK GROUT USED FOR SETTING AND FINISHING COLUMN BASE PLATES AND EQUIPMENT BASES SHALL BE A COMMERCIALY PRE-MIXED AND BAGGED NON-METALLIC PRODUCT, AS APPROVED BY OWNER, CONTAINING, AS PART OF THE MIX, AN ADDITIVE TO COUNTERACT SHRINKAGE AND SETTLEMENT OF THE GROUT. NON-SHRINK GROUT SHALL REQUIRE ONLY THE ADDITION OF MIXING WATER FOR USE, AND SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 7000 psi AT 28 DAYS.

## PEMB Structural Steel Notes

- PRE-ENGINEERED METAL BUILDING (PEMB) STRUCTURAL COMPONENTS TO BE DESIGNED AND DETAILED PER PEMB MANUFACTURER.
- THE CONTRACTOR TO SUPPLY SEALED ENGINEERING DESIGN DATA AND DRAWINGS FOR PEMB MANUFACTURER SUPPLIED MATERIAL AS PART OF THE OVERALL PROJECT TO OBTAIN PERMITS, APPROVALS, AND COORDINATE OTHER TRADES.

## Concrete Notes

- THE DESIGN AND CONSTRUCTION SHALL CONFORM TO THE AMERICAN CONCRETE INSTITUTE "BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE (ACI 318)," LATEST EDITION AND "CODE REQUIREMENTS FOR ENVIRONMENTAL ENGINEERING CONCRETE STRUCTURES (ACI 350)," LATEST EDITION.
- CONCRETE CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE AMERICAN CONCRETE INSTITUTE "SPECIFICATIONS FOR STRUCTURAL CONCRETE (ACI 301)," LATEST EDITION AND "SPECIFICATION FOR TOLERANCES FOR CONCRETE CONSTRUCTION AND MATERIALS (ACI 117)," LATEST EDITION.
- WHEN CONDITIONS ARE SUCH THAT THE AMBIENT TEMPERATURE MAY BE EXPECTED TO BE 40°F OR LESS, WORK SHALL CONFORM TO THE AMERICAN CONCRETE INSTITUTE "GUIDE TO COLD WEATHER CONCRETING (ACI 308R)," LATEST EDITION.
- WHEN CONDITIONS ARE SUCH THAT THE AMBIENT TEMPERATURE MAY BE EXPECTED TO BE 80°F OR HIGHER, WORK SHALL CONFORM TO THE AMERICAN CONCRETE INSTITUTE "GUIDE TO HOT WEATHER CONCRETING (ACI 308R)," LATEST EDITION.
- CONCRETE SHALL BE NORMAL WEIGHT CONCRETE CONFORMING TO THE FOLLOWING REQUIREMENTS:
  - FOUNDATIONS:
    - MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS,  $f_c = 4000$  psi
    - MAXIMUM WATER-CEMENTITIOUS MATERIAL RATIO,  $w/cm = 0.50$
    - AIR-ENTRAINED WITH 5% AIR CONTENT (+/- 1.5%)
  - EXTERIOR EXPOSED SLABS, WALLS, PIERS, PEDESTALS AND COLUMNS:
    - MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS,  $f_c = 5000$  psi
    - MAXIMUM WATER-CEMENTITIOUS MATERIAL RATIO,  $w/cm = 0.45$
    - AIR-ENTRAINED WITH 5% AIR CONTENT (+/- 1.5%)
  - INTERIOR SLABS, WALLS, PIERS, PEDESTALS AND COLUMNS:
    - MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS,  $f_c = 4000$  psi
    - MAXIMUM WATER-CEMENTITIOUS MATERIAL RATIO,  $w/cm = 0.50$
    - AIR-ENTRAINED = N/A
- THE CONTRACTOR SHALL SUBMIT CONCRETE MIX DESIGNS TO THE ENGINEER OF RECORD FOR APPROVAL PRIOR TO PLACEMENT OF ANY CONCRETE STRUCTURES.
- THE CONTRACTOR SHALL TAKE SAMPLES FOR STRENGTH TESTS OF EACH CLASS OF CONCRETE PLACED EACH DAY. SAMPLES FOR STRENGTH TESTS SHALL BE TAKEN NOT LESS THAN ONCE PER DAY, NOR LESS THAN ONCE FOR EACH 150 yd<sup>3</sup> OF CONCRETE, NOR LESS THAN ONCE FOR EACH 5000 ft<sup>2</sup> OF SURFACE AREA FOR SLABS OR WALLS. THREE 4x8-INCH CYLINDERS SHALL BE TESTED AT SEVEN DAYS AND 28 DAYS FOR EACH SAMPLE TAKEN.
- REINFORCING BARS SHALL BE DEFORMED BARS CONFORMING TO THE REQUIREMENTS OF ASTM A615, LATEST EDITION, GRADE 60 ( $f_y = 60$  ksi).
- DETAILS AND DETAILING OF CONCRETE REINFORCEMENT SHALL BE IN ACCORDANCE WITH THE "ACI DETAILING MANUAL," REPORTED BY ACI COMMITTEE 315. THE CONTRACTOR SHALL SUBMIT REINFORCEMENT SHOP DRAWINGS TO THE ENGINEER OF RECORD FOR REVIEW AND APPROVAL.
- PLACEMENT OF REINFORCEMENT BARS IN FOOTINGS, WALLS AND COLUMNS SHALL BE EVENLY SPACED WITHIN THE STRUCTURE. DRIVING OR PUSHING DOWELS INTO WET CONCRETE IS PROHIBITED.
- CONCRETE COVER FOR REINFORCEMENT SHALL NOT BE LESS THAN THE FOLLOWING:
  - CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH.....3"
  - CONCRETE EXPOSED TO EARTH OR WEATHER:
    - #6 THROUGH #18 BARS.....2"
    - #5 BAR, W31 OR D31 WIRE, AND SMALLER.....1-1/2"
  - CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH GROUND:
    - SLABS, WALL, JOISTS:
      - #14 BAR AND #18 BARS.....1-1/2"
      - #11 BAR AND SMALLER.....3/4"
    - BEAMS, COLUMNS:
      - PRIMARY REINFORCEMENT, TIES, STIRRUPS, SPIRALS.....1-1/2"
- CONTINUOUS UNCOATED REINFORCEMENT OF DEFORMED BARS NOT LARGER THAN #11 MAY BE LAPPED AT SPLICES. THE MINIMUM LAP LENGTH SHALL BE AS REQUIRED FOR CLASS A OR CLASS B SPLICE, BUT NOT LESS THAN 12 INCHES ( $f_c = 4000$  psi).
  - CLASS A SPLICE = (1.0) $l_d$ 
    - #6 AND SMALLER BARS AND DEFORMED WIRES.....38d<sub>b</sub>
    - #7 AND LARGER BARS.....47d<sub>b</sub>
  - CLASS B SPLICE = (1.3) $l_d$ 
    - #6 AND SMALLER BARS AND DEFORMED WIRES.....49d<sub>b</sub>
    - #7 AND LARGER BARS.....62d<sub>b</sub>
- CONCRETE FOUNDATIONS SHALL NOT BE PLACED ON FROZEN GROUND SURFACE OR PLACED IN WATER. THE CONTRACTOR SHALL USE A DEWATERING POINT SYSTEM, AS NECESSARY.
- ALL NORMAL STRENGTH CONCRETE SHALL BE MAINTAINED ABOVE 50°F AND IN A MOIST CONDITION FOR A MINIMUM OF SEVEN DAYS AFTER PLACEMENT BEFORE ANY EXTERNAL LOADS CAN BE APPLIED.
- CONCRETE NOTED AS HIGH-EARLY STRENGTH SHALL BE MAINTAINED ABOVE 50°F AND IN A MOIST CONDITION FOR A MINIMUM OF THREE DAYS AFTER PLACEMENT BEFORE ANY EXTERNAL LOADS CAN BE APPLIED.
- THE CONTRACTOR SHALL BE RESPONSIBLE TO DESIGN, FURNISH AND PLACE ALL TEMPORARY OR PERMANENT SHORING TO PROTECT EXCAVATIONS, EXISTING STRUCTURES, AND UTILITIES ADJACENT TO THE SITE. DETAILED INFORMATION ON FORMWORK FOR CONCRETE IS GIVEN IN THE "GUIDE TO FORMWORK FOR CONCRETE," REPORTED BY ACI COMMITTEE 347.
- THE CONTRACTOR SHALL PROVIDE ALL NECESSARY SHORING REQUIRED TO RETAIN THE STABILITY OF THE STRUCTURE WHILE REPAIRS AND REHABILITATION TAKE PLACE.
- THE CONTRACTOR SHALL PROVIDE ALL NECESSARY LABOR AND MATERIALS FOR UNDERPINNING REQUIREMENTS WHEN PLACING FOOTINGS NEXT TO OR BELOW EXISTING ADJACENT STRUCTURES, AS APPLICABLE.
- NEATLY FORMED EARTH TRENCHES MAY BE PERMITTED FOR CASTING GRADE BEAMS WHERE SOIL CONDITIONS DO NOT REQUIRE FORMWORK. THE CONTRACTOR SHALL VERIFY SOIL CONDITIONS WITH A LICENSED GEOTECHNICAL ENGINEER AND OBTAIN APPROVAL BY THE ENGINEER OF RECORD PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL PLACE THESE STRUCTURES NEATLY WITHIN ACI 301 DIMENSION TOLERANCES, WITHOUT CONCRETE OVERPOUR SHELVES, AND SUCH THAT ALL REINFORCEMENT COVER AND SPACING REQUIREMENTS ARE PROVIDED.
- EARTH FORMED SPREAD AND CONTINUOUS STRIP FOOTINGS ARE PROHIBITED.
- SLOPE SLABS DOWN 1/4 INCH PER FOOT TO ALL FLOOR DRAINS.
- PROVIDE 2 - #4 x 3'-0" TOP AND BOTTOM AT 45° ANGLE AT ALL REENTRANT CORNERS IN CONCRETE SLAB. PROVIDE THE BOTTOM LAYER OF REINFORCEMENT FOR SLABS GREATER THAN OR EQUAL TO SIX INCHES THICK.
- PROVIDE 4 - #4 x 3'-0" AT ONE INCH CLEAR FROM TOP OF SLAB AT ALL DISCONTINUOUS CONTRACTION OR CONSTRUCTION JOINTS.
- EXPANSION ANCHORS SHALL BE PLATED CARBON STEEL TORQUE CONTROLLED, WEDGE-TYPE MECHANICAL EXPANSION ANCHORS INSTALLED IN HARDENED CONCRETE, IN ACCORDANCE WITH MANUFACTURER SPECIFICATIONS, UNLESS NOTED OTHERWISE.
- ADHESIVE ANCHORS SHALL BE AN ICC-ES APPROVED POST-INSTALLED SYSTEM FOR USE IN HARDENED, CRACKED AND UNCRACKED NORMAL WEIGHT CONCRETE HAVING A SPECIFIED COMPRESSIVE STRENGTH  $f_c$  OF 2500 psi TO 8500 psi. THE SYSTEM SHALL CONSIST OF HIGH-STRENGTH STRUCTURAL ADHESIVE, ANCHOR ELEMENTS (CONTINUOUSLY THREADED RODS OR DEFORMED STEEL REINFORCING BARS), AND NORMAL WEIGHT CONCRETE. ADHESIVE ANCHORS SHALL BE INSTALLED PER MANUFACTURER SPECIFICATIONS UTILIZING THE ANCHOR ELEMENT SIZE AND MINIMUM EFFECTIVE EMBEDMENT INDICATED ON THE DRAWINGS. ADHESIVE ANCHORS SHALL BE INSTALLED IN CONCRETE HAVING A MINIMUM AGE OF 21 DAYS AT TIME OF ANCHOR INSTALLATION.
- CONTRACTION JOINTS SHALL BE LOCATED ALONG COLUMN LINES, WITH INTERMEDIATE JOINTS LOCATED AT EQUAL SPACES BETWEEN COLUMN LINES, UNLESS OTHERWISE NOTED. CONTRACTION JOINT SPACING SHALL NOT EXCEED 30 TIMES THE SLAB THICKNESS, UNLESS OTHERWISE APPROVED BY THE ENGINEER OF RECORD.
- ISOLATION JOINTS SHALL BE PLACED BETWEEN THE SLAB AND ADJOINING BUILDING ELEMENTS AS DETAILED AND OTHERWISE NOTED. ISOLATION JOINTS SHALL BE PLACED AT JUNCTIONS WITH WALLS, COLUMNS, EQUIPMENT FOUNDATIONS, FOOTINGS, OR OTHER POINTS OF RESTRAINT SUCH AS DRAINS, MANHOLES, SUMPS, AND STAIRWAYS.
- EXPANSION AND ISOLATION JOINT MATERIAL TO BE PREFORMED, FLEXIBLE CLOSED CELL FOAM PLANK THE FULL THICKNESS OF THE SLAB.
- VAPOR BARRIER TO BE ASTM E1745, CLASS A PLASTIC SHEET VAPOR BARRIER WITH A MINIMUM THICKNESS OF 10 MILS AND JOINT TAPPED NOT LESS THAN SIX INCHES, UNLESS OTHERWISE SPECIFIED BY ARCHITECTURAL SPECIFICATIONS.

## General Notes

- ALL CONSTRUCTION SHALL CONFORM WITH THE PROVISIONS OF THE CURRENTLY ADOPTED IBC, OSHA, AND ALL STATE AND LOCAL CODES AND THEIR SUPPLEMENTS. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL OR OTHER GOVERNING BODIES' CODES. ADDITIONALLY, ALL WORK SHALL BE COMPLETED IN ACCORDANCE WITH APPLICABLE INDUSTRY STANDARDS OR GUIDELINES AND CONFORM WITH AIA DOCUMENT A201 "GENERAL CONDITIONS OF THE CONTRACT FOR CONSTRUCTION".
- THE CONTRACTOR SHALL SUPPLY ALL MATERIAL SAFETY DATA SHEETS (MSDS) FOR CHEMICALS BROUGHT ONTO THE SITE.
- SHOP DRAWINGS, PRODUCT DATA, SAMPLES, AND SIMILAR SUBMITTALS ARE NOT PART OF THE CONTRACT DOCUMENTS. THE DESIGN PROFESSIONAL OF RECORD'S REVIEW AND APPROVAL OF SUCH SUBMITTALS IS STRICTLY FOR THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS. REVIEW OF SUCH SUBMITTALS IS NOT CONDUCTED FOR THE PURPOSE OF DETERMINING THE ACCURACY AND COMPLETENESS OF OTHER DETAILS SUCH AS DIMENSIONS AND QUANTITIES, OR FOR SUBSTANTIATING INSTRUCTIONS FOR INSTALLATION OR PERFORMANCE OF THE EQUIPMENT OR SYSTEMS, ALL OF WHICH REMAIN THE RESPONSIBILITY OF THE CONTRACTOR. THE DESIGN PROFESSIONAL OF RECORD'S REVIEW OF THE CONTRACTOR'S SUBMITTALS SHALL NOT RELIEVE THE CONTRACTOR OF THE OBLIGATIONS UNDER AIA DOCUMENT A201, SECTIONS 3.3, 3.5, AND 3.12 OF AIA A201. THE DESIGN PROFESSIONAL OF RECORD'S REVIEW SHALL NOT CONSTITUTE APPROVAL OF SAFETY PRECAUTIONS OR OF ANY CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, OR PROCEDURES. THE DESIGN PROFESSIONAL OF RECORD'S APPROVAL OF A SPECIFIC ITEM SHALL NOT INDICATE APPROVAL OF AN ASSEMBLY OF WHICH THE ITEM IS A COMPONENT.
- THE CONTRACTOR'S SUBMITTAL OF SHOP DRAWINGS, SAMPLES, AND SIMILAR SUBMITTALS REPRESENTS TO THE OWNER AND DESIGN PROFESSIONAL OF RECORD THAT THE CONTRACTOR HAS (1) REVIEWED AND APPROVED THEM, (2) DETERMINED AND VERIFIED MATERIALS, FIELD MEASUREMENTS AND FIELD CONSTRUCTION CRITERIA RELATED THERETO, OR WILL DO SO, AND (3) CHECKED AND COORDINATED THE INFORMATION CONTAINED WITHIN SUCH SUBMITTALS WITH THE REQUIREMENTS OF THE WORK AND OF THE CONTRACT DOCUMENTS.
- THE CONTRACTOR SHALL FIELD CHECK AND VERIFY ALL DIMENSIONS AND ELEVATIONS OF EXISTING/PREVIOUSLY PHASED WORK PRIOR TO THE START OF FABRICATION AND CONSTRUCTION. NOTIFY DESIGN PROFESSIONAL OF RECORD OF ANY DISCREPANCIES.
- ALL DIMENSIONS ARE TO FACE OF MASONRY, FACE OF CONCRETE, FACE OF EXISTING WALL AND/OR FACE OF NEW FRAMING. STRUCTURAL STEEL FRAMING DIMENSIONS ARE CENTER LINE DIMENSIONS.
- INDICATED DIMENSIONS ARE TAKEN FROM CASUAL FIELD OBSERVATIONS AND EXISTING DRAWINGS. CONTRACTOR TO VERIFY ALL DIMENSIONS IN FIELD PRIOR TO CONSTRUCTION. CONTRACTOR TO NOTIFY DESIGN PROFESSIONAL OF RECORD OF ANY DISCREPANCIES. ALL CHANGES TO THE WORK SHALL BE APPROVED BY THE DESIGN PROFESSIONAL OF RECORD AND OWNER PRIOR TO PROCEEDING.
- THE CONTRACTOR SHALL SECURE ALL NECESSARY LOCAL PERMITS REQUIRED FOR ITS WORK.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING THE LOCATION OF ANY UTILITIES IN THE VICINITY OF THE CONSTRUCTION (UNDERGROUND OR OTHERWISE) AND SHALL COMPLETE THE CONSTRUCTION IN A MANNER WHICH WILL PREVENT DAMAGE TO THEM. SHOULD ANY DAMAGE TO SUCH UTILITIES OCCUR, THE CONTRACTOR SHALL REPAIR THE DAMAGE AT ITS OWN EXPENSE AND TO THE SATISFACTION OF THE OWNER.
- COORDINATE ALL WORK WITH MECHANICAL, ELECTRICAL, CIVIL, STRUCTURAL, ARCHITECTURAL DRAWINGS AND TRADES. VERIFY EXACT SIZE AND LOCATION OF ALL WALL, FLOOR AND ROOF OPENINGS REQUIRED OF THESE AND OTHER TRADES.
- THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING CONSTRUCTION EFFORTS OF ALL SUB-CONTRACTORS. FAILURE TO ANTICIPATE CHANGES OR MODIFICATIONS SHALL NOT BE THE BASIS FOR ADDITIONAL COST REQUESTS.
- CONTRACTORS SHALL COORDINATE THEIR WORK WITH THE OTHER TRADES. EXTRAS WILL NOT BE GIVEN FOR FORESEEABLE WORK COORDINATION.
- REFER TO EQUIPMENT SCHEDULES AND SPECIFICATIONS FOR INSTALLATION REQUIREMENTS.
- PROTECT ALL EQUIPMENT, BUILDING, AND PAVEMENTS, NEW AND EXISTING, FROM DEBRIS AND DAMAGE. FINAL CLEAN-UP OF ALL EQUIPMENT, BUILDINGS AND PAVEMENTS SHALL BE COMPLETED PRIOR TO SUBSTANTIAL COMPLETION.

## Structural Design Criteria

- RISK CATEGORY II; MAIN BUILDING AND COLD STORAGE
  - SNOW IMPORTANCE FACTOR,  $I_s = 1.00$
  - ICE IMPORTANCE FACTOR - THICKNESS,  $I_i = 1.00$
  - ICE IMPORTANCE FACTOR - WIND,  $I_w = 1.00$
  - SEISMIC IMPORTANCE FACTOR,  $I_e = 1.00$
- RISK CATEGORY I: SALT BARN
  - DESIGN ENGINEER TO DETERMINE MINIMUM UNIFORM SNOW LOAD AND OTHER CRITERIA
- FLOORS, ROOFS, AND OTHER SIMILAR SURFACES ARE DESIGNED TO SUPPORT SAFELY THE LISTED UNIFORMLY DISTRIBUTED LIVE LOAD (psf) OR THE CONCENTRATED LOAD (lb), WHICHEVER PRODUCES THE GREATER LOAD EFFECTS.
- ROOF LIVE LOAD,  $L_r = 20$  psf / 300 lb
- FLOOR LIVE LOAD,  $L$ :
  - IT ROOM/OFFICE = 50 psf / 2000 lb
  - LOBBIES, MEETING ROOMS, CORRIDORS = 100 psf / 2000 lb
  - MEZZANINE = 125 psf
  - STAIRS = 100 psf / 300 lb
  - PARTS AND SIGNAGE = 100 psf / 2000 lb
  - MAINTENANCE AREA = 250 psf / 8,000 lb (4.5 in BY 4.5 in AREA)
- CONCENTRATED LOADS ON FLOORS, ROOFS, AND SIMILAR SURFACES ARE ASSUMED TO BE UNIFORMLY DISTRIBUTED OVER AN AREA 2.5 ft BY 2.5 ft.
- CONCENTRATED LOADS ON STAIR TREADS ARE ASSUMED TO BE UNIFORMLY DISTRIBUTED OVER AN AREA 2 in BY 2 in.
- GROUND SNOW LOAD,  $p_g = 25$  psf
- MINIMUM UNIFORM SNOW LOAD,  $p_u = 1p_g = 20$  psf
- SNOW EXPOSURE FACTOR,  $C_e = 0.9$
- THERMAL FACTOR:  
ADMIN. /MAINT. /TRUCK PARKING:  $C_t = 1.0$   
SALT BARN / COLD STORAGE:  $C_t = 1.2$
- FLAT ROOF SNOW LOAD,  $p_s = (0.7)C_eC_dI_p$   
ADMIN. /MAINT. /TRUCK PARKING:  $p_s = 16.8$  psf  
SALT BARN / COLD STORAGE:  $p_s = 18.9$  psf
- ROOF SLOPE FACTOR,  $C_s = 1.0$
- SLOPED ROOF SNOW LOAD,  $p_s = C_d p_g$   
ADMIN. /MAINT. /TRUCK PARKING:  $p_s = 16.8$  psf  
SALT BARN / COLD STORAGE:  $p_s = 18.9$  psf
- UNBALANCED SNOW LOAD, DRIFTING SNOW LOAD, AND SLIDING SNOW LOAD PER ASCE 7:
  - SURCHARGE LOAD DUE TO DRIFTING SHALL BE ADDED TO THE BALANCED SNOW LOAD,  $p_s$ , AS A STRIP RUNNING PARALLEL TO THE EAVES WITH A MAXIMUM INTENSITY AT THE EVE EDGE AND TAPERING LINEARLY TO 0 psf ACROSS THE STRIP:
    - ADMIN. - NORTH EDGE: 38 psf MAX, OVER 8'-10" STRIP
    - ADMIN. - EAST EDGE: 78 psf MAX, OVER 18'-0" STRIP
    - ADMIN. - SOUTH EDGE: 65 psf MAX, OVER 15'-0" STRIP
    - ADMIN. - WEST EDGE: 42 psf MAX, OVER 9'-7" STRIP
  - LOWER ROOFS
  - NO SLIDING SNOW LOADS APPLY.
- RAIN-ON-SNOW SURCHARGE = 0 psf
- DESIGN WIND SPEED,  $V = 115$  mph
- WIND EXPOSURE CATEGORY C
- INTERNAL PRESSURE COEFFICIENT,  $GCF_p = +0.18$
- MAPPED SPECTRAL RESPONSE ACCELERATION PARAMETERS:
  - SHORT PERIODS,  $S_s = 0.117g$
  - 1-SECOND PERIODS,  $S_1 = 0.063g$
- SITE CLASS D
- DESIGN SPECTRAL RESPONSE ACCELERATION PARAMETERS:
  - SHORT PERIODS,  $S_{DS} = 0.124g$
  - 1-SECOND PERIODS,  $S_{D1} = 0.101g$
- SEISMIC DESIGN CATEGORY B
- SEISMIC FORCE-RESISTING SYSTEM: STEEL SYSTEM NOT SPECIFICALLY DETAILED FOR SEISMIC RESISTANCE.
- RESPONSE MODIFICATION COEFFICIENT,  $R = 3$
- SEISMIC ANALYSIS BY EQ. **Soil Notes** FORCE PROCEDURE.


- BUILDING AREA FOUNDATIONS AND FLOOR SLABS ARE TO BE CONSTRUCTED BY CONVENTIONAL METHODS OVER SOILS IMPROVED BY THE INSTALLATION OF RAMMED AGGREGATE PIERS.
- THE CONTRACTOR SHALL HIRE A SPECIALTY CONTRACTOR WITH A PROVEN RECORD OF PERFORMANCE THAT DELIVERS THEIR WORK ON A DESIGN-BUILD BASIS TO DESIGN AND INSTALL THE RAMMED AGGREGATE PIERS. THE SPECIALTY CONTRACTOR SHALL COORDINATE THE SIZE, DEPTH, AND SPACING OF THE PIERS WITH THE FOUNDATION PLANS AND LOADING SCHEDULES. SEALED RAMMED AGGREGATE PIER PLANS, DETAILS AND SUPPORTING CALCULATIONS SHALL BE SUBMITTED FOR REVIEW TO THE ENGINEER OF RECORD.
- FOUNDATIONS ARE DESIGNED FOR A MINIMUM BEARING CAPACITY OF 2500 psf FOR SPREAD FOOTINGS AND 2000 psf FOR STRIP FOOTINGS. FLOOR SLABS ARE DESIGNED FOR A STIFFNESS RATIO,  $R_s = k_d/k_{eq} = 20$ .
- THE CONTRACTOR SHALL HIRE A REGISTERED GEOTECHNICAL ENGINEER TO INSPECT AND APPROVE EXCAVATION SUBGRADE, BEARING SURFACES, BACKFILL MATERIAL, AND BACKFILL COMPACTION. THE REGISTERED GEOTECHNICAL ENGINEER SHALL VERIFY THAT THE BEARING CAPACITY AND MODULUS OF SUBGRADE REACTION OF THE SOIL MEETS OR EXCEEDS THE MINIMUM BEARING CAPACITY AND MODULUS OF SUBGRADE REACTION UTILIZED FOR THE FOUNDATION DESIGN. SHOULD CONDITIONS PROVE OTHERWISE, CONTACT THE ENGINEER OF RECORD AND PROCEED AS DIRECTED.
- REFER TO THE GEOTECHNICAL REPORT FOR INFORMATION REGARDING SITE PREPARATION, FOUNDATION EXCAVATIONS, STRUCTURAL BACK FILL, COMPACTION REQUIREMENTS, SUITABLE BACK FILL MATERIAL, AND GROUNDWATER. THE GROUNDWATER LEVEL FOR THIS PROJECT IS HIGH.
- EXTERIOR/UNHEATED AREA SLABS PLACED DIRECTLY UPON SOILS SUBJECT TO HEAVING AND SUBSEQUENT SETTLEMENT DUE TO FREEZE/THAW CYCLES SHALL BE LIMITEDLY UNDERCUT OF FROST SUSCEPTIBLE MATERIALS TO A DEPTH OF ONE TO TWO FEET BELOW THE SLAB, AND REPLACEMENT WITH WELL GRADED, PROPERLY PLACED AND COMPACTED GRANULAR SOILS.
- DEWATERING WILL BE REQUIRED DURING CONSTRUCTION AND UNTIL THE CONCRETE FOUNDATIONS ARE SET. SEE GEOTECHNICAL REPORT.
- THE CONTRACTOR SHALL PROVIDE ALL PROTECTION REQUIRED SO AS TO SAFEGUARD EXISTING UTILITIES.
- LOCATE ALL UNDERGROUND UTILITIES PRIOR TO EXCAVATION.
- UNLESS OTHERWISE SPECIFIED BY A LICENSED GEOTECHNICAL ENGINEER, THE CONTRACTOR SHALL COMPACT ALL STRUCTURAL FILL SUPPORTING FOUNDATIONS OR SLABS-ON-GRADE TO 100% OF THE MAXIMUM STANDARD PROCTOR DRY DENSITY (ASTM D-698) WITH MAXIMUM LIFTS OF 8 INCHES OR LESS. FILLS ADJACENT TO FOUNDATIONS AND OVER FOUNDATIONS SHALL BE COMPACTED TO 95% OF MAXIMUM STANDARD PROCTOR DRY DENSITY.



**MARTIN RILEY**  
architects+engineers

221 West Baker Street  
Fort Wayne, Indiana 46802

pho 260.422.7994  
fax 260.426.2067



ALL DESIGN, ENGINEERING, MANAGEMENT AND/OR SERVICES REPRESENTED BY THIS DRAWING ARE OWNED BY, AND THE PROPERTY OF, MARTIN RILEY, INC. ANY REUSE, REPRODUCTION, MODIFICATION, ALTERATION, ADAPTATION, OR TRANSMISSION OF ANY PART OF THIS DRAWING WITHOUT THE WRITTEN PERMISSION OF MARTIN RILEY, INC. IS STRICTLY PROHIBITED. THE USER OF THIS DRAWING SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES AND FOR OBTAINING ALL NECESSARY INSURANCE COVERAGE. THE USER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES AND FOR OBTAINING ALL NECESSARY INSURANCE COVERAGE. THE USER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES AND FOR OBTAINING ALL NECESSARY INSURANCE COVERAGE.

REVISION	DATE
1	ADDENDUM 1
2024-06-12	
DRAWN BY:	NMS
COMMISSION NUMBER:	F22146
REVIEWED BY:	JLB
DATE:	2024-05-24

**S001**

STRUCTURAL  
SPECIFICATIONS

New Construction Work for :  
**Porter County Highway Department -  
Central Facility**

1955 IN-2  
Valparaiso, IN 46385