







- EQUIPMENT SCHEDULE**
- Gas fired condensing furnace, Input 100,000 BTU/hr. Output 93,000 BTU/hr.
 F1 Fan 385 CFM @ .6" ESP. Motor 3/4 H.P. 115V. 1φ 60 HZ. Provide with 7 (seven) days commercial programmable thermostat termination kit & complete control package. Unit shall be Model 350 MAY by Bryant Mfr. or approved equal.
- Exhaust Fan, in line belt driven 380 CFM. .50" S.P. Motor 1/4 H.P. 115V. 1PH. 60 HZ.
 EF1 Provide angles, supports, vibration isolators, etc. to support unit. Fan shall be Model B 50-4 by Greenheck Mfg. or approved equal.
- Exhaust Fan in line belt driven 1200 CFM. .75" S.P. Motor 1/2 H.P. 208V 1PH 60 HZ.
 EF2 Provide angles, supports, vibration isolators etc. to support unit. Fan shall be Model B 50-4 by Greenheck Mfg. or approved equal.
- Exhaust Fan in line belt driven 300 CFM. .50" S.P. Motor 1/4 H.P. 115V 1PH 60 HZ.
 EF3 Provide angles, supports, vibration isolators etc. to support unit. Fan shall be Model B 50-4 by Greenheck Mfg. or approved equal.
- Wall mounted electric unit heater 2000 Watts 208V 1PH. 60 HZ.
 WH Provide integrally mounted thermostat. Unit shall be Model 021-A2-AT by Trane Co. or approved equal.
- Electric Unit Heater 5 KW, 208 V, 1 PH. 60 HZ. Provide integrally mounted thermostat & ceiling mounted support.
- H.V. PLAN NOTES**
- 1" vent pipe terminate with discharge kit supplied by Unit Mfg.
 - 2" Combustion Air Pipe terminate with intake kit supplied by Unit Mfg.
 - 12" x 8" outdoor air intake Louver. Bottom & 7/4" AFF. Provide sheet metal plenum.
 - 2" PVC combustion air pipe
 - 2" CPVC Vent pipe
 - 6" x 6" Transfer air grille connected by 6" x 6" ductwork
 - 10" x 8" Exhaust duct terminate above roof with gooseneck.
 - 18" x 10" Exhaust duct terminate above roof with gooseneck.
 - 8" x 8" Exhaust duct terminate above roof with gooseneck.
 - 8" x 6" ER 180 CFM each Typical of 2
 - 32" x 24" Outdoor air Louver. Bottom & 7/4" AFF.
 - Run ductwork above ceiling
 - 3/4" Condensate drain terminate over nearest floor drain.
 - All outdoor motorized dampers & exhaust fans shall be sized on unoccupied time from ready on 7 day programmable thermostat.
 - Insulate all supply air ductwork with one inch thick fiberglass insulation.
 - All grilles, registers & diffusers located in ceilings shall be provided with radiation damper & fire blankets see detail this sheet.



GIBALTAR DESIGN
ARCHITECTURE • ENGINEERING • INTERIOR DESIGN

CONTINUATION OF
FACILITIES IMPROVEMENTS
LAWRENCE CENTRAL
HIGH SCHOOL FOR
MSD LAWRENCE TOWNSHIP

GIBALTAR DESIGN
9102 N. Meridian St., Ste. 300
Indianapolis, IN 46260
Home: 317.580.3777 Fax: 317.580.3778
Email: info@gibaltardesign.com

PROJECT 97.01.60.15
DATE 3/25/98
COORDINATED BY
DRAWN BY JHS
CHECKED BY

COPYRIGHT NOTICE:
THE CONCEPT, DESIGN, PLANS, DETAILS, ETC. SHOWN ON THIS DOCUMENT ARE THE PROPERTY OF GIBALTAR DESIGN AND WERE CREATED FOR USE ON THIS SPECIFIC PROJECT. NONE OF THIS INFORMATION SHALL BE USED BY ANY PERSON OR FIRM FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF GIBALTAR DESIGN. THE OWNER MAY RETAIN COPIES FOR INFORMATION AND REFERENCE IN CONNECTION ONLY WITH THE PROJECT.

REVISIONS

MARK	DATE	ISSUED FOR
4-17-98	PLAN REVIEW	

DRAWING

PROJECT
**FACILITIES IMPROVEMENTS AT
LAWRENCE CENTRAL HIGH SCHOOL**

© GIBALTAR DESIGN SHEET